


FBS Flat Busbar Support – FBS400A (551350)



- Support for threaded busbars
- Three phase with neutral circuit
- Plastic positioning pin for bar location
- Adjusts quickly to accommodate multiple busbar widths
- Protection screen can be fixed using spacers
- A ground can be mounted on either side
- Halogen free



Part Number	FBS400A
Article Number	551350
Material	Glass Fibre Reinforced Polyamide Steel
Finish	Electrogalvanized
Max Working Voltage, IEC (Ui)	1,000 VAC 1,500 VDC
Working Temperature	-40 to 130 °C
Typical Application Current Rating	160 – 400 A
Complies With	IEC® 61439.1
Flammability Rating	UL® 94V-0
Busbar Width	15 mm 20 mm 32 mm
Busbar Thickness	5 mm
Height (H)	34 mm
Width (W)	465 mm
A	450 mm
B	300 mm
C	18 mm
D	26 mm
E	50 mm
X	6 x 8 mm
Certifications	CE EAC 8546901000 (Russian Federation) IEC 61439-1 Busbar Supports

Part Number	FBS400A
	RoHS
Standard Packaging Quantity	1 pc
UPC	78285667784
EAN-13	3479775513508

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2016 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.