


U.I. Lapp GmbH	PRODUCT INFORMATION	
	SKINDICHT® MR-M ATEX	07.11.2014

Enables the use of cable glands with smaller connection threads than the existing threaded holes

With guide notch for O-ring

Assembling with a wrench



Application range

Equipment group II / Category 2G+1D

Devices, machines and apparatus

For mobile applications in offshore and marine industries

Chemical and petrochemical industry

Product Make-up

Metric connection thread acc. to EN 50262

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

Approvals:

CE 0637 Ex II 2G
Ex eb IIC
Ex II 1D Ex ta IIIC
IECEX IBE 13.0028X

Classification:

ETIM 5.0 Class-ID: EC000441
ETIM 5.0 Class-Description: cable screw gland

Material:

Body: nickel-plated brass
O-ring: NBR

Temperature range:

-30°C to +90°C

Product Management	Document: LAPP_PRO1035EN.pdf	1 / 2
--------------------	------------------------------	-------



Part number	Thread/ male M1	Thread/ female M2	Overall height (mm)	Thread length/ D (mm)	Outer Ø (mm)	Pieces / PU
SKINDICHT® MR-M ATEX						
52104570	16 x 1.5	12 x 1.5	10.5	5.0	19.0	50
52104571	20 x 1.5	16 x 1.5	13.0	6.0	24,5	50
52104572	25 x 1.5	20 x 1.5	15.0	7.0	30,1	25
52104573	32 x 1.5	25 x 1.5	16.5	8.0	37,2	25
52104574	40 x 1.5	32 x 1.5	16.5	8.0	45,6	10
52104575	50 x 1.5	40 x 1.5	19.5	10.0	55,3	5
52104576	63 x 1.5	50 x 1.5	18.5	8.5	71,3	5