


U.I. Lapp GmbH	<b>PRODUCT INFORMATION</b>	
	<b>SKINDICHT® ME-M ATEX</b>	07.11.2014

Enables the use of cable glands with larger connection threads than the existing threaded holes  
 With guide notch for O-ring  
 Assembling with a wrench



Assembly time



Space requirement



Reliability

### Application range

Equipment group II / Category 2G+1D  
 Devices, machines and apparatus  
 For mobile applications in offshore and marine industries  
 Chemical and petrochemical industry

### Product Make-up

Metric connection thread acc. to EN 50262

### Remark

Photographs are not to scale and do not represent detailed images of the respective products.

### Technical Data

Approvals:	CE 0637 Ex II 2G Ex eb IIC Ex II 1D Ex ta IIIC IECEX IBE 13.0028X
Classification:	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: cable screw gland
Material:	Body: nickel-plated brass O-ring: NBR
Temperature range:	-30°C to +90°C

Product Management	Document: LAPP_PRO1038EN.pdf	1 / 2
--------------------	------------------------------	-------



Part number	Thread/ male M1	Thread/ female M2	Overall height (mm)	SW (mm)	Outer thread length (mm)	Outer Ø (mm)	Pieces / PU
SKINDICHT® ME-M ATEX							
52104580	12 x 1.5	16 x 1.5	17.0	18	5	20.0	50
52104581	16 x 1.5	20 x 1.5	20.0	22	6	24.0	50
52104582	20 x 1.5	25 x 1.5	22.5	27	6.5	30.0	50
52104583	25 x 1.5	32 x 1.5	21.5	34	6.5	37,7	25
52104584	32 x 1.5	40 x 1.5	23.0	42	7	46.0	25
52104585	40 x 1.5	50 x 1.5	26.0	54	8	59.0	25
52104586	50 x 1.5	63 x 1.5	32.0	67	9	73.0	10