


U.I. Lapp GmbH	PRODUCT INFORMATION	
	SKINDICHT® SR	07.11.2014

Reliable bending and anti-kink protection
High strain relief
Robust
For cables with large outer diameters
High degree of protection



Wide clamping range



Optimum strain relief



Robust

Application range

Cables for electrical appliances and machinery that are moved under normal use must be protected against excessive bending as required in accordance with VDE 0700-1

Handheld device
Portable equipment
Building sites
Moving machine parts

Product Make-up

PG connection thread

Note

Counter nut to be used: SKINDICHT® SM
For EMC version, refer to SKINDICHT® SRE

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

Caution:	The installation dimensions can be found in appendix T21
On request:	Available with long connection thread
Classification:	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: cable screw gland
Material:	Body: nickel-plated brass O-ring: NBR Anti-kink protection: CR
Protection rating:	IP 65
Temperature range:	-20°C to +80°C


Product Management	Document: LAPP_PRO1089EN.pdf	1 / 3
--------------------	------------------------------	-------

SKINDICHT® SR

07.11.2014

Part number	Article designation / size	Clamping range ØF (mm)	Max. fitting size for installation (mm)	SW1/SW2 mm	Overall length/ C (mm)	Thread length/ D (mm)	Pieces / PU
SKINDICHT® SR							
52000990	SR 07/05	3,5 - 5	23	14 / 15	50.0	5.0	50
52001000	SR 09/07	5,5 - 7	25	17 / 17	52.0	6.0	50
52001010	SR 11/07	5,5 - 7	28	20 / 20	56.0	6.0	25
52001020	SR 11/09	7,5 - 9	28	20 / 20	56.0	6.0	25
52001030	SR 13/09	7,5 - 9	32	22 / 22	62.0	6.5	25
52001040	SR 13/11	9 - 11	32	22 / 22	62.0	6.5	25
52001050	SR 13/13	11 - 13	32	22 / 22	62.0	6.5	25
52001060	SR 16/13	11,5 - 13	35	24 / 24	67.0	6.5	25
52001070	SR 16/15	13 - 15	35	24 / 24	67.0	6.5	25
52001080	SR 21/15	13,5 - 15	46	30 / 30	79.0	7.0	25
52001090	SR 21/17	15 - 17	46	30 / 30	79.0	7.0	25
52001100	SR 21/19	17 - 19	46	30 / 30	79.0	7.0	25
52001110	SR 21/20	18 - 20	46	30 / 30	79.0	7.0	25
52001120	SR 29/20	18 - 20	59	40 / 41	91.0	8.0	10
52001130	SR 29/23	21 - 23	59	40 / 41	91.0	8.0	10
52001140	SR 29/25	23 - 25	59	40 / 41	91.0	8.0	10
52001150	SR 36/26	23 - 26	70	50 / 50	110.0	9.0	5
52001160	SR 36/30	27 - 30	70	50 / 50	110.0	9.0	5
52001170	SR 36/33	30 - 33	70	50 / 50	110.0	9.0	5
52001180	SR 36/35	32 - 35	70	50 / 50	110.0	9.0	5
52001190	SR 42/35	32 - 35	75	57 / 57	114.0	10.0	5
52001200	SR 42/38	35 - 38	75	57 / 57	114.0	10.0	5
52001210	SR 42/40	36 - 40	75	57 / 57	114.0	10.0	5
52001220	SR 48/40	36 - 40	83	64 / 64	119.0	10.0	1
52001230	SR 48/44	40 - 44	83	64 / 64	119.0	10.0	1

U.I. Lapp GmbH	PRODUCT INFORMATION	 LAPP GROUP
	SKINDICHT® SR	07.11.2014



Product Management	Document: LAPP_PRO1089EN.pdf	3 / 3
--------------------	------------------------------	-------