


Product Description

Lateral sealing lips fit automatically around various cable dimensions; Cable-specific seal dimensions are no longer necessary; Large clear opening allows clamping of up to two flat cables; Optimal strain relief; Dimensional adaptability



Application range

- For inserting of flat cables.
- Switch cabinet building
- Conveyor systems
- Pumps
- Elevators

Benefits

- Lateral sealing lips fit automatically around various cable dimensions
- Cable-specific seal dimensions are no longer necessary
- Large clear opening allows clamping of up to two flat cables
- Optimal strain relief
- Dimensional adaptability

Design

- Metric connection thread acc. to EN 50262

Note

- For suitable flat cables, see ÖLFLEX® LIFT F for indoor applications or ÖLFLEX® CRANE F for outdoor applications
- Counter nut to be used SKINDICHT® SM-M

Technical Data

Caution

Installation dimensions see Appendix T21

Range of temperature

-30°C up to +100°C

Material

Body: Nickel plated brass Seal: CR

Article List

Part number	Part designation / size	Flat cable width min./ max.	Min./ max. cable thickness in mm	Pieces / PU
SKINDICHT® SVF-M				
52107320	M 20/16	- / 15	- / 5	25
52107340	M 25/21	9 / 20	3 / 8	25
52107350	M 32/29	14 / 27	4 / 11,5	10
52107360	M 40/36	24 / 34	4 / 11,5	10
52107370	M 50/42	29 / 44	5 / 12	5
52107380	M 63/48	34 / 50	5 / 12	5

Footnote:

Photographs are not to scale and do not represent detailed images of the respective products.