

SKINDICHT® MR-M ATEX

SKINDICHT® MR-M ATEX, reducers, enables the use of cable glands with smaller connection threads than the existing threaded holes



Application range

Equipment group II / Category 2G+1D
 Devices, machines and apparatus
 For mobile applications in offshore and marine industries
 Chemical and petrochemical industry

Benefits

Enables the use of cable glands with smaller connection threads than the existing threaded holes
 With guide notch for O-ring
 Assembling with a wrench

Product Make-up

Metric connection thread acc. to DIN EN 60423
 Basis for technical information EN 50262

Technical Data

Certifications:	CE 0637 Ex II 2G Ex eb IIC Ex II 1D Ex ta IIIC IECEx IBE 13.0028X DIN EN 60079-0/DIN EN 60079-7/DIN EN 60079-31
Classification:	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: Cable screw gland
Material:	Body: nickel-plated brass O-ring: NBR
Temperature range:	-30°C to +90°C

Note

Photographs are not to scale and do not represent detailed images of the respective products.

**SKINDICHT® MR-M ATEX**

Part number	Thread/ male M1	Thread/ female M2	Overall height (mm)	Thread length/ D (mm)	Outer Ø (mm)	Pieces / PU
SKINDICHT® MR-M ATEX						
52104570	16 x 1.5	12 x 1.5	10.5	5.0	19.0	50
52104571	20 x 1.5	16 x 1.5	13.0	6.0	24,5	50
52104572	25 x 1.5	20 x 1.5	15.0	7.0	30,1	25
52104573	32 x 1.5	25 x 1.5	16.5	8.0	37,2	25
52104574	40 x 1.5	32 x 1.5	16.5	8.0	45,6	10
52104575	50 x 1.5	40 x 1.5	19.5	10.0	55,3	5
52104576	63 x 1.5	50 x 1.5	18.5	8.5	71,3	5