

## SKINDICHT® SVRE-M

SKINDICHT® SVRE-M, metric, nickel-plated brass cable gland with variable incised sealing ring and hexagonal fitting



Robust



Reliability

### Application range

Brass cable gland with hexagonal fitting and variable incised sealing ring.

### Benefits

With incised sealing ring for adjustment to several cable diameters  
Fewer sizes need to be kept in stock

### Product Make-up

Metric connection thread acc. to DIN EN 60423  
Basis for technical information EN 50262

### Note

Refer to SKINDICHT® EV for additional accessories  
Counter nut to be used: SKINDICHT® SM-M

### Technical Data

Caution:

The installation dimensions  
can be found in appendix T21

On request:

Available with long connection thread  
Available with VITON® incised ring

Classification:

ETIM 5.0 Class-ID: EC000441  
ETIM 5.0 Class-Description: Cable screw gland

Material:

Body: nickel-plated brass  
Incised seal: CR/NBR

Temperature range:

-20 °C to +80 °C



### Note

Viton® is a registered trademark of DuPont de Nemours  
Photographs are not to scale and do not represent detailed images of the respective products.

**SKINDICHT® SVRE-M**

Part number	Article designation / size	Incised sealing ring ØF (mm)	Max. internal Ø (mm)	Function thread PG	SW1/SW2 mm	Overall length/ C (mm)	Thread length/ D (mm)	Pieces / PU
SKINDICHT® SVRE-M								
52104980	16 x 1,5	5/8	10	9	18 / 15	21,6	5.0	100
52104990	20 x 1,5	7/10/12.5	12	11	22 / 18	23,6	6.0	50
52105000	20 x 1,5	7/10.5/13/16	14	13.5	22 / 20	25,6	6.0	50
52105010	20 x 1,5	8/10.5/13.5/16	15	16	24 / 22	26,6	6.0	50
52105002	25 x 1,5	11/15/18/20	20	21	30 / 28	29,6	7.0	50
52105003	32 x 1,5	19/23/27/31	27	29	40 / 37	32,6	8.0	50
52105004	40 x 1,5	25/28/31/35	34	36	50 / 47	37,6	8.0	20
52105005	50 x 1,5	35.5/39/42.5/46	43	42	57 / 54	42,6	9.0	5
52105006	63 x 1,5	40.5/44/47/50.5	48	48	66 / 60	45,1	10.0	5

## SKINDICHT® SVRE-M

