



UNITRONIC® FD P plus

Highly flexible data cable with PUR jacket and AWM certification for US & Canadian use

Info

- Flexible at low temperatures
- Low capacitance
- Halogen-free



Benefits

- Well-proven and reliable
- Wide temperature range for applications in harsh climatic environments
- UL AWM voltage rating 1000V in case of internal wiring allows for internal laying next to power cables with applied UL rating of 1kV
- In the USA inside of industrial machines, per NFPA 79, 2015 Ed., 12.9.2 (condition 3 under 12.9.2: Through 1 mm² and <16 AWG), but not inside drag chains or on machines since AWM style is limited to internal wiring

Application range

- Highly flexible data cable with PUR outer sheath, meets the highest service life requirements, even under harsh climatic conditions.
- Multifunctional-use, e.g. for packaging industry and storage and retrieval units
- Suitable for use in measuring, control and regulating circuits
- Drag chain use - in case of horizontal installation travel distances up to 100 m
- For use in drag chains: Please respect the assembly guidelines listed in Appendix T3

Product features

- PUR outer sheath, tear and notch-resistant, resistant to mineral oils and abrasion when used in power chains
- Flame retardance ratings: IEC 60332-1-2, FT2 (Horizontal flame test)
- Halogen-free, has low capacitance and is flexible down to -40°C
- Oil-resistant
- Low-adhesive surface, resistant to hydrolysis and microbes, oil resistant

Norm references / Approvals

- Based on VDE 0812
- CULus AWM/ Recognized certification (by UL/ UL file no. for Stuttgart-based U.I. Lapp GmbH: E63634): UL AWM Style 21576 acc. to UL 758 and AWM A/B I/II to CSA C22.2 No. 210-11

Product Make-up

- Extra-fine wire strand made of bare copper wires
- Core insulation: Based on Polyolefin
- Non-woven wrapping
- Outer sheath made of special PUR compound
- Outer sheath colour: grey (RAL 7001)

Technical data

Classification
ETIM 5.0 Class-ID: EC000830
ETIM 5.0 Class-Description: Data cable

Core identification code
DIN 47100, refer to Appendix T9

Mutual capacitance
C/C approx. 60 nF/km

Peak operating voltage
Peak: 250 V (not for power current use or continuous operating voltage to ground above 49VAC or 74VDC)

Inductivity
approx. 0.65 mH/km

Conductor stranding
Stranded, extra-fine wire

Minimum bending radius
Flexing: 5 x outer diameter
Fixed installation: 3 x outer diameter

Test voltage
1500 V

Temperature range
Flexing: -40°C to +80°C
Fixed installation: -40°C to +80°C

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC® FD P plus				
0028650	3 x 0.14	3.9	4.1	25
0028651	4 x 0.14	4.2	5.6	30
0028652	5 x 0.14	4.5	7	34
0028653	7 x 0.14	5.1	9.8	48
0028654	10 x 0.14	6.1	14	60
0028656	18 x 0.14	6.8	25.2	87
0028657	25 x 0.14	8.3	35	120
0028658	2 x 0.25	4.3	5	27
0028659	3 x 0.25	4.5	7.5	32
0028660	4 x 0.25	4.9	10	39
0028662	7 x 0.25	6.1	17.5	61
0028663	10 x 0.25	7.4	25	80
0028664	14 x 0.25	7.5	35	103
0028665	18 x 0.25	8.5	45	125
0028666	25 x 0.25	10.4	62.5	171
0028667	2 x 0.34	4.7	6.8	33
0028668	3 x 0.34	5	10.2	41
0028669	4 x 0.34	5.4	13.6	55
0028670	5 x 0.34	5.9	17	62
0028671	7 x 0.34	6.8	23.8	80
0028672	10 x 0.34	8.5	34	110
0028673	14 x 0.34	8.6	47.6	144
0028674	18 x 0.34	9.7	61.2	175
0028675	25 x 0.34	11.9	85	239

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/ 100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® CLASSIC FD 810 P refer to page 131
- UNITRONIC® FD CP plus refer to page 308

Accessories

- SILVYN® CHAIN
- SMART STRIP stripping tool