




EPIC® H-A 3

H-A inserts with screw termination up to 2.5 mm² wire cross section




Info

- Small power connector for single- or three-phase current
- Easy to assemble due to straight entry of conductors

EPIC® H-A 4

H-A inserts with screw termination up to 2.5 mm² wire cross section



Info

- Insert for three-phase current application with neutral conductor
- Easy to assemble due to straight entry of conductors

Suitable housing

- EPIC® H-A 3 Housings
- Refer to Selection Table A10 to select the required inserts and housings

Benefits

- The small H-A 3 / H-A 4 are used whenever there is minimal space.
- Easy to service screw connection
- Easy cable connection with strait cable entry in the contacts

Application range

- Machine and equipment manufacturing
- Control engineering
- Apparatus construction

Suitable tools

- PEW 8.186 crimping pliers refer to page 1015
- MULTICRIMP 6 crimping pliers
- Kraftform® adjustable torque screwdriver/ Kraftform Kompakt® Set refer to page 1078

Technical data

ETIM ETIM 5.0 Class-ID: EC000438
ETIM 5.0 Class-Description: Contact insert for industrial connectors

Rated voltage (V)
IEC: 400 V
UL: 600 V
CSA: 600 V

Rated impulse voltage
4 kV

Rated current (A)
IEC: 23 A
UL: 10 A
CSA: 10 A

Degree of soiling
3

Contact resistance
1.5 - 4 mohm

Contacts
Copper alloy, hard silver-plated

Number of contacts
EPIC® H-A 3
3 + PE
EPIC® H-A 4
4 + PE

Termination methods
Screw termination: 0.5 - 2.5 mm²
(2.5 mm² with conductor end sleeves depending on the crimping profile)

Stripping length (mm)
6

Cycle of mechanical operation
100

VDE-tested
Certified production control:
VDE-REG. no.: B437
UL-tested:
UL File Number: E75770

Temperature range
-40 °C to +100 °C,
short-term up to +125 °C

Article number	Article description	Contact type	Number of operating contacts	Pieces / PU
H-A 3 screw termination				
10420000	H-A 3 SS	male	1 - 3	10
10421000	H-A 3 BS	female	1 - 3	10
H-A 4 screw termination				
10431000	H-A 4 SS	male	1 - 4	10
10432000	H-A 4 BS	female	1 - 4	10

Photographs are not to scale and do not represent detailed images of the respective products.