



## NSGAFÖU 1.8/3 kV

Flexible single-conductor rubber cable with 1.8/3 kV rated voltage



### Info

- Public transport
- Control panel internal wiring

### Benefits

- Arrangements made of single-conductor cables NSGAFÖU in accordance with VDE 0250 Part 602 with nominal voltage of at least U<sub>0</sub>/U: 1.8/3 kV can be used for short circuit-proof and short-to-ground-proof installation up to 1000 V in acc. with VDE 0100 Part 520 and VDE 0298 Part 3

### Application range

- Wiring of machines, tools, devices, appliances and control cabinets
- Railway vehicles, buses, switching stations (short-circuit-proof up to 1000 V), power distributors (short-circuit-proof up to 1000 V)
- No direct burial, except of lead-through through fire separations such as sand cups
- In ducts, tubes, pipes, conduits and closed installation channels
- Bundled or for connection of movable parts

### Product features

- Flame-retardant according IEC 60332-1-2
- Oil-resistant according to EN 60811-404
- Normative rated voltage classes U<sub>0</sub>/U 0.6/1 kVac and 3.6/6 kVac available on request

### Norm references / Approvals

- <VDE> certification according to the VDE cable type NSGAFÖU 1,8/3 kV acc. VDE 0250-602

### Product make-up

- Fine-wire strand made of tinned-copper wires
- Core insulation: rubber compound type 3GI3
- Outer coating: rubber compound, type 5GM3
- No outer sheath

### Technical data



#### Classification

ETIM 5.0 Class-ID: EC000993  
ETIM 5.0 Class-Description: Single core cable



#### Conductor stranding

Fine wire according to VDE 0295 Class 5 / IEC 60228 Class 5



#### Minimum bending radius

Flexible use: 10 x outer diameter  
Fixed installation: 6 x outer diameter



#### Nominal voltage

U<sub>0</sub>/U: 1.8/3 kV



#### Test voltage

6000 V



#### Current rating

According to VDE 0298 Part 4, Table 15



#### Temperature range

Flexible use: -25°C to +90°C  
Fixed installation: -40°C to +90°C

Article number	Conductor cross-section (mm <sup>2</sup> )	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
1600300	1.5	7.0	14.4	60
1600301	2.5	7.5	24.0	70
1600302	4	9.0	38.4	90
1600303	6	9.5	57.6	120
1600304	10	11.0	96.0	180
1600305	16	13.0	153.6	250
1600306	25	15.0	240.0	390
1600307	35	16.5	336.0	470
1600308	50	18.0	480.0	625
1600309	70	20.5	672.0	880
1600310	95	24.0	912.0	1190
1600311	120	26.0	1,152.0	1430
1600312	150	28.0	1,440.0	1750
1600313	185	31.0	1,776.0	2160
1600314	240	34.5	2,304.0	2640
3026826	300	38.0	2,880.0	3545

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs are not to scale and do not represent detailed images of the respective products.

### Accessories

- V 1311 pressing pliers, hydraulic refer to page 934
- KS 20 cable shears refer to page 908