

# EXIT BUTTONS

A range of Stainless Steel green domed, push plate and standard and architrave exit buttons designed to meet the most robust applications and to comply with Risk Assessment RA001 and EN50133/Industry Codes of Practice. Designs have been made to comply with H&S regulation

## **XB/SS25**



**(H: 90mm W: 90mm D: 28mm ) for surface mounting**

Stainless Steel Button mounted on a Stainless Steel plate complete with Security Screws and innovative Green Back Box

<b>Dimensions:</b>	<b>Specification:</b>
Voltage:	S/Steel plate: H:90mm W:90mm
Current:	<30v DC/AC
Operations:	4 Amps @ 30v AC/DC
Contacts:	> 1 Million
IP Rating:	NO/NC Contacts
	IP 66

**(H: 90mm W: 90mm D: 28mm ) for surface mounting**

A Small Push Plate mounted on a Stainless Steel Plate complete with Security Screws and innovative Green Back Box

## **XB/PP25**



<b>Dimensions:</b>	<b>Specification:</b>
Voltage:	S/Steel plate: H:90mm W:90mm
Current:	<30v DC/AC
Operations:	4 Amps @ 30v AC/DC
Contacts:	> 1 Million
IP Rating:	NO/NC Contacts
	IP 66

## **XB/GO25**



**(H: 90mm W: 90mm D: 28mm ) for surface mounting**

Stainless Steel Button mounted on a Stainless Steel Architrave Plate complete with Screws and innovative Green Back Box.

<b>Dimensions:</b>	<b>Specification:</b>
Voltage:	S/Steel plate: H:90mm W:90mm
Current:	<30v DC/AC
Operations:	4 Amps @ 30v AC/DC
Contacts:	> 1 Million
IP Rating:	NO/NC Contacts
	IP 66

**(H: 90mm W: 44mm D: 28mm ) for surface mounting**

Green Domed Button on Stainless Steel Plate complete with Security Screws and innovative Green Back Box

## **XB/ARCSS25**



<b>Dimensions:</b>	<b>Specification:</b>
Voltage:	S/Steel plate: H:90mm W:44mm
Current:	<30v DC/AC
Operations:	4 Amps @ 30v AC/DC
Contacts:	> 1 Million
IP Rating:	NO/NC Contacts
	IP 66