

panel mounting socket outlet, angled - flange 85x85,  
fixing centers 70x70




| Product description           |                                                    |
|-------------------------------|----------------------------------------------------|
| BALS-Prd.-Nr                  | 12763                                              |
| EAN                           | 4024941127639                                      |
| product category (PG)         | Panel mounting socket outlet Quick-Connect, angled |
| current (A)                   | 32A                                                |
| number of poles (P99)         | 4p                                                 |
| number of poles (P)           | 3P+PE                                              |
| position of earth contact (H) | 9 h                                                |
| voltage (V)                   | 200 up to 250V                                     |

| Product description            |                                                                  |
|--------------------------------|------------------------------------------------------------------|
| frequency (HZ)                 | 50 and 60Hz                                                      |
| protection degree (SA)         | IP44                                                             |
| colour code 1 (KF1)            | blue RAL 5015                                                    |
| Colour of appliance            | Hinged lid blue, Enclosure grey                                  |
| connection design (AT)         | screwless spring terminals as cage clamp with Kontext-contact    |
| maximum conductor size (LQ)    | 10,0 qmm                                                         |
| cable entry (KE)               | null                                                             |
| Height                         | 94mm                                                             |
| Width                          | 85mm                                                             |
| Depth                          | 117mm                                                            |
| Flange size vertical           | 85mm                                                             |
| Flange size horizontal         | 85mm                                                             |
| Drill hole distance vertical   | 70mm                                                             |
| Drill hole distance horizontal | 70mm                                                             |
| material of enclosure (GM)     | Polyamide                                                        |
| contact                        | The contact carrier is made of polyamide, The contacts are brass |

| Additional technical information |                        |
|----------------------------------|------------------------|
|                                  | The inclination is 20° |

| Logistics data |                  |
|----------------|------------------|
| Weight/pcs     | 0.189 kg / Piece |
| Packaging      | Bag              |
| Content amount | 1 ST             |
| EAN            | 4024941127639    |
| Length         | 117 mm           |
| Width          | 85 mm            |
| Height         | 94 mm            |
| Weight         | 0.19 kg          |
| Volume         | 934.83 ccm       |
| Packaging      | Carton           |
| Content amount | 10 ST            |
| EAN            | 4024941820820    |
| Length         | 128 mm           |
| Width          | 225 mm           |
| Height         | 399 mm           |
| Weight         | 2.149 kg         |
| Volume         | 11,491.2 ccm     |



4 MB 264

| Ampere<br>Polzahl | 16<br>3 | 16<br>4 | 16<br>5 | 32<br>3 | 32<br>4 | 32<br>5 |
|-------------------|---------|---------|---------|---------|---------|---------|
| a                 | 85,0    | 85,0    | 85,0    | 85,0    | 85,0    | 85,0    |
| b                 | 85,0    | 85,0    | 85,0    | 85,0    | 85,0    | 85,0    |
| c                 | 70,0    | 70,0    | 70,0    | 70,0    | 70,0    | 70,0    |
| d                 | 70,0    | 70,0    | 70,0    | 70,0    | 70,0    | 70,0    |
| e ø               | 5,5     | 5,5     | 5,5     | 5,5     | 5,5     | 5,5     |
| f                 | 8,0     | 8,0     | 8,0     | 8,0     | 8,0     | 8,0     |
| h                 | 46,0    | 46,0    | 46,0    | 55,0    | 55,0    | 55,0    |
| i                 | 50,0    | 51,0    | 54,0    | 60,0    | 60,0    | 60,0    |
| l ø               | 57,0    | 65,0    | 70,0    | 78,0    | 78,0    | 78,0    |
| α                 | 20°     | 20°     | 20°     | 20°     | 20°     | 20°     |
| Leiter mm² min    | 1,5     | 1,5     | 1,5     | 2,5     | 2,5     | 2,5     |
| Leiter mm² max    | 4       | 4       | 4       | 10      | 10      | 10      |
|                   |         |         |         |         |         |         |