

Presence detector

DualTech

DALI-2 Input Device

EAN 4007841 057473

STEINEL[®]
PROFESSIONAL



ideal 2,5 - 3,5 m



IP20



10 - 1000 lux



CE



max. Ø 6 m
presence



ultrasonic sensor
360°



energy saving



indoor sensor

5 JAHRE
HERSTELLER
GARANTIE

manufacturer's
warranty
[steinel-professional.de/garantie](https://www.steinel-professional.de/garantie)

Function description

The best of both worlds. Combined in one detector. Ultrasonic presence detector DualTech, ideal for offices, conference rooms and class rooms. 36 sq.m. presence zone, ultrasonic technology provides reliable detection behind objects regardless of temperature, additional detection capability with PIR technology. DALI-2 input device enables sensors to communicate collected sensor data to higher-level lighting management systems.

Presence detector

DualTech

DALI-2 Input Device
EAN 4007841 057473



Technical specifications

Type	Presence detector
Dimensions (L x W x H)	120 x 120 x 68 mm
Mains power supply	12 – 22,5 V
Sensor Technology	Ultrasonic
Application, place	Indoors
Application, place, room	classroom, one-person office, open-plan office, conference room / meeting room, duty room, recreation room, indoors
Installation site	ceiling
Type of installation	Concealed wiring
Electronic scalability	Yes
Mechanical scalability	No
Mounting height	2,50 – 3,5 m
Optimum mounting height	2,8 m
Detection angle	360 °
Sneak-by guard	Yes
Reach, radial	Ultrasonic: Ultraschall: Ø 10 m (Ultraschall: 79 m ²)
Reach, presence	Ultrasonic: Ultraschall: Ø 6 m (Ultraschall: 28 m ²)
Sensor Technology 2	passive infrared
Reach, radial 2	passive infrared: Passiv Infrarot: Ø 4 m (Passiv Infrarot: 13 m ²)

Reach, tangential 2	passive infrared: Passiv Infrarot: Ø 8 m (Passiv Infrarot: 50 m ²)
Reach, presence 2	passive infrared: Passiv Infrarot: Ø 4 m (Passiv Infrarot: 13 m ²)
Twilight setting TEACH	Yes
Twilight setting	10 – 1000 lx
Time setting	30 s – 30 Min.
Control output, Dali	Addressable/slave
Constant-lighting control	No
Basic light level function	No
With remote control	No
Interconnection	Yes
IP rating	IP20
Material	Plastic
Ambient temperature	-25 – +55 °C
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years
Version	DALI-2 Input Device
PU1, EAN	4007841057473

Accessories


EAN 4007841 009151 Remote control Smart Remote

Presence detector

DualTech


DALI-2 Input Device
EAN 4007841 057473

Detection Zone



Mögliche Montagehöhe: 2,50 m – 3,50 m
Orange: Präsenz und tangential
Schwarz: radial

Dimension Drawing



Circuit diagram

