




## Product data sheet

Item No. 57.510.0155.6

## Feed-through terminal WKN 10 / U BLUE /V0

Feed-through DIN rail terminal block with screw connection for mounting on TS 35 and TS 32, nominal cross section 10 mm², width 10 m m, color blue



Item No.	57.510.0155.6
EAN	4015573487994
Order Unit	50 Piece(s)

# Certificates / Approvals



### Technical data

#### General

Nominal cross section	10 mm²
Colour	Blue
Number of levels	1
Number of clamp positions per level	2
Width/grid dimension	10 mm
Insulating housing	PA666
Inflammability class of insulation material acc. with UL94	VO
Explosion-tested version "Ex e"	Yes
Mounting method	DIN rail (top hat rail)/G-rail
Terminal blocks for electrical installations	No

#### Technical data

Rated current	57 A
Rated voltage	1000 V
Rated impulse voltage	8 kV
Pollution degree	3
Closing plate required	Yes
Type of insulation material	Thermoplastic
Length	53.8 mm

### Connection Data

Connection type 1	Screw connection
Connection type 2	Screw connection
Minimum cross section solid	1.5 mm <sup>2</sup>





Maximum cross section solid	10 mm²
Minimum cross section fine stranded	2.5 mm²
Maximum cross section fine stranded	10 mm²
Minimum cross section stranded	16 mm²
Maximum cross section stranded	16 mm²
Wire strip length	13 mm
Torque conductor mounting	2 Nm

#### Technical Data UL/CSA

Cross section UL	16-6 AWG
Voltage UL	600 V
Current factory wiring	65 A
Current field wiring	65 A
Cross section CSA	16-6 AWG
Voltage CSA	600 V
Current CSA	70 A

## Technical drawing

