

Product data sheet

Item No. 93.421.0853.0

Female connector BST14I2I B1VZB GN01

Flat cable adapter BST14i2, 50V, 3A, for tapping off the KNX signal of the combination flat cable mains + bus/ signals,, output with female connector, parallel to cable entry



Item No.	93.421.0853.0
EAN	4015573531345
Order Unit	50 Piece(s)

Certificates / Approvals

Technical data

General

Rated voltage	50 V
Rated current	3 A
Degree of protection (IP)	IP20
Mechanical coding	Yes
Marking of poles	1+, 2-
Color of coding/ contact carrier	Green
Lockable	Yes

Model

Model	Tapp-off
Number of poles	2
Selection of phase	1+/2-

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C



Dimensions

Length	54 mm
Width	27 mm
Height	25 mm

Technical drawing

Abdeckung
 cover
 Polycarbonat, transparent
 loose beiliegend
 unassembled

Grundplatte
 base plate
 PA66 halogenfrei, violett öhnl. RAL 4005
 PA66 halogen-frei, violett similar RAL 4005
 loose beiliegend
 unassembled

Buchseinteil
 Female connector
 PA66 halogenfrei, grün
 PA66 halogen-free, green

EIB - Kodierung
 EIB - coding M 1:1

Weitere Daten siehe Katalog
 further data see catalog

1. Zeichnung nach DIN 7162/Reference system acc. to DIN 7162. (This dimensioned drawing, the envelope principle. According to the envelope principle the deviations of form and position are limited by the size tolerances.)
 2. Maßstab 2:1
 3. Material PA66
 4. Zeichnung Nr./Drawing No. 93.421.0853.0 01K a
 5. Typ Bezeichnung/Title FLACHLEITUNGS_ADAPTER
 6. Flachkabeladapter
 7. Kodierung/coding 2 polig/2 pole