

Product data sheet

Item No. 92.238.1503.2

Cable assembly GST18I3K1B- 25E 15WS

geis® Connection cable female - free end; length: 1,5m; type GST18I3; 3 -pole; 250 V / 20 A; colour of coding: white with white strain-relief; cable: H05VV-F 3G2,5, colour: white, fire class Eca



Item No.	92.238.1503.2
EAN	4015573420670
Order Unit	40 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	White
Marking of poles	L, N, PE
Color of housing inclusive strain relief	White

Model

Nominal cross section conductor	2.5 mm²
Degree of protection (IP)	IP20
Wire strip length	9 mm
sheath strip length	37 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F
Cable colour	White

Cable diameter	10.2 mm
Version of cable	Female - free end
Type of cord set	Connection cable
Version cable end 1	GST1813 female
Version cable end 2	Free end

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C
Fire class	Eca

Dimensions

Total length	1.5 m
--------------	-------

Technical drawing

Buchsenteil/female connector

Kabel/cable H05VV-F362,5
Farbe/colour: siehe Tabelle/see table

Gesamtlänge / total length L±3%

.F	Farbe colour	Codierung Buchse female	Kabelfarbe cable colour
.1	schwarz black	N P L	schwarz black
.2	weiß white		weiß white
.3	grau grey	N P L	schwarz black
.5	rot red		schwarz black

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.238.XX03.F	XX in dm-Schritten	92.238.1003.1 = 10dm/L= 1000mm	GST1813K1B- 25 10SW
U2.238.XX03.F	XX in m-Schritten	U2.238.1203.1 = 12 m/L=12000mm	GST1813K1B- 25 X12SW

Typ/type: GST1813K1B- 25 ..
 SW = schwarz/black
 WS = weiß/white
 GR01 = grau/grey
 RT03 = rot/red

Furthering Size ISO 14269 / Furthering system Size ISO 14269 / ...
 (This ISO-standard describes the envelope principle. According to the envelope principle the deviations of form and position are limited by the size tolerances.)
 (This ISO-standard describes the envelope principle. According to the envelope principle the deviations of form and position are limited by the size tolerances.)

Freitoleranz nach
control: tolerance

2006 Zug/Bolt
42.02.01.01
42.02.01.01
42.02.01.01
42.02.01.01

Zeichnung Nr./Drawing No.
92.238.0203.1 01K a

Made in Germany/Produced in Germany

Wieland
Wieland Electric
Wieland Electric

PRE-ASSEMBLED CABLE
KONFERT-LEITUNG
Buchse/female-frees End/free end (Impression K1)
250V AC 20A 2,5sqmm

01-FEM-08/916