

Elementnr. 2202-1611/1000-867

TOPJOB® S > 2-leder sikringsklemme; med svingbar sikringsholder; med endeplate; for 5 x 20 mm miniatyr metrisk sikring; med trykknapp; med utbrent sikring-indikasjon med LED; 120 V; for DIN-skinne 35 x 15 og 35 x 7,5; 2,5 mm²; Push-in CAGE CLAMP®; 2,50 mm²; grå



Farge: ●

Listepris per del* Etter anmodning
Priser og tilgjengelighet etter [Logg på](#)
Din pris per enhet* Etter anmodning

PU (SPU): 50 Piece

- 50 +

[Legg til handlekurv](#)[Datablad som PDF](#)[Sammenlikne](#)[Bokmerke](#)**Safety information 1:**

Electrical ratings are given by the fuse and blown fuse indication.

Safety information 2:

Leakage current in case of a blown fuse: LED 2 mA

Produktdetaljer

Detaljer ^

Electrical data

Ratings per IEC/EN 60664-1

Ratings per	IEC/EN 60947-7-3
Rated voltage (III / 3)	250 V
Rated impulse voltage (III / 3)	6 kV
Rated current	6,3 A
Operation status indicator	120 V

Connection data

> Norway (NO) Technology

> Vi hjelper deg gjerne Push-in CAGE CLAMP®

47 22 36 34 50

Actuation type

Kontakt

Push-in
Push-button
Selskapsinformasjon
Operating tool

Personvern

Vilkår og betingelser

Juridisk informasjon

© 2020 WAGO



Connectable conductor materials	Copper
Nominal cross section	2,5 mm²
Solid conductor	0,25 ... 4 mm² / 22 ... 12 AWG

■ Geometrical Data

Width	6,2 mm / 0.244 inch
Høyde fra øverste kant av DIN-skinne	57,6 mm / 2.268 inch
Depth	66,1 mm / 2.602 inch

■ Mechanical data

Design	horizontal
Type of mounting	DIN-35 rail
Marking level	Center/side marking

■ Material Data

Color	grå
Insulating material	Polyamide 66 (PA66)
Weight	13,9 g

■ Commercial data

Packaging type	BOX
Country of origin	DE
GTIN	4055143907750
Customs tariff number	85369095990

Nedlastinger

Documentation ^

■ Additional Information

English



Technical
explanations
03.apr.2019



Kompatible produkter

skinne ^

ELEMENTNR.: 210-112
Bæreskinne i stål; 35 x 7,5 mm; 1 mm tykk; 2 m lang; med spor; i henhold til EN 60715; "Hullbredde 25 mm



ELEMENTNR.: 210-113
Bæreskinne i stål; 35 x 7,5 mm; 1 mm tykk; 2 m lang; uten spor; i henhold til EN 60715



Bæreskinne i stål; 35 x 15 mm; 1 mm tykk; 2 m lang; uten spor; likner EN 60715

ELEMENTNR.: 210-114

Bæreskinne i stål; 35 x 15 mm; 1,5 mm tykk; 2 m lang; uten spor; likner EN 60715



^ Vis færre ^ Vis flere

Endeplate ^

Isolasjonsstopper ^

Lask ^

Låsespaker ^

Marking accessories ^

Push-In-type trådbroer ^

ferruled ^

Verktøy ^

[Handling Instructions](#)

Produktfamilie

TOPJOB® S

TOPJOB® S: In various industrial applications and modern building installations, WAGO's wide and versatile range of rail-mount terminal blocks provides more than just reliable electrical connections.

› [Vis alle produkter fra familien](#)