



110931
M22-DL-W-K10LED-BVP



Overview



Specifications



Resources



[Delivery program >](#)

[Technical data >](#)

[Design verification as per IEC/EN 61439 >](#)

[Technical data ETIM 7.0 >](#)

DELIVERY PROGRAM

Product range
RMQ-Titan

Description
Blister pack for hanging.
Complete practical solution.
Can be ordered using a single article no.

Connection to SmartWire-DT
no

Equipment supplied	
1 illuminated pushbutton actuator	M22-DL-W
1 mounting clamp	M22-A
1 LED element	M22-LED-W
1 contact element	M22-K10

TECHNICAL DATA

General

Ambient temperature
Open
-25 - +70 °C

shipping classification
DNV
GL
LR



DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat
dissipation [I_n]
6 A

Heat dissipation per pole, current-dependent [P_{id}]
0.11 W

Equipment heat dissipation, current-dependent
[P_{id}]
0 W

Static heat dissipation, non-current-dependent [P_{is}]
0.45 W

Heat dissipation capacity [P_{diss}]
0 W

Operating ambient temperature min.
-25 °C

Operating ambient temperature max.
+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.4 Resistance to ultra-violet (UV) radiation
Please enquire

10.2 Strength of materials and parts
10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.

10.8 Connections for external conductors
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.

10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Low-voltage industrial components (EG000017) / Front element for push button (EC0000221)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for push-button actuators (ec1@ss10.0.1-27-37-12-10 [AKF028014])

Colour button
White

Number of command positions
1

Construction type lens
Round

Hole diameter
22.5 mm

Width opening
0 mm

Height opening
0 mm

Type of button
Flat

Suitable for illumination
Yes

With protective cover
No

Labelled
No

Switching function latching
No

Spring-return
Yes

With front ring

Yes

Material front ring
Plastic

Colour front ring
Chrome

Degree of protection (IP), front side
IP67

Degree of protection (NEMA), front side
4X



