

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



Powering Business Worldwide

NZMN4-4-VE1250 - Circuit-breaker, 4p, 1250A



265981 NZMN4-4-VE1250

[Overview](#) [Specifications](#) [Resources](#)



265981 NZMN4-4-VE1250

Circuit-breaker, 4p, 1250A

EL-Nummer (Norway)

4358948

Circuit-breaker NZM4, 4 pole, Switching capacity 400/415 V 50 Hz(Icu): 50 kA, Rated current = rated uninterrupted current Rated current = rated uninterrupted current(I_n = I_u): 1250 A, Installation type: Fixed, Screw connection, Standard/Approval: IEC, Protective function: Systems, cable, selectivity and generator protection

- [Delivery program](#)
- [Technical data](#)
- [Design verification as per IEC/EN 61439](#)
- [Technical data ETIM 7.0](#)
- [Characteristics](#)
- [Dimensions](#)

Delivery program

Product range

Circuit-breaker

Protective function

Systems, cable, selectivity and generator protection

Standard/Approval

IEC

Installation type

Fixed

Release system

Electronic release

Construction size

NZM4

Description

R.m.s. value measurement and “thermal memory”

Adjustable time delay setting to overcome current peaks t_r at $6 \times I_r$ also infinity (without overload releases)

Adjustable delay time t_{sd}

i^2t constant function: switchable

Set value in neutral conductor is synchronous with set value I_r of main pole.

Number of poles

4 pole

Standard equipment

Screw connection

Switching capacity

400/415 V 50 Hz [I_{cu}]

50 kA

Rated current = rated uninterrupted current [$I_n = I_u$]

Rated current = rated uninterrupted current [$I_n = I_u$]

1250 A

Neutral conductor [% of phase conductor]

100 %

Setting range

Overload trip  [I_t]

630 - 1250 A

Overload trip Main pole  [I_t]

630 - 1250 A

Short-circuit releases  [I_{rm}] Non-delayed  [$I_t = I_n \times \dots$]

2 - 12

Short-circuit releases  [I_{rm}] Delayed  [$I_{sd} = I_t \times \dots$]

2 - 10

Technical data

General

Standards

IEC/EN 60947

Protection against direct contact

Finger and back of hand proof to VDE 0106 Part 100

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature Ambient temperature, storage

- 40 - + 70 °C

Ambient temperature Operation

-25 - +70 °C

Mechanical shock resistance (10 ms half-sinusoidal shock) according to IEC 60068-2-27

15 (half-sinusoidal shock 11 ms) g

Safe isolation to EN 61140 Between auxiliary contacts and main contacts

500 V AC

Safe isolation to EN 61140 between the auxiliary contacts

300 V AC

Mounting position

Vertical and 90° in all directions	
	With XFI earth-fault release:
	- NZM1, N1, NZM2, N2: vertical and 90° in all directions
	with plug-in unit
	- NZM1, N1, NZM2, N2: vertical, 90° right/left
	with withdrawable unit:
	- NZM3, N3: vertical, 90° right/left
- NZM4, N4: vertical	
with remote operator:	
- NZM2, N(S)2, NZM3, N(S)3, NZM4, N(S)4: vertical and 90° in all directions	

Direction of incoming supply

as required

Degree of protection Device

In the operating controls area: IP20 (basic degree of protection)

Degree of protection Enclosures

With insulating surround: IP40

With door coupling rotary handle: IP66

Degree of protection Terminations

Tunnel terminal: IP10

Phase isolator and strip terminal: IP00

Other technical data (sheet catalogue)

[Temperature dependency, Derating](#)

Circuit-breakers

Rated current = rated uninterrupted current [$I_n = I_u$]

1250 A

Rated surge voltage invariability [U_{imp}] Main contacts

8000 V

Rated surge voltage invariability [U_{imp}] Auxiliary contacts

6000 V
 Rated operational voltage [U_b]
 690 V AC
 Overvoltage category/pollution degree
 III/3
 Rated insulation voltage [U_i]
 1000 V
 Use in unearthed supply systems
 525 V
 Switching capacity
 Rated short-circuit making capacity [I_{cm}]240 V [I_{cm}]
 105 kA
 Rated short-circuit making capacity [I_{cm}]400/415 V [I_{cm}]
 105 kA
 Rated short-circuit making capacity [I_{cm}]440 V 50/60 Hz [I_{cm}]
 74 kA
 Rated short-circuit making capacity [I_{cm}]525 V 50/60 Hz [I_{cm}]
 53 kA
 Rated short-circuit making capacity [I_{cm}]690 V 50/60 H [I_{cm}]
 40 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cu} to IEC/EN 60947 test cycle O-t-CO [I_{cu}]240 V 50/60 Hz [I_{cu}]
 50 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cu} to IEC/EN 60947 test cycle O-t-CO [I_{cu}]400/415 V 50/60 Hz [I_{cu}]
 50 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cu} to IEC/EN 60947 test cycle O-t-CO [I_{cu}]440 V 50/60 Hz [I_{cu}]
 35 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cu} to IEC/EN 60947 test cycle O-t-CO [I_{cu}]525 V 50/60 Hz [I_{cu}]
 25 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cu} to IEC/EN 60947 test cycle O-t-CO [I_{cu}]690 V 50/60 Hz [I_{cu}]
 20 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]240 V 50/60 Hz [I_{cs}]
 37 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]400/415 V 50/60 Hz [I_{cs}]
 37 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]440 V 50/60 Hz [I_{cs}]
 26 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]525 V 50/60 Hz [I_{cs}]
 19 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]690 V 50/60 Hz [I_{cs}]
 15 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}]
 Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit-breaker.
 Rated short-time withstand current I_{cw} = 0.3 s [I_{cw}]
 19.2 kA
 Rated short-time withstand current I_{cw} = 1 s [I_{cw}]
 19.2 kA
 Utilization category to IEC/EN 60947-2
 B
 Lifespan, mechanical (of which max. 50 % trip by shunt/undervoltage release) [Operations]
 10000
 Lifespan, electrical AC-1400 V 50/60 Hz [Operations]
 3000
 Lifespan, electrical AC-1415 V 50/60 Hz [Operations]
 3000
 Lifespan, electrical AC-1690 V 50/60 Hz [Operations]
 2000
 Lifespan, electrical AC-3400 V 50/60 Hz [Operations]
 2000
 Lifespan, electrical AC-3415 V 50/60 Hz [Operations]
 2000
 Lifespan, electrical AC-3690 V 50/60 Hz [Operations]
 1000
 Lifespan, electrical Max. operating frequency
 60 Ops/h
 Total break time at short-circuit
 < 25 □ 415 V; < 35 > 415 V ms
Terminal capacity
 Standard equipment

Screw connection
 Optional accessories
 Tunnel terminal
 connection on rear
 Strip terminal
 Round copper conductor Tunnel terminal Stranded 4-hole
 4 x (50 - 240) mm²
 Round copper conductor Bolt terminal and rear-side connection Direct on the switch Stranded
 1 x (120 - 185)
 4 x (50 - 185) mm²
 Round copper conductor Bolt terminal and rear-side connection Module plate Single hole [min.]
 1 x (120 - 300) mm²
 Round copper conductor Bolt terminal and rear-side connection Module plate Single hole [max.]
 2 x (95 - 300) mm²
 Round copper conductor Bolt terminal and rear-side connection Module plate Double hole [min.]
 2 x (95 - 185) mm²
 Round copper conductor Bolt terminal and rear-side connection Module plate Double hole [max.]
 4 x (35 - 185) mm²
 Round copper conductor Bolt terminal and rear-side connection Connection width extension Connection width extension
 4 x 300
 6 x (95 - 240) mm²
 Al circular conductor Tunnel terminal Stranded 4-hole
 4 x (50 - 240) mm²
 Al circular conductor Bolt terminal and rear-side connection Module plate Single hole [min.]
 1 x (185 - 240) mm²
 Al circular conductor Bolt terminal and rear-side connection Module plate Single hole [max.]
 2 x (70 - 185) mm²
 Al circular conductor Bolt terminal and rear-side connection Module plate Double hole
 4 x 50 mm²
 Al circular conductor Bolt terminal and rear-side connection Connection width extension Connection width extension
 2 x 240
 6 x (70 - 240) mm²
 Cu strip (number of segments x width x segment thickness) Flat conductor terminal [min.]
 6 x 16 x 0.8 mm
 Cu strip (number of segments x width x segment thickness) Flat conductor terminal [max.]
 (2 x) 10 x 32 x 1.0 mm
 Cu strip (number of segments x width x segment thickness) Module plate Single hole
 (2 x) 10 x 50 x 1.0 mm
 Cu strip (number of segments x width x segment thickness) Bolt terminal and rear-side connection Flat copper strip,
 with holes [min.]
 5 x 25 x 1.0 mm
 Cu strip (number of segments x width x segment thickness) Bolt terminal and rear-side connection Flat copper strip,
 with holes [max.]
 (2 x) 10 x 50 x 1.0 mm
 Cu strip (number of segments x width x segment thickness) Bolt terminal and rear-side connection Connection width
 extension
 (2 x) 10 x 80 x 1.0 mm
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Screw connection
 M10
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Direct on the switch [min.]
 25 x 5 mm
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Direct on the switch [max.]
 2 x (50 x 10) mm
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Module plate Single hole [min.]
 25 x 5 mm
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Module plate Single hole [max.]
 2 x (50 x 10) mm
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Module plate Double hole
 2 x (50 x 10) mm
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Connection width extension Connection
 width extension [min.]
 60 x 10 mm
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Connection width extension Connection
 width extension [max.]
 2 x (80 x 10) mm
 Control cables
 1 x (0.75 - 2.5)
 2 x (0.75 - 1.5) mm²

Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_n]

1250 A

Equipment heat dissipation, current-dependent [P_{id}]

173.44 W

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss10.0.1-27-37-04-09 [AJZ716013])

Rated permanent current I_n

1250 A

Rated voltage

690 - 690 V


Rated short-circuit breaking capacity I_{cu} at 400 V, 50 Hz

50 kA


Overload release current setting
 630 - 1250 A
 Adjustment range short-term delayed short-circuit release
 1250 - 12500 A
 Adjustment range undelayed short-circuit release
 2500 - 15000 A
 Integrated earth fault protection
 No
 Type of electrical connection of main circuit
 Screw connection
 Device construction
 Built-in device fixed built-in technique
 Suitable for DIN rail (top hat rail) mounting
 No
 DIN rail (top hat rail) mounting optional
 No
 Number of auxiliary contacts as normally closed contact
 0
 Number of auxiliary contacts as normally open contact
 0
 Number of auxiliary contacts as change-over contact
 0
 With switched-off indicator
 No
 With under voltage release
 No
 Number of poles
 4
 Position of connection for main current circuit
 Front side
 Type of control element
 Rocker lever
 Complete device with protection unit
 Yes
 Motor drive integrated
 No
 Motor drive optional
 Yes
 Degree of protection (IP)
 IP20

Characteristics


Characteristic curve



Characteristic curve



Dimensions



- Blow out area, minimum clearance to adjacent parts
 $U_i \leq 690 \text{ V}$: 100 mm
 $U_i \leq 1500 \text{ V}$: 200 mm
- Minimum clearance to adjacent parts
 $U_i \leq 1000 \text{ V}$: 15 mm
 $U_i \leq 1500 \text{ V}$: 70 mm

CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)

DWG files

- [DA-CD-nzm4_4p](#)
File
(Web)

edz files

- [DA-CE-ETN.NZM4-4-VE1250](#)
File
(Web)


Step files

- [DA-CS-nzm4_4p](#)
File
(Web)



Additional product information

- [Temperature dependency, Derating](#)
(Web)
- [CurveSelect characteristics program](#)
(Web)
- [Eaton configurator](#)
(Web)
- [additional technical information for NZM power switch](#)
(PDF)


Dimensions single product

- 
[123X509](#)
Line drawing
Circuit-breakers
 - Blow out area, minimum clearance to adjacent parts
 - Minimum clearance to adjacent parts
 - Does not apply to DC applications

Characteristic curve

- 
[123U174](#)
Coordinate visualization
NZM4-VE630...1600 tripping characteristic
- 
[123U175](#)
Coordinate visualization
NZM4-VE630...1600 tripping characteristic

3D drawing



123I613

Line drawing

Protection of systems and cables

Product photo



1230PIC-713

Photo

Instruction Leaflet

- [AWA1230-2022, AWA1230-2540 \(IL01210010Z\)](#)
Asset
IL01210010Z2018_11
(PDF, 11/18, Language independent)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH