

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NZMH2-VE250-S1 - Circuit-breaker, 3p, 250A 1000V



100779 NZMH2-VE250-S1

[Overview](#) [Specifications](#) [Resources](#)



# 100779 NZMH2-VE250-S1

Circuit-breaker, 3p, 250A 1000V

EL-Nummer (Norway)

0004359045

Circuit-breaker NZM2, 3 pole, Switching capacity 1000 V 50/60 Hz( Ics): 10 kA, Rated current = rated uninterrupted current( I<sub>n</sub> = I<sub>u</sub>): 250 A, Installation type: Fixed, Screw connection, Standard/Approval: IEC, Protective function: Systems, cable, selectivity and generator protection

- Delivery program
- Technical data
- Design verification as per IEC/EN 61439
- Technical data ETIM 7.0
- Characteristics
- Dimensions

## Delivery program

Product range

Circuit-breaker

Protective function

Systems, cable, selectivity and generator protection

Standard/Approval

IEC

Installation type

Fixed

Release system

Electronic release

Construction size

NZM2

Description

R.m.s. value measurement and “thermal memory”

adjustable time delay setting to overcome current peaks tr: 2 – 20 s at 6 x I<sub>r</sub> also infinity (without overload releases)

Adjustable delay time tsd: Steps: 0, 20, 60, 100, 200, 300, 500, 750, 1000 ms

i<sup>2</sup>t constant function: fixed OFF

NZM...S1 terminal type: NZM...XKSA cover required

Number of poles

3 pole

Standard equipment

Screw connection

Rated current = rated uninterrupted current [I<sub>n</sub> = I<sub>u</sub>]

250 A

Switching capacity

1000 V 50/60 Hz [ $I_{cu}$ ]

10 kA

### Setting range

Overload trip  [ $I_t$ ]

125 - 250 A

Short-circuit releases  [ $I_{rm}$ ] Non-delayed  [ $I_t = I_n \times \dots$ ]

3000 A fixed

Short-circuit releases  [ $I_{rm}$ ] Delayed  [ $I_{sd} = I_t \times \dots$ ]

2 - 10

## Technical data

### Circuit-breakers

Rated surge voltage invariability [ $U_{imp}$ ] Main contacts

8000 V

Rated surge voltage invariability [ $U_{imp}$ ] Auxiliary contacts

6000 V

Rated operational voltage [ $U_e$ ]

1000 V AC

Rated current = rated uninterrupted current [ $I_n = I_u$ ]

250 A

Overvoltage category/pollution degree

III/3

Rated insulation voltage [ $U_i$ ]

1000 V

Utilization category

A

Ambient temperature Ambient temperature, storage

- 40 - + 70 °C

Ambient temperature Operation

-25 - +70 °C

Rated short-circuit making capacity [ $I_{cm}$ ]

240 V 50/60 Hz [ $I_{cm}$ ]

330 kA

400/415 V 50/60 Hz [ $I_{cm}$ ]

330 kA

440 V 50/60 Hz [ $I_{cm}$ ]

286 kA

525 V 50/60 Hz [ $I_{cm}$ ]

105 kA

690 V 50/60 Hz [ $I_{cm}$ ]

40 kA

1000 V 50/60 Hz [ $I_{cm}$ ]

17 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]

$I_{cu}$  to IEC/EN 60947 test cycle O-t-CO [ $I_{cu}$ ] 240 V 50/60 Hz [ $I_{cu}$ ]

150 kA

$I_{cu}$  to IEC/EN 60947 test cycle O-t-CO [ $I_{cu}$ ] 400/415 V 50 Hz [ $I_{cu}$ ]

150 kA

$I_{cu}$  to IEC/EN 60947 test cycle O-t-CO [ $I_{cu}$ ] 440 V 50/60 Hz [ $I_{cu}$ ]

130 kA

$I_{cu}$  to IEC/EN 60947 test cycle O-t-CO [ $I_{cu}$ ] 525 V 50/60 Hz [ $I_{cu}$ ]

50 kA

$I_{cu}$  to IEC/EN 60947 test cycle O-t-CO [ $I_{cu}$ ] 690 V 50/60 Hz [ $I_{cu}$ ]

20 kA

$I_{cu}$  to IEC/EN 60947 test cycle O-t-CO [ $I_{cu}$ ] 1000 V 50/60 Hz [ $I_{cu}$ ]

10 kA

$I_{cs}$  to IEC/EN 60947 test cycle O-t-CO-t-CO [ $I_{cs}$ ] 230 V 50/60 Hz [ $I_{cs}$ ]

150 kA

$I_{cs}$  to IEC/EN 60947 test cycle O-t-CO-t-CO [ $I_{cs}$ ] 400/415 V 50/60 Hz [ $I_{cs}$ ]

150 kA

$I_{cs}$  to IEC/EN 60947 test cycle O-t-CO-t-CO [ $I_{cs}$ ] 440 V 50/60 Hz [ $I_{cs}$ ]

130 kA

$I_{cs}$  to IEC/EN 60947 test cycle O-t-CO-t-CO [ $I_{cs}$ ] 525 V 50/60 Hz [ $I_{cs}$ ]

37.5 kA

$I_{cs}$  to IEC/EN 60947 test cycle O-t-CO-t-CO [ $I_{cs}$ ] 690 V 50/60 Hz [ $I_{cs}$ ]

5 kA

$I_{cs}$  to IEC/EN 60947 test cycle O-t-CO-t-CO [ $I_{cs}$ ] 1000 V AC [ $I_{cs}$ ]

3 kA  
 Rated short-time withstand current  
 $t = 0.3 \text{ s } [I_{cw}]$   
 1.9 kA  
 $t = 1 \text{ s } [I_{cw}]$   
 1.9 kA  
 Lifespan, mechanical [Operations]  
 20000  
 Max. operating frequency  
 120 Cps/h  
 Lifespan, mechanical: of which max. 50 % trip by shunt/undervoltage release  
 Lifespan, electrical  
 1000 V 50/60 Hz [Operations]  
 3000

#### Terminal capacity

Standard equipment  
 Screw connection  
 Round copper conductorBox terminalSolid  
 1 x (10 - 16)  
 2 x (6-16) mm<sup>2</sup>  
 Round copper conductorBox terminalStranded  
 1 x (25 - 185)  
 2 x (25-70) mm<sup>2</sup>  
 Round copper conductorTunnel terminalSolid  
 1 x 16 mm<sup>2</sup>  
 Round copper conductorTunnel terminalStrandedStranded  
 1 x (25 - 185) mm<sup>2</sup>  
 Round copper conductorBolt terminal and rear-side connectionDirect on the switchSolid  
 1 x (10 - 16)  
 2 x (10 - 16) mm<sup>2</sup>  
 Round copper conductorBolt terminal and rear-side connectionDirect on the switchStranded  
 1 x (25 - 50)  
 2 x (25 - 50) mm<sup>2</sup>  
 Al conductors, Cu cableTunnel terminalSolid  
 1 x 16 mm<sup>2</sup>  
 Al conductors, Cu cableTunnel terminalStrandedStranded  
 1 x (25 - 185)<sup>2</sup> mm<sup>2</sup>  
 Al conductors, Cu cableTunnel terminalStranded  
<sup>2)</sup> Up to 240 mm<sup>2</sup> can be connected depending on the cable manufacturer.  
 Cu strip (number of segments x width x segment thickness)Box terminal [min.]  
 2 x 9 x 0.8 mm  
 Cu strip (number of segments x width x segment thickness)Box terminal [max.]  
 10 x 16 x 0.8  
 (2x) 8 x 15.5 x 0,8 mm  
 Cu strip (number of segments x width x segment thickness)Bolt terminal and rear-side connectionFlat copper strip,  
 with holes [min.]  
 2 x 16 x 0.8 mm  
 Cu strip (number of segments x width x segment thickness)Bolt terminal and rear-side connectionFlat copper strip,  
 with holes [max.]  
 10 x 24 x 0.8 mm  
 Copper busbar (width x thickness) [mm]Bolt terminal and rear-side connectionScrew connection  
 M8  
 Copper busbar (width x thickness) [mm]Bolt terminal and rear-side connectionDirect on the switch [min.]  
 16 x 5 mm  
 Copper busbar (width x thickness) [mm]Bolt terminal and rear-side connectionDirect on the switch [max.]  
 24 x 8 mm  
 Control cables  
 1 x (0.75 - 2.5)  
 2 x (0.75 - 1.5) mm<sup>2</sup>

## Design verification as per IEC/EN 61439

Technical data for design verification  
 Rated operational current for specified heat dissipation [I<sub>r</sub>]  
 250 A  
 Equipment heat dissipation, current-dependent [P<sub>vid</sub>]  
 51.56 W  
 Operating ambient temperature min.  
 -25 °C

Operating ambient temperature max.

+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss10.0.1-27-37-04-09 [AJZ716013])

Rated permanent current I<sub>n</sub>

250 A

Rated voltage

1000 - 1000 V

Rated short-circuit breaking capacity I<sub>cu</sub> at 400 V, 50 Hz

150 kA

Overload release current setting

125 - 250 A

Adjustment range short-term delayed short-circuit release

250 - 2500 A

Adjustment range undelayed short-circuit release

3000 - 3000 A

Integrated earth fault protection

No

Type of electrical connection of main circuit  
Screw connection  
Device construction  
Built-in device fixed built-in technique  
Suitable for DIN rail (top hat rail) mounting  
No  
DIN rail (top hat rail) mounting optional  
Yes  
Number of auxiliary contacts as normally closed contact  
0  
Number of auxiliary contacts as normally open contact  
0  
Number of auxiliary contacts as change-over contact  
0  
With switched-off indicator  
No  
With under voltage release  
No  
Number of poles  
3  
Position of connection for main current circuit  
Front side  
Type of control element  
Rocker lever  
Complete device with protection unit  
Yes  
Motor drive integrated  
No  
Motor drive optional  
Yes  
Degree of protection (IP)  
IP20

## Characteristics

Characteristic curve

Characteristic curve

Let-through current

Characteristic curve

Let-through energy

## Dimensions

Blow out area, minimum clearance to adjacent parts

Minimum clearance to adjacent parts

## CAD data

- [Product-specific CAD data](#)  
(Web)
- [3D Preview](#)  
(Web)

## DWG files

- [DA-CD-nzm2\\_3p](#)  
File  
(Web)

## Step files

- [DA-CS-nzm2\\_3p](#)  
File  
(Web)

## Additional product information

- [Weight](#)  
(Web)
- [Temperature dependency, Derating](#)  
(Web)
- [Effective power loss](#)  
(Web)
- [Selectivity, Back Up Protection and Coordination Guide](#)  
(PDF)
- [Setting-Specific Representation of Tripping Characteristics and Competent Assessment of their Interaction](#)  
(PDF)
- [Busbar Component Adapters for modern Industrial control panels](#)  
(PDF)
- [CurveSelect characteristics program](#)  
(Web)
- [Eaton configurator](#)  
(Web)
- [additional technical information for NZM power switch](#)  
(PDF)

## Dimensions single product

- [123X312](#)  
Line drawing  
Circuit-breaker, switch-disconnector, 3-pole
  - Blow out area, minimum clearance to adjacent parts
  - Minimum clearance to adjacent parts
- [123X341](#)  
Line drawing  
Circuit-breakers, switch-disconnectors

## 3D drawing

- [123I247](#)  
Line drawing  
Circuit-breakers, switch-disconnectors

## Product photo



[1230PIC-806](#)  
Photo

## Characteristic curve

- [1230DIA-57](#)  
Coordinate visualization  
Let-through characteristics
- [1230DIA-8](#)  
Coordinate visualization  
Let-through current
- [123U180](#)  
Coordinate visualization  
NZM2-VE100...250 tripping characteristic

## Instruction Leaflet

- [NZMB, NZMN \(IL01206006Z\)](#)  
Asset  
(PDF, 11/2015, Language independent)

## Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

