



121748

MSC-DE-32-M17(24VDC)

Overview

Specifications

Resources



DELIVERY PROGRAM

[Delivery program](#)

Basic function
DOL starters (complete devices)

[Technical data](#)

Basic device
MSC

[Design verification as per IEC/EN 61439](#)[Technical data ETIM 7.0](#)

Notes
Also suitable for motors with efficiency class IE3.

[Dimensions](#)

Connection technique
Screw terminals

Connection to SmartWire-DT
no

Motor ratings

Motor rating [P]
AC-3
380 V 400 V 415 V [P]
7.5 kW

Motor rating [P]
AC-3
500 V [P]
7.5 kW

Rated operational current
AC-3
380 V 400 V 415 V [I_e]
15.2 A

Rated operational current
AC-3
500 V [I_e]
12.1 A

Rated short-circuit current 380 - 415 V [I_q]
100 kA

Rated conditional short-circuit current 500 V [I_q]
50 kA

Setting range

Setting range of overload releases  [I]
8 - 32 A

Coordination
Type of coordination "1"
Type of coordination "2"

Contact sequence



Actuating voltage
24 V DC

DC voltage

Motor-protective circuit-breakers
PKE32/XTU-32 Type

Contactor
DILM17-10(...) Part no.

DOL starter wiring set

Mechanical connection element and electrical
electric contact module
PKZM0-XDMB2 Type

Notes

The DOL starter (complete devices) consists of a
PKE motor protective circuit breaker and a DILM
contactor.

With the adapter-less top-hat rail mounting of
starters up to 15 A, only the motor-protective
circuit-breaker on the top-hat rail requires an
adapter.

The contactors are provided with mechanical
support via a mechanical connection element.

Control wire guide with max. 6 conductors up to
2.5^omm²external diameter or 4 conductors up to
3.5^omm²external diameter.

From 16 A, the motor-protective circuit-breaker
and contactor are mounted on the top-hat rail
adapter plate.

The connection of the main circuit between PKE
and contactor is established with electrical contact
modules.

When using DILA-XHT... auxiliary contacts with
MSC-DE... DOL starters, the plug-in electrical
connectors can be removed without removing the
front-mounted auxiliary contact.

Cannot be combined with NH-E..PKZ0-C.

MSC-DEA... DOL starters are prepared for
communications via SmartWire-DT. In order to be
used this way, they first need to be expanded
with the PKE-SWD-32 communications module.


Motor output/rated motor current

Motor output	Rated motor current		AC-3		500 V with CL-PKZ0		660 V	
	220 V	380 V	415 V	440 V	500 V	500 V	690 V	
	230 V	400 V						
	240 V	V						
	$I_q = 100$ kA	$I_q = 100$ kA	$I_q = 65$ kA	$I_q = 65$ kA	$I_q = 50$ kA	$I_q = 100$ kA	$I_q = 3$ kA	
P	I	I	I	I	I	I	I	I
kW	A	A	A	A	A	A	A	A
2.2	8.7	-	-	-	-	-	-	-
3	11.5	-	-	-	-	-	-	-
4	14.8	8.5	8.5	-	-	-	-	-
5.5	-	11.3	11.3	10.2	9	9	-	-
7.5	-	15.2	15.2	13.8	12.1	12.1	8.8	

TECHNICAL DATA

General

Standards
IEC/EN 60947-4-1, VDE 0660



Ambient temperature
-25 - +55

Main conducting paths

Rated impulse withstand voltage [U_{imp}]
6000 V AC

Overvoltage category/pollution degree
III/3

Rated operational voltage [U_e]
230 - 415 V

Rated operational current
Open, 3-pole: 50 – 60 Hz
380 V 400 V [I_e]
17 A

AC-4 cycle operation
Minimum current flow times
500 (Class 5)
700 (Class 10)
900 (Class 15)
1000 (Class 20) ms

AC-4 cycle operation
Minimum cut-out periods
500 ms

AC-4 cycle operation
Note
In AC-4 cycle operation, going below the minimum current flow time can cause overheating of the load (motor).
For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods. ms

Additional technical data

Motor protective circuit breaker PKZM0, PKE
PKZM0 motor-protective circuit-breakers, see
motor-protective circuit-breakers/PKZM0 product
group
DILM contactors, see contactor product group
DILET timing relay, ETR, see contactors, electronic
timing relays product group

DILM contactors
Current heat loss
Current heat loss at I_e to AC-3/400 V
2.55 W

Power consumption

DC operated [Sealing]
0.86 W

Rating data for approved types

Short Circuit Current Rating
Basic Rating
SOCR
10 kA

Short Circuit Current Rating
Basic Rating
max. CB
400 A

DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_h]
17 A

Heat dissipation per pole, current-dependent [P_{vid}]
0.85 W

Equipment heat dissipation, current-dependent [P_{vid}]
2.55 W

Static heat dissipation, non-current-dependent [P_s]
0.86 W

Heat dissipation capacity [P_{diss}]
0 W

Operating ambient temperature min.
-25 °C

Operating ambient temperature max.
+55 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.

10.8 Connections for external conductors
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.

10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Electric engineering, automation, process control engineering / Low-voltage switch technology / Load breakout, motor breakout / Motor starter combination (ecl@ss10.0.1-27-37-09-05 [AJZ718013])

Kind of motor starter

Direct starter

With short-circuit release

Yes

Rated control supply voltage U_s at AC 50Hz

0 - 0 V

Rated control supply voltage U_s at AC 60Hz

0 - 0 V

Rated control supply voltage U_s at DC

24 - 24 V

Voltage type for actuating

DC

Rated operation power at AC-3, 230 V, 3-phase

4 kW

Rated operation power at AC-3, 400 V

7.5 kW

Rated power, 460 V, 60 Hz, 3-phase

0 kW

Rated power, 575 V, 60 Hz, 3-phase

0 kW

Rated operation current I_e

16.7 A

Rated operation current at AC-3, 400 V

17 A

Overload release current setting

8 - 32 A

Rated conditional short-circuit current, type 1, 480
Y/277 V
0 A

Rated conditional short-circuit current, type 1, 600
Y/347 V
0 A

Rated conditional short-circuit current, type 2, 230
V
100000 A

Rated conditional short-circuit current, type 2, 400
V
100000 A

Number of auxiliary contacts as normally open
contact
1

Number of auxiliary contacts as normally closed
contact
0

Ambient temperature, upper operating limit
60 °C

Temperature compensated overload protection
Yes

Release class
Adjustable

Type of electrical connection of main circuit
Screw connection

Type of electrical connection for auxiliary- and
control current circuit
Screw connection

Rail mounting possible
Yes

With transformer
No

Number of command positions

0

Suitable for emergency stop

No

Coordination class according to IEC 60947-4-3

Class 2

Number of indicator lights

0

External reset possible

No

With fuse

No

Degree of protection (IP)

IP20

Degree of protection (NEMA)

Other

Supporting protocol for TCP/IP

No

Supporting protocol for PROFIBUS

No

Supporting protocol for CAN

No

Supporting protocol for INTERBUS

No

Supporting protocol for ASI

No

Supporting protocol for MODBUS

No

Supporting protocol for Data-Highway

No

Supporting protocol for DeviceNet
No

Supporting protocol for SUCONET
No

Supporting protocol for LON
No

Supporting protocol for PROFINET IO
No

Supporting protocol for PROFINET OBA
No

Supporting protocol for SERCOS
No

Supporting protocol for Foundation Fieldbus
No

Supporting protocol for EtherNet/IP
No

Supporting protocol for AS-Interface Safety at Work
No

Supporting protocol for DeviceNet Safety
No

Supporting protocol for INTERBUS-Safety
No

Supporting protocol for PROFlsafe
No

Supporting protocol for SafetyBUS p
No

Supporting protocol for other bus systems
No

Width
45 mm

Height
242 mm

Depth
128 mm

DIMENSIONS



