

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



Powering Business Worldwide

SL4-BL230-W - Flashing light module;white; LED;230 V



171352 SL4-BL230-W

[Overview](#) [Specifications](#) [Resources](#)



# 171352 SL4-BL230-W

Flashing light module;white; LED;230 V

Alternate Catalog No.

SL4-BL230-W

EL-Nummer (Norway)

4137587

Flashing light module, Colour Clear, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage:  $U_e = 230/240$  V AC, Type of light: Flashing light, Light elements: LED, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

•  Delivery program

•  Technical data

•  Design verification as per IEC/EN 61439

•  Technical data ETIM 7.0

•  Approvals

•  Dimensions

## Delivery program

Product range

SL signal towers

Basic function

Flashing light module

Degree of Protection

IP66

Rated operational voltage [ $U_e$ ]

230/240 V ACV

Type of light

Flashing light

Light elements


LED

Colour

Clear



Function



Connection to SmartWire-DT

no



## Technical data

General  
Standards  
IEC/EN 60947-5-1  
Climatic proofing  
Damp heat, cyclic, to IEC 60068-2-30  
Mounting position  
As required  
Mechanical shock resistance  
> 15  
according to IEC 60068-2-27  
Shock duration 11 ms  
Sinusoidal g  
IEC degree of protection  
IP66  
IEC/EN 60529  
Protection type UL  
Type 4, 4X, 13  
Material  
Enclosure: Polycarbonate (PC), black  
Cap: Polycarbonate (PC)  
Cap colour  
Clear  
Ambient temperature  
-30 - +60 °C  
Number of signal elements  
Max. 5 with standard base  
Max. 10 with base for mounting on both sides  
Weight  
45 g  
Contacts  
Rated impulse withstand voltage [ $U_{imp}$ ]  
4000 V AC  
Rated insulation voltage [ $U_i$ ]  
250 V  
Overvoltage category/pollution degree  
III/3  
modules  
Type of light  
Flashing light  
Light elements  
LED  
Flashing/strobe frequency  
2 Hz  
Leakage current  
< 0.003 A  
lifespan  
> 100000 h  
Transmission angle  
360°  
Current-/power consumption at 230 /240V AC  
0.030 A  
Voltage range  
230/240 V AC  $\pm$  10 %

## Design verification as per IEC/EN 61439

Operating ambient temperature min.  
-30 °C  
Operating ambient temperature max.  
+60 °C

## Technical data ETIM 7.0


Low-voltage industrial components (EG000017) / Optical module for signal tower (EC000232)  
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Optical module for signal tower (ecl@ss10.0.1-27-37-12-20 [AKF038014])  
Function  
Blinker light

Colour  
Clear  
Outer diameter  
43 mm  
Operating voltage at AC 50 Hz  
230 - 240 V  
Operating voltage at AC 60 Hz  
230 - 240 V  
Operating voltage at DC  
0 - 0 V  
Voltage type  
AC  
Lamp type  
LED  
Colour housing  
Black  
Degree of protection (IP)  
IP66  
Degree of protection (NEMA)  
4X

## Approvals

Product Standards  
IEC/EN 60947-5-1; UL 508; CSA-C22.2 No. 14-10; CSA-C22.2 No. 94-91; CE marking  
UL File No.  
E29184  
UL Category Control No.  
NKCR  
CSA File No.  
UL report applies to both US and Canada  
CSA Class No.  
NKCR7  
North America Certification  
UL listed, certified by UL for use in Canada  
Degree of Protection  
UL Type 4, 4X, 13

## Dimensions



## CAD data

- [Product-specific CAD data](#)  
(Web)
- [3D Preview](#)  
(Web)

## DWG files

- [DA-CD-sI4\\_bfI4](#)  
File  
(Web)

## edz files

- [DA-CE-ETN.SL4-BL230-W](#)  
File  
(Web)

## Step files



- [DA-CS-sI4\\_bfI4](#)  
File

(Web)

## Product photo

-   
1160PIC-1282  
Photo


## Symbol

-   
1160SFC-48  
Graphic
-   
116C069  
Graphic  
Button plate, white

## 3D drawing

-   
1160DRW-299  
Line drawing

## Dimensions single product

-   
1160DIM-61  
Line drawing

## Instruction Leaflet

- [Signal Towers SL4: Main instruction \(IL047001ZU\)](#)  
Asset  
(PDF, multilingual)

## Declaration of Conformity

### EU

- [Signal tower series SL4 and SL7 \(DA-DC-00003679\)](#)  
Asset  
(PDF)

## Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

