

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



Powering Business Worldwide

SL4-L-B - Ba15d continuous light module; blue



171331 SL4-L-B

[Overview](#) [Specifications](#) [Resources](#)



171331 SL4-L-B

Ba15d continuous light module; blue

Alternate Catalog No.

SL4-L-B

EL-Nummer (Norway)

4137566

Continuous light module, Colour Blue, without light elements, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage: $U_e = < 250 \text{ V AC/DC}$, Type of light: Continuous light, Light elements: Filament lamp max. 4 W, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

• [Delivery program](#)

• [Technical data](#)

• [Design verification as per IEC/EN 61439](#)

• [Technical data ETIM 7.0](#)

• [Approvals](#)

• [Dimensions](#)

Delivery program

Product range

SL signal towers

Basic function

Continuous light module

Degree of Protection

IP66

Rated operational voltage [U_e]

< 250 V AC/DC V

Description

without light elements

Type of light

Continuous light

Light elements


Filament lamp max. 4 W

Colour

Blue



Function



Connection to SmartWire-DT
no

Technical data

General

Standards

IEC/EN 60947-5-1

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Mounting position

As required

Mechanical shock resistance

> 15

according to IEC 60068-2-27

Shock duration 11 ms

Sinusoidal g

IEC degree of protection

IP66

IEC/EN 60529

Protection type UL

Type 4, 4X, 13

Material

Enclosure: Polycarbonate (PC), black

Cap: Polycarbonate (PC)

Cap colour

Blue

Ambient temperature

-30 - +60 °C

Number of signal elements

Max. 5 with standard base

Max. 10 with base for mounting on both sides

Weight

45 g

Contacts

Rated impulse withstand voltage [U_{imp}]

4000 V AC

Rated insulation voltage [U_i]

250 V

Overvoltage category/pollution degree

III/3

modules

Type of light

Continuous light

Light elements

Filament lamp max. 4 W

Mounting

Ba15d

Leakage current

< 0.003 A

lifespan

> 3000 h

Transmission angle

360°

Current-/power consumptionPower consumption

Max. 4 W with the specified voltages

Voltage range

up to 250 V AC/DC

Design verification as per IEC/EN 61439

Operating ambient temperature min.

-30 °C

Operating ambient temperature max.

+60 °C

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Optical module for signal tower (EC000232)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Optical module for signal tower (ecl@ss10.0.1-27-37-12-20 [AKF038014])

Function

Continuous light

Colour

Blue

Outer diameter

43 mm

Operating voltage at AC 50 Hz

24 - 250 V

Operating voltage at AC 60 Hz

24 - 250 V

Operating voltage at DC

24 - 250 V

Voltage type

AC/DC

Lamp type

None

Colour housing

Black

Degree of protection (IP)

IP66

Degree of protection (NEMA)

4X

Approvals

Product Standards

IEC/EN 60947-5-1; UL 508; CSA-C22.2 No. 14-10; CSA-C22.2 No. 94-91; CE marking

UL File No.

E29184

UL Category Control No.

NKCR

CSA File No.

UL report applies to both US and Canada

CSA Class No.

NKCR7


North America Certification

UL listed, certified by UL for use in Canada

Degree of Protection

UL Type 4, 4X, 13

Dimensions



CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)

DWG files

- [DA-CD-sl4_bf14](#)
File
(Web)

edz files

- [DA-CE-ETN.SL4-L-B](#)
File
(Web)


Step files

- [DA-CS-sl4_bf14](#)
File
(Web)

Product photo

- 
[1160PIC-1055](#)
Photo


Symbol

- 
[1160SFC-21](#)
Graphic
- 
[116C267](#)
Graphic
Button plate, blue

3D drawing

- 
[1160DRW-299](#)
Line drawing

Dimensions single product

- 
[1160DIM-61](#)
Line drawing

Instruction Leaflet

- [Signal Towers SL4/7: Incandescent Mbduls \(IL047005ZU\)](#)
Asset
(PDF, multilingual)

Declaration of Conformity

EU

- [Signal tower series SL4 and SL7 \(DA-DC-00003679\)](#)
Asset
(PDF)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)
© 2021 by Eaton Industries GmbH

