



- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



Powering Business Worldwide

ZEB32-20/KK - Overload relay, Separate mounting, Earth-fault protection: none,  $I_r = 4 - 20 A$ , 1 N/O, 1 N/C

136496 ZEB32-20/KK

[Overview](#) [Specifications](#) [Resources](#)

- Delivery program
- Technical data
- Design verification as per IEC/EN 61439
- Technical data ETIM 7.0
- Approvals
- Characteristics
- Dimensions

## 136496 ZEB32-20/KK

Overload relay, Separate mounting, Earth-fault protection: none,  $I_r = 4 - 20 A$ , 1 N/O, 1 N/C

Alternate Catalog No.

XTOE020CCSS

EL-Nummer (Norway)

4137365

Overload relay, Product range: Electronic overload relays ZEB, Phase-failure sensitivity: IEC/EN 60947, VDE 0660 Part 102, Description: Test/off button, Reset pushbutton, Manual/auto reset selectable, Protection with heavy starting duty (Class 10A-30), Mounting type: Separate mounting, Auxiliary contacts N/O = Normally open: 1 N/O, Auxiliary contacts N/C = Normally closed: 1 N/C, For use with: DILM17, DILM25, DILM32, DILM88, DIULM17, DIULM25, DIULM32, SDAINLM80, SDAINLM45, SDAINLM65, Standards: IEC/EN 60947, VDE 0660, UL, CSA, Degree of Protection: IP20

### Delivery program

Product range

Electronic overload relays ZEB

Phase-failure sensitivity

IEC/EN 60947, VDE 0660 Part 102

Description

Test/off button

Reset pushbutton

Manual/auto reset selectable

Protection with heavy starting duty (Class 10A-30)

Mounting type

Separate mounting

Earth-fault protection


Earth-fault protection

none

**Setting range**Overload releases [ $I_r$ ]

4 - 20 A

Contact sequence



Auxiliary contacts  
NO = Normally open  
1 NO  
NC = Normally closed  
1 NC  
For use with  
DILM17  
DILM25  
DILM32  
DILM88  
DIULM17  
DIULM25  
DIULM32  
SDAINLM30  
SDAINLM45  
SDAINLM55  
Conformity, Approval  
Explosion protection (according to ATEX 94/9/EC)  
II(2)GD [Ex d] [Ex e] [Ex tb]  
EC-prototype test certification  
SIRA 13 ATEX 9348X

## Technical data

General  
Standards  
IEC/EN 60947, VDE 0660, UL, CSA  
Climatic proofing  
Damp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30  
Ambient temperatureOpen  
-25 - +65 °C  
Ambient temperatureAmbient temperature open max.  
65 °C  
Ambient temperatureEnclosedAmbient temperature enclosed max.  
65 °C  
Mechanical shock resistance  
15  
Shock duration 10 ms  
according to IEC 60068-2-27 g  
Degree of Protection  
IP20  
Protection against direct contact when actuated from front (EN 50274)  
Finger and back-of-hand proof  
Altitude  
Max. 2000 m  
Main conducting paths  
Rated impulse withstand voltage [ $U_{imp}$ ]  
6000 V AC  
Overvoltage category/pollution degree  
III/3  
Rated insulation voltage [ $U_i$ ]  
690 V AC  
Rated operational voltage [ $U_o$ ]  
690 V AC  
Rated frequency [f]  
50/60 Hz  
Safe isolation to EN 61140 Between auxiliary contacts and main contacts  
600 V AC  
Safe isolation to EN 61140 Between main circuits  
600 V AC  
Terminal capacitiesSolid  
1 x 1.5 - 16 mm<sup>2</sup>  
Terminal capacitiesSolid or stranded  
1 x 14 - 4 AWG  
Stripping length  
13 mm  
Auxiliary and control circuits  
Rated impulse withstand voltage [ $U_{imp}$ ]

6000 V  
 Overvoltage category/pollution degree  
 III/3  
 Terminal capacitiesSolid  
 2 x (0.75 - 4) mm<sup>2</sup>  
 Terminal capacitiesFlexible with ferrule  
 2 x (0.75 - 2.5) mm<sup>2</sup>  
 Terminal capacitiesSolid or stranded  
 2 x (18 - 12) AWG  
 Terminal screw  
 M8.5  
 Tightening torque  
 0.8 - 1.2 Nm  
 Tightening torque  
 7 lb-in  
 Stripping length  
 8 mm  
 ToolsPozidriv screw driver  
 2 Size  
 ToolsStandard screw driver  
 1 x 6 mm  
 Rated insulation voltage [U<sub>0</sub>]  
 500 V AC  
 Rated operational voltage [U<sub>e</sub>]  
 500 V AC  
 Safe isolation to EN 61140 between the auxiliary contacts  
 240 V AC  
 Conventional thermal current [I<sub>th</sub>]  
 5 A  
 Rated operational current [I<sub>e</sub>]AC-15Make contact120 V [I<sub>e</sub>]  
 1.5 A  
 Rated operational current [I<sub>e</sub>]AC-15Make contact220 V 230 V 240 V [I<sub>e</sub>]  
 1.5 A  
 Rated operational current [I<sub>e</sub>]AC-15Make contact380 V 400 V 415 V [I<sub>e</sub>]  
 0.5 A  
 Rated operational current [I<sub>e</sub>]AC-15Make contact500 V [I<sub>e</sub>]  
 0.5 A  
 Rated operational current [I<sub>e</sub>]AC-15Break contact120 V [I<sub>e</sub>]  
 1.5 A  
 Rated operational current [I<sub>e</sub>]AC-15Break contact220 V 230 V 240 V [I<sub>e</sub>]  
 1.5 A  
 Rated operational current [I<sub>e</sub>]AC-15Break contact380 V 400 V 415 V [I<sub>e</sub>]  
 0.9 A  
 Rated operational current [I<sub>e</sub>]AC-15Break contact500 V [I<sub>e</sub>]  
 0.8 A  
 Rated operational current [I<sub>e</sub>]DC L/R □ 15 ms  
 Switch-on and switch-off conditions based on DC-13, time constant as specified.  
 Rated operational current [I<sub>e</sub>]DC L/R □ 15 ms24 V [I<sub>e</sub>]  
 0.9 A  
 Rated operational current [I<sub>e</sub>]DC L/R □ 15 ms60 V [I<sub>e</sub>]  
 0.75 A  
 Rated operational current [I<sub>e</sub>]DC L/R □ 15 ms110 V [I<sub>e</sub>]  
 0.4 A  
 Rated operational current [I<sub>e</sub>]DC L/R □ 15 ms220 V [I<sub>e</sub>]  
 0.2 A  
 Short-circuit rating without weldingmax. fuse  
 6 A gG/gL  
 Rating data for approved types  
 Auxiliary contactsPilot Duty AC operated  
 B600  
 Auxiliary contactsPilot Duty DC operated  
 R300  
 Short Circuit Current Rating600 V High FaultSCCR (fuse)  
 100 kA  
 Short Circuit Current Rating600 V High Faultmax. Fuse  
 60 Class J A

Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [ $I_h$ ]  
20 A

Heat dissipation per pole, current-dependent [ $P_{vid}$ ]  
0.77 W

Equipment heat dissipation, current-dependent [ $P_{vid}$ ]  
2.3 W

Static heat dissipation, non-current-dependent [ $P_{s}$ ]  
0 W

Heat dissipation capacity [ $P_{diss}$ ]  
0 W

Operating ambient temperature min.  
-25 °C

Operating ambient temperature max.  
+65 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance  
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures  
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation  
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions  
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES  
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances  
Meets the product standard's requirements.

10.5 Protection against electric shock  
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components  
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections  
Is the panel builder's responsibility.

10.8 Connections for external conductors  
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength  
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage  
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material  
Is the panel builder's responsibility.

10.10 Temperature rise  
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function  
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Electronic overload relay (EC001080)  
Electric engineering, automation, process control engineering / Low-voltage switch technology / Overload protection device / Electronic overload relay (ecl@ss10.0.1-27-37-15-02 [AKF076014])  
Adjustable current range  
4 - 20 A  
Mounting method


Separate positioning  
Type of electrical connection of main circuit  
Screw connection  
Number of auxiliary contacts as normally closed contact  
1  
Number of auxiliary contacts as normally open contact  
1  
Number of auxiliary contacts as change-over contact  
0  
Rated control supply voltage  $U_s$  at AC 50HZ  
0 - 0 V  
Rated control supply voltage  $U_s$  at AC 60HZ  
0 - 0 V  
Rated control supply voltage  $U_s$  at DC  
0 - 0 V  
Release class  
Adjustable  
Voltage type for actuating  
Self powered  
Reset function automatic  
Yes  
Reset function input  
No  
Reset function push-button  
Yes

## Approvals


Product Standards  
UL 508; CSA-C22.2 No. 14; IEC/EN 60947-4-1; CE marking  
UL File No.  
E1230  
UL Category Control No.  
NKCR  
CSA File No.  
2290956  
CSA Class No.  
3211-03  
North America Certification  
UL listed, CSA certified  
Specially designed for North America  
No  
Suitable for  
Branch circuits  
Max. Voltage Rating  
600 V AC  
Degree of Protection  
IEC: IP20, UL/CSA Type: -

## Characteristics

Characteristic curve



## Dimensions



## CAD data

- Product-specific CAD data  
(Web)

- [3D Preview](#)  
(Web)

## DWG files

- [DA-CD-zeb32\\_kk](#)  
File  
(Web, Language independent)


## edz files

- [DA-CE-ETN ZEB32-20\\_KK](#)  
File  
(Web)

## Step files

- [DA-CS-zeb32\\_kk](#)  
File  
(Web, Language independent)

## 3D drawing

-   
[2327DRW-7](#)  
Line drawing  
electronic overload relays


## Product photo

-   
[2327PIC-23](#)  
Photo  
Electronic overload relays



## Dimensions single product

-   
[2327DIM-2](#)  
Line drawing
-   
[2327DIM-4](#)  
Line drawing  
electronic overload relays

## Characteristic curve

-   
[2327DIA-5](#)  
Coordinate visualization

## Wiring diagram

-   
**000S015**  
Line drawing  
Overload release symbol
-   
**230S005**  
Line drawing  
Overload relay circuit symbol

## Instruction Leaflet

- [Solid-state motor protection relay \(IL04210002E\)](#)  
Asset  
(PDF, multilingual)

## Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH