



289240
M22-WRJ2V

[Overview](#)

[Specifications](#)

[Resources](#)



DELIVERY PROGRAM

[Delivery program](#)

Product range
RMQ-Titan

[Technical data](#)

Basic function
Joystick

[Design verification as
per IEC/EN 61439](#)

Mounting hole diameter [□]
22.5 mm

[Technical data ETIM 7.0](#)

Single unit/Complete unit
Single unit

[Approvals](#)

Function: [□ = spring-return]

[Dimensions](#)

Function



Description

with one operating point per operating direction

With plastic shaft

2 positions

Degree of Protection
IP66

Front ring
Bezel: titanium

Connection to SmartWire-DT
yes
with SWD-RMQ connections

Function
maintained
Vertical

TECHNICAL DATA

General

Standards
IEC/EN 60947
VDE 0660

Lifespan, mechanical [Operations]
 $> 0.1 \times 10^6$

Operating frequency [Operations/h]
 2000

Actuating force
 5 N

Climatic proofing
Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30

Degree of Protection
IP66

Ambient temperature
Open
-25 - +70 °C

Mounting position
As required

Mechanical shock resistance
30
Shock duration 11 ms
Sinusoidal
according to IEC 60068-2-27 g

Shipping classification
DNV
GL
LR



DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_h]
0 A

Heat dissipation per pole, current-dependent [P_{vid}]
0 W

Equipment heat dissipation, current-dependent [P_{vid}]
0 W

Static heat dissipation, non-current-dependent [P_{vs}]
0 W

Heat dissipation capacity [P_{diss}]

0 W

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2 Strength of materials and parts

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The

specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Control switch, Joystick (EC000632)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Control switch, joystick (ecl@ss10.0.1-27-37-14-04 [AKF061013])

Rated operation current I_e at AC-21, 400 V
0 A

Centre mounting, hole diameter
22.5 mm

Joy stick length
75 mm

Number of actuation directions
2

Number of switch levels
0

Number of normally open contacts per actuation direction
0

Number of normally closed contacts per actuation direction
0

Number of make-and-break contacts per direction
0

With retraction in 0-position

No

Locking in 0-position
No

Coder
No

Analogue output signal configurable
No

With front ring
Yes

Material front ring
Plastic

Colour front ring
Chrome

Degree of protection (IP)
IP66

Degree of protection (NEMA)
4X

APPROVALS

Product Standards
IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05;
CSA-C22.2 No. 94-91; CE marking

UL File No.
E29184

UL Category Control No.
NKCR

CSA File No.
012528

CSA Class No.

3211-03

North America Certification
UL listed, CSA certified

Degree of Protection
UL/CSA Type 3R, 4X, 12, 13

DIMENSIONS



