



121463

M22-PVT45P-MPI

[Overview](#)[Specifications](#)[Resources](#)

DELIVERY PROGRAM

[Delivery program](#)

Product range

RMQ-Titan

[Technical data](#)

Basic function

Controlled stop pushbuttons/emergency-stop
buttons[Technical data ETIM 7.0](#)

Mounting hole diameter [□]

22.5 mm

[Approvals](#)

Single unit/Complete unit

Single unit

[Dimensions](#)

Design

Palm-tree shape

Diameter [□]

45 mm

Illumination

Non-illuminated

Turn-to-release function

Description

Tamper-proof according to ISO 13850/EN 418

with mechanical switch position indication
Switch position indicator red pushbutton actuated
Switch position indication green pushbutton
released

Colour

Mushroom head
Red



Base
yellow

RAL 3000

Degree of Protection
IP66, IP67, IP69

Connection to SmartWire-DT
no

Instructions

Max. number of contacts: four M22-(C)K01, ...10
or two M22-(C)K02, ...20, ...11

TECHNICAL DATA

General

Standards
IEC/EN 60947

Lifespan, mechanical [Operations]
 $> 0.1 \times 10^6$

Operating frequency [Operations/h]
 600

Actuating force
 50 n

Climatic proofing
Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30

Degree of Protection
IP66, IP67, IP69

Ambient temperature
Open
-25 - +70 °C

Mounting position
As required

Mechanical shock resistance
50
Shock duration 11 ms
Sinusoidal
according to IEC 60068-2-27 g

Shipping classification
DNV
GL
LR



DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_h]
0 A

Heat dissipation per pole, current-dependent [P_{vid}]
0 W

Equipment heat dissipation, current-dependent [P_{vid}]
0 W

Static heat dissipation, non-current-dependent [P_{vs}]
0 W

Heat dissipation capacity [P_{diss}]
0 W

Operating ambient temperature min.
-25 °C

Operating ambient temperature max.
+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.4 Resistance to ultra-violet (UV) radiation
Please enquire

10.2 Strength of materials and parts
10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.

10.8 Connections for external conductors
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Front element for mushroom push-button (EO001038)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for mushroom push-button actuators (ecl@ss10.0.1-27-37-12-12 [AKF030014])

Colour button
Red

Construction type lens
Round

Diameter cap
45 mm

Hole diameter
22.5 mm

Width opening
0 mm

Height opening
0 mm

Degree of protection (IP)
IP67/IP69K

Degree of protection (NEMA)
4X

Type of button
Flat

Suitable for illumination
No

Switching function latching
Yes

Spring-return
No

With front ring
No

Material front ring
Other

Colour front ring
Other

Suitable for emergency stop
Yes

Unlocking method
Turn-release

APPROVALS

DIMENSIONS



