

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NZMH3-4-VE630 - Circuit-breaker, 4p, 630A



265966 NZMH3-4-VE630

[Overview](#) [Specifications](#) [Resources](#)



265966 NZMH3-4-VE630

Circuit-breaker, 4p, 630A

EL-Nummer (Norway)

4358867

Circuit-breaker NZM3, 4 pole, Switching capacity 400/415 V 50 Hz(I_{cu}): 150 kA, Rated current = rated uninterrupted current Rated current = rated uninterrupted current(I_n = I_u): 630 A, Installation type: Fixed, Screw connection, Standard/Approval: IEC, Protective function: Systems, cable, selectivity and generator protection

- Delivery program
- Technical data
- Design verification as per IEC/EN 61439
- Technical data ETIM 7.0
- Characteristics
- Dimensions

Delivery program

Product range

Circuit-breaker

Protective function

Systems, cable, selectivity and generator protection

Standard/Approval

IEC

Installation type

Fixed

Release system

Electronic release

Construction size

NZM3

Description

R.m.s. value measurement and "thermal memory"

Adjustable time delay setting to overcome current peaks t_r at $6 \times I_r$ also infinity (without overload releases)

Adjustable delay time t_{sd}

i^2t constant function: switchable

Number of poles

4 pole

Standard equipment

Screw connection

Switching capacity

400/415 V 50 Hz [I_{cu}]

150 kA

Rated current = rated uninterrupted current [I_n = I_u]

Rated current = rated uninterrupted current [$I_n = I_u$]
 630 A
 Neutral conductor [% of phase conductor]
 100 %
Setting range
 Overload trip I_r [I_r]
 315 - 630 A
 Overload trip Main pole I_r [I_r]
 315 - 630 A
 Short-circuit releases I_{rm} [I_{rm}] Non-delayed I_{rs} [$I_{rs} = I_n \times \dots$]
 2 - 8
 Short-circuit releases I_{rm} [I_{rm}] Delayed I_{sd} [$I_{sd} = I_r \times \dots$]
 1.5 - 7

Technical data

General

Standards

IEC/EN 60947

Protection against direct contact

Finger and back of hand proof to VDE 0106 Part 100

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature Ambient temperature, storage

- 40 - + 70 °C

Ambient temperature Operation

-25 - +70 °C

Mechanical shock resistance (10 ms half-sinusoidal shock) according to IEC 60068-2-27

20 (half-sinusoidal shock 20 ms) g

Safe isolation to EN 61140 Between auxiliary contacts and main contacts

500 V AC

Safe isolation to EN 61140 between the auxiliary contacts

300 V AC

Mounting position

Vertical and 90° in all directions
<input type="checkbox"/> With XFI earth-fault release:
- NZM1, N1, NZM2, N2: vertical and 90° in all directions
with plug-in unit
- NZM1, N1, NZM2, N2: vertical, 90° right/left
with withdrawable unit:
- NZM3, N3: vertical, 90° right/left
- NZM4, N4: vertical
with remote operator:
- NZM2, N(S)2, NZM3, N(S)3, NZM4, N(S)4: vertical and 90° in all directions

Direction of incoming supply

as required

Degree of protection Device

In the operating controls area: IP20 (basic degree of protection)

Degree of protection Enclosures

With insulating surround: IP40

With door coupling rotary handle: IP66

Degree of protection Terminations

Tunnel terminal: IP10

Phase isolator and strip terminal: IP00

Other technical data (sheet catalogue)

[Temperature dependency, Derating](#)

Circuit-breakers

Rated current = rated uninterrupted current [$I_n = I_u$]

630 A

Rated surge voltage invariability [U_{imp}] Main contacts

8000 V

Rated surge voltage invariability [U_{imp}] Auxiliary contacts

6000 V

Rated operational voltage [U_e]

690 V AC

Overvoltage category/pollution degree
 III/3
 Rated insulation voltage [U]
 1000 V
 Use in unearthed supply systems
 690 V
 Switching capacity
 Rated short-circuit making capacity [I_{cm}]240 V [I_{cm}]
 330 kA
 Rated short-circuit making capacity [I_{cm}]400/415 V [I_{cm}]
 330 kA
 Rated short-circuit making capacity [I_{cm}]440 V 50/60 Hz [I_{cm}]
 286 kA
 Rated short-circuit making capacity [I_{cm}]525 V 50/60 Hz [I_{cm}]
 143 kA
 Rated short-circuit making capacity [I_{cm}]690 V 50/60 H [I_{cm}]
 74 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}]I_{cu} to IEC/EN 60947 test cycle O-t-OO [I_{cu}]240 V 50/60 Hz [I_{cu}]
 150 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}]I_{cu} to IEC/EN 60947 test cycle O-t-OO [I_{cu}]400/415 V 50/60 Hz [I_{cu}]
 150 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}]I_{cu} to IEC/EN 60947 test cycle O-t-OO [I_{cu}]440 V 50/60 Hz [I_{cu}]
 130 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}]I_{cu} to IEC/EN 60947 test cycle O-t-OO [I_{cu}]525 V 50/60 Hz [I_{cu}]
 65 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}]I_{cu} to IEC/EN 60947 test cycle O-t-OO [I_{cu}]690 V 50/60 Hz [I_{cu}]
 35 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}]I_{cs} to IEC/EN 60947 test cycle O-t-OO-t-OO [I_{cs}]240 V 50/60 Hz [I_{cs}]
 150 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}]I_{cs} to IEC/EN 60947 test cycle O-t-OO-t-OO [I_{cs}]400/415 V 50/60 Hz [I_{cs}]
 150 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}]I_{cs} to IEC/EN 60947 test cycle O-t-OO-t-OO [I_{cs}]440 V 50/60 Hz [I_{cs}]
 130 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}]I_{cs} to IEC/EN 60947 test cycle O-t-OO-t-OO [I_{cs}]525 V 50/60 Hz [I_{cs}]
 33 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}]I_{cs} to IEC/EN 60947 test cycle O-t-OO-t-OO [I_{cs}]690 V 50/60 Hz [I_{cs}]
 9 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}]
 Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit-breaker.
 Rated short-time withstand current I_{ts} = 0.3 s [I_{ts}]
 3.3 kA
 Rated short-time withstand current I_{ts} = 1 s [I_{ts}]
 3.3 kA
 Utilization category to IEC/EN 60947-2
 A
 Lifespan, mechanical(of which max. 50 % trip by shunt/undervoltage release) [Operations]
 15000
 Lifespan, electricalAC-1400 V 50/60 Hz [Operations]
 5000
 Lifespan, electricalAC-1415 V 50/60 Hz [Operations]
 5000
 Lifespan, electricalAC-1690 V 50/60 Hz [Operations]
 3000
 Lifespan, electricalAC-3400 V 50/60 Hz [Operations]
 2000
 Lifespan, electricalAC-3415 V 50/60 Hz [Operations]
 2000
 Lifespan, electricalAC-3690 V 50/60 Hz [Operations]
 2000
 Lifespan, electricalMax. operating frequency
 60 Ops/h
 Total break time at short-circuit
 < 10 ms
Terminal capacity
 Standard equipment
 Screw connection
 Optional accessories
 Box terminal

Tunnel terminal
 connection on rear
 Round copper conductor Box terminal Solid
 2 x 16 mm²
 Round copper conductor Box terminal Stranded
 1 x (35 - 240)
 2 x (25-120) mm²
 Round copper conductor Tunnel terminal Solid
 1 x 16 mm²
 Round copper conductor Tunnel terminal Stranded 1-hole
 1 x (16 - 185) mm²
 Round copper conductor Tunnel terminal Stranded Double hole fitting
 2 x (50 - 240) mm²
 Round copper conductor Bolt terminal and rear-side connection Direct on the switch Solid
 1 x 16
 2 x 16 mm²
 Round copper conductor Bolt terminal and rear-side connection Direct on the switch Stranded
 1 x (25 - 240)
 2 x (25 - 240) mm²
 Round copper conductor Bolt terminal and rear-side connection Connection width extension Connection width extension
 2 x 300 mm²
 Al circular conductor Tunnel terminal Solid
 1 x 16 mm²
 Al circular conductor Tunnel terminal Stranded Stranded
 1 x (25 - 185)²⁾ mm²
 Al circular conductor Tunnel terminal Stranded Double hole
 1 x (50 - 240)
 2 x (50 - 240) mm²
 Al circular conductor Tunnel terminal Stranded
²⁾ Up to 240 mm² can be connected depending on the cable manufacturer.
 Al circular conductor Bolt terminal and rear-side connection Direct on the switch Solid
 1 x 16
 2 x (10 - 16) mm²
 Al circular conductor Bolt terminal and rear-side connection Direct on the switch Stranded
 1 x (25 - 120)
 2 x (25 - 120) mm²
 Cu strip (number of segments x width x segment thickness) Box terminal [min.]
 6 x 16 x 0.8 mm
 Cu strip (number of segments x width x segment thickness) Box terminal [max.]
 10 x 24 x 1.0
 + 5 x 24 x 1.0
 (2 x) 8 x 24 x 1.0 mm
 Cu strip (number of segments x width x segment thickness) Bolt terminal and rear-side connection Flat copper strip,
 with holes [min.]
 6 x 16 x 0.8 mm
 Cu strip (number of segments x width x segment thickness) Bolt terminal and rear-side connection Flat copper strip,
 with holes [max.]
 10 x 32 x 1.0 + 5 x 32 x 1.0 mm
 Cu strip (number of segments x width x segment thickness) Bolt terminal and rear-side connection Connection width
 extension
 (2 x) 10 x 50 x 1.0 mm
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Screw connection
 M10
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Direct on the switch [min.]
 20 x 5 mm
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Direct on the switch [max.]
 30 x 10
 + 30 x 5 mm
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Connection width extension Connection
 width extension [max.]
 2 x (10 x 50) mm
 Control cables
 1 x (0.75 - 2.5)
 2 x (0.75 - 1.5) mm²

Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_r]

630 A

Equipment heat dissipation, current-dependent [P_{id}]

178.61 W

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss10.0.1-27-37-04-09 [AJZ716013])

Rated permanent current I_u

630 A

Rated voltage

690 - 690 V

Rated short-circuit breaking capacity I_{cu} at 400 V, 50 Hz

150 kA

Overload release current setting


315 - 630 A

Adjustment range short-term delayed short-circuit release

472 - 4410 A
 Adjustment range undelayed short-circuit release
 1260 - 5040 A
 Integrated earth fault protection
 No
 Type of electrical connection of main circuit
 Screw connection
 Device construction
 Built-in device fixed built-in technique
 Suitable for DIN rail (top hat rail) mounting
 No
 DIN rail (top hat rail) mounting optional
 No
 Number of auxiliary contacts as normally closed contact
 0
 Number of auxiliary contacts as normally open contact
 0
 Number of auxiliary contacts as change-over contact
 0
 With switched-off indicator
 No
 With under voltage release
 No
 Number of poles
 4
 Position of connection for main current circuit
 Front side
 Type of control element
 Rocker lever
 Complete device with protection unit
 Yes
 Motor drive integrated
 No
 Motor drive optional
 Yes
 Degree of protection (IP)
 IP20

Characteristics

Characteristic curve



Characteristic curve


Let-through current

Characteristic curve


Let-through energy

Characteristic curve

Dimensions



- Blow out area, minimum clearance to adjacent parts
- Minimum clearance to adjacent parts



CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)

DWG files

- [DA-CD-nzm3_4p](#)
File
(Web)

edz files

- [DA-CE-ETN.NZMH3-4-VE630](#)
File
(Web)


Step files


- [DA-CS-nzm3_4p](#)
File
(Web)

Additional product information


- [Temperature dependency, Derating](#)
(Web)
- [CurveSelect characteristics program](#)
(Web)
- [Eaton configurator](#)
(Web)
- [additional technical information for NZM power switch](#)
(PDF)

Dimensions single product

- 
[123X332](#)
Line drawing
Circuit-breakers
 Blow out area, minimum clearance to adjacent parts
 Minimum clearance to adjacent parts
 Does not apply to DC applications

- 
[123X553](#)
Line drawing
Circuit-breakers, switch-disconnectors

3D drawing

- 
[123I612](#)
Line drawing


Product photo



1230PIC-705

Photo

Characteristic curve

- [1230DIA-11](#)
Coordinate visualization
Let-through current
- [1230DIA-21](#)
Coordinate visualization
Let-through energy
- [123U172](#)
Coordinate visualization
NZMB-VE250...630 tripping characteristic
- 
[123U183](#)
Coordinate visualization
NZMB-VE250...630 tripping characteristic

Instruction Leaflet

- [IL01208009Z](#)
Asset
(PDF, Language independent)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH