

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



Powering Business Worldwide

M22-XAK11 - Label, emergency stop, D=90mm, yellow, DE, EN, FR, IT



121085 M22-XAK11

[Overview](#) [Specifications](#) [Resources](#)



121085 M22-XAK11

Label, emergency stop, D=90mm, yellow, DE, EN, FR, IT

Alternate Catalog No.

M22-XAK11Q

EL-Nummer (Norway)

4315237

Emergency stop label, Product range: Accessories, RAL 1004, Connection to SmartWire-DT: no

• [Delivery program](#)

• [Technical data](#)

• [Design verification as per IEC/EN 61439](#)

• [Technical data ETIM 7.0](#)

• [Approvals](#)

• [Dimensions](#)

Delivery program

Product range

Accessories

Basic function accessories

Emergency stop labels

Form

Diameter = 90 mm

Name

quadrilingual

Language

de, en, fr, it

Colour

RAL 1004

RAL Value

RAL 1004

Degree of Protection

IP66

Connection to SmartWire-DT

no

Notes

Lettering black

Technical data

General
Degree of Protection
IP66
Ambient temperatureOpen
-25 - +70 °C
shipping classification
DNV
GL
LR



Germanischer Lloyd



Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_n]

0 A

Heat dissipation per pole, current-dependent [P_{vd}]

0 W

Equipment heat dissipation, current-dependent [P_{vd}]

0 W

Static heat dissipation, non-current-dependent [P_{vs}]

0 W

Heat dissipation capacity [P_{diss}]

0 W

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2 Strength of materials and parts10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Text plate for control circuit devices (EC000624)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Identification plate for command devices (ecl@ss10.0.1-27-37-12-25 [AKF043014])

Imprint

Other

Imprint ISO symbols

Other

Colour

Yellow

Shape

Round

Width

90 mm

Height

90 mm

Outer diameter


90 mm

Approvals

North America Certification

UL/CSA certification not required

Dimensions



CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)

DWG files

- [DA-CD-not_aus_schild_xak](#)
File
(Web)

Step files

- [DA-CS-not_aus_schild_xak](#)
File
(Web)


Product photo



1160PIC-1185

Photo

Dimensions single product

- 
116X128
Line drawing
Emergency-Stop label

3D drawing

- 
1160DRW-258
Line drawing

Symbol

- 
Germanischer Lloyd
0000SFC-180
Graphic
Germanischer Lloyd approval for Germany (color logo)
- 
0000SFC-183
Logo
Approval Norway Det Norske Veritas DNV

Instruction Leaflet

- [RMQ-Titan System \(IL04716002Z\)](#)
Asset
former AWA1160-1745, IL04716001E
(PDF, 09/2020, multilingual)

StandardsSymbol

- 
0000SFC-179
Graphic
Lloyd's Register approval for Great Britain

Declaration of Conformity

UK

- [AS-i interface / AS-i safety interface \(DA-DC-00003973\)](#)
Asset
(PDF)

Download-Center

- [Download-Center \(this item\)](#)

Eaton EMEA Download-Center - download data for this item

- [Download-Center](#)

Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

