



102969

MSC-D-2,5-M7(24VDC)/BBA

Overview

Specifications

Resources



Delivery program

Technical data

Design verification as per IEC/EN 61439

Technical data ETIM7.0

Approvals

Dimensions

DELIVERY PROGRAM

Basic function
DOL starters (complete devices)

Basic device
MSC



Notes
Also suitable for motors with efficiency class IE3.

Connection technique
Screw terminals

Connection to SmartWire-DT
no

Motor ratings

Motor rating [P]
AC-3
380 V 400 V 415 V [P]
0.75 kW

Rated operational current
AC-3
380 V 400 V 415 V [I_e]
1.9 A

Rated short-circuit current 380 - 415 V [I_k]
100 kA

Setting range

Setting range of overload releases  [I_n]
1.6 - 2.5 A

Coordination
Type of coordination "1"
Type of coordination "2"

Contact sequence



Actuating voltage
24 V DC

DC voltage

Motor-protective circuit-breakers
PKZM0-2,5 Type

Contactor
DILM7-10(...) Part no.

DOL starter wiring set

Mechanical connection element and electrical
electric contact module
PKZM0-XDM12 Type

Notes

BK25/3-PKZ0-E extension terminal and if necessary B3.../...-PKZ0 three-phase commoning link can be added to motor-starter combinations to make Type F starters in accordance with UL508.

Notes

The DOL starters (complete units) consist of a PKZM0 motor protective circuit breaker and a DILM contactor. These combinations are mounted on the busbar adapters.

The connection of the main circuit between the motor protective circuit breaker and the contactor is established with an electrical contact module.

Cannot be combined with NH-E...-PKZ0-C standard auxiliary contact with spring-cage terminal.

Further information	Page
Technical data PKZM0	□ PKZM0
Accessories PKZ	□ 072896
Technical data DILM	□ DILM
Accessories DILM	□ 281199

TECHNICAL DATA

General

Standards

UL 508 (on request)
CSA C22.2 No. 14 (on request)

Altitude
Max. 2000 m

Ambient temperature
-25 - +55

Main conducting paths

Rated impulse withstand voltage [U_{imp}]
6000 V AC

Overvoltage category/pollution degree
III/3

Rated operational voltage [U_e]
230 - 415 V

Rated operational current
Open, 3-pole: 50 – 60 Hz
380 V 400 V [I_e]
2.5 A

Additional technical data

Motor protective circuit breaker PKZM0, PKE
PKZM0 motor-protective circuit-breakers, see
motor-protective circuit-breakers/PKZM0 product
group
DILM contactors, see contactor product group
DILET timing relay, ETR, see contactors, electronic
timing relays product group

Power consumption

DC operated [Sealing]
3 W

Rating data for approved types

Auxiliary contacts
Pilot Duty
AC operated
A600

Auxiliary contacts
Pilot Duty
DC operated
P300

Auxiliary contacts
General Use
AC
600 V

Auxiliary contacts
General Use
AC
15 A

Auxiliary contacts
General Use
DC
250 V

Auxiliary contacts
General Use
DC
1 A

DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat
dissipation [I_h]
2.5 A

Heat dissipation per pole, current-dependent [P_{vid}]
1.9 W

Equipment heat dissipation, current-dependent
[P_{vid}]
5.7 W

Static heat dissipation, non-current-dependent [P_{vs}]
2.6 W

Heat dissipation capacity [P_{diss}]
0 W

Operating ambient temperature min.
-25 °C

Operating ambient temperature max.
+55 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs

to be evaluated.

10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.

10.8 Connections for external conductors
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.

10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Motor starter/Motor starter combination (EQ001037)

Kind of motor starter
Direct starter

With short-circuit release
Yes

Rated control supply voltage U_s at AC 50HZ
0 - 0 V

Rated control supply voltage U_s at AC 60HZ
0 - 0 V

Rated control supply voltage U_s at DC
24 - 24 V

Voltage type for actuating
DC

Rated operation power at AC-3, 230 V, 3-phase
0.37 kW

Rated operation power at AC-3, 400 V
0.75 kW

Rated power, 460 V, 60 Hz, 3-phase
0 kW

Rated power, 575 V, 60 Hz, 3-phase
0 kW

Rated operation current I_e
1.9 A

Rated operation current at AC-3, 400 V
2.5 A

Overload release current setting
1.6 - 2.5 A

Rated conditional short-circuit current, type 1, 480
Y/277 V

0 A

Rated conditional short-circuit current, type 1, 600
Y/347 V
0 A

Rated conditional short-circuit current, type 2, 230
V
50000 A

Rated conditional short-circuit current, type 2, 400
V
50000 A

Number of auxiliary contacts as normally open
contact
1

Number of auxiliary contacts as normally closed
contact
0

Ambient temperature, upper operating limit
60 °C

Temperature compensated overload protection
Yes

Release class
CLASS 10

Type of electrical connection of main circuit
Screw connection

Type of electrical connection for auxiliary- and
control current circuit
Screw connection

Rail mounting possible
Yes

With transformer
No

Number of command positions
0

Suitable for emergency stop
No

Coordination class according to IEC 60947-4-3
Class 2

Number of indicator lights
0

External reset possible
No

With fuse
No

Degree of protection (IP)
IP20

Degree of protection (NEMA)
Other

Supporting protocol for TCP/IP
No

Supporting protocol for PROFIBUS
No

Supporting protocol for CAN
No

Supporting protocol for INTERBUS
No

Supporting protocol for ASI
No

Supporting protocol for MODBUS
No

Supporting protocol for Data-Highway
No

Supporting protocol for DeviceNet
No

Supporting protocol for SUCONET
No

Supporting protocol for LON
No

Supporting protocol for PROFINET IO
No

Supporting protocol for PROFINET CBA
No

Supporting protocol for SERCOS
No

Supporting protocol for Foundation Fieldbus
No

Supporting protocol for EtherNet/IP
No

Supporting protocol for AS-Interface Safety at
Work
No

Supporting protocol for DeviceNet Safety
No

Supporting protocol for INTERBUS-Safety
No

Supporting protocol for PROFIsafe
No

Supporting protocol for SafetyBUS p
No

Supporting protocol for other bus systems
No

Width

45 mm

Height
200 mm

Depth
154 mm

APPROVALS

Product Standards
UL60947-4-1A; CSA-C22.2 No. 14-10; IEC60947-4-1; CE marking

UL File No.
E123500

UL Category Control No.
NKJH


CSA File No.
12528

CSA Class No.
3211-04

North America Certification
UL listed, CSA certified

Specially designed for North America
No

DIMENSIONS



□ | = 73 mm

MSC-D...-M7[...15]BBA...

