



- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



M22-XYK1 - Label, emergency switching off, yellow, HxW=50x50mm, 4 languages, DE, EN, FR, IT



216484 M22-XYK1

[Overview](#) [Specifications](#) [Resources](#)



- Delivery program
- Technical data
 - Design verification as per IEC/EN 61439
- Technical data ETIM 7.0
- Approvals
- Dimensions

216484 M22-XYK1

Label, emergency switching off, yellow, HxW=50x50mm, 4 languages, DE, EN, FR, IT

Alternate Catalog No.

M22-XYK1Q

EI-Nummer (Norway)

4315294

Emergency-Stop label, Product range: Accessories, yellow, Connection to SmartWire-DT: no

Delivery program

Product range

Accessories

Basic function accessories

Emergency-stop labels

Form

50 x 50 mm

Name

Four languages

Language

de, en, fr, it

Colour

yellow



RAL Value

RAL 1004

Degree of Protection

IP66

Connection to SmartWire-DT

no

Notes

Technical data

General

Degree of Protection

IP66

Ambient temperature Open


-25 - +70 °C

shipping classification

DNV

GL

LR



Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_h]

0 A

Heat dissipation per pole, current-dependent [P_{vid}]

0 W

Equipment heat dissipation, current-dependent [P_{vid}]

0 W

Static heat dissipation, non-current-dependent [P_{vs}]

0 W

Heat dissipation capacity [P_{diss}]

0 W

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.
10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.
10.10 Temperature rise
Not applicable.
10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Text plate for control circuit devices (EO000624)
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Identification plate for command devices (ecl@ss10.0.1-27-37-12-25 [AKF043014])
Imprint
Other
Imprint ISO symbols
Other
Colour
Yellow
Shape
Square
Width
50 mm
Height
50 mm
Outer diameter
0 mm

Approvals

North America Certification
UL/CSA certification not required

Dimensions



CAD data

- [Product-specific CAD data \(Web\)](#)
- [3D Preview \(Web\)](#)

DWG files

- [DA-CD-not_aus_schild_xyk File \(Web\)](#)

Step files

- [DA-CS-not_aus_schild_xyk File \(Web\)](#)

3D drawing

- [1161246 Line drawing Emergency-Stop label](#)

Dimensions single product

- **116X091**
Line drawing
Emergency-Stop label

Product photo



- **1160PIC-97**
Photo
Emergency-Stop labels

Symbol

- 
Germanischer Lloyd
0000SPC-180
Graphic
Germanischer Lloyd approval for Germany (color logo)
- 
DNV
0000SPC-183
Logo
Approval Norway Det Norske Veritas DNV
- 
1160064
Graphic
Button plate, yellow

StandardsSymbol

- 
0000SPC-179
Graphic
Lloyd's Register approval for Great Britain

Instruction Leaflet

- [RMQ-Titan System \(IL04716002Z\)](#)
Asset
former AWA1160-1745, IL04716001E
(PDF, 09/2020, multilingual)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



Generate data sheet in PDF format

[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GrbH

