



138517

PKE65/XTUW-32

[Overview](#)[Specifications](#)[Resources](#)

## DELIVERY PROGRAM

[Delivery program](#)

Product range

PKE motor-protective circuit-breaker with  
electronic wide-range overload protection up to 65  
A[Design verification as  
per IEC/EN 61439](#)

Basic function

Motor protection

Motor protection for heavy starting duty

[Technical data ETIM 7.0](#)

Single unit/Complete unit

Complete device with standard knob

[Approvals](#)[Characteristics](#)

Notes

Also suitable for motors with efficiency class IE3.

[Dimensions](#)

Connection technique

Screw terminals

Setting range of overload releases  [I]

8 - 32 A

Function

With overload release

Rated uninterrupted current = rated operational

current [ $I_u = I_e$ ]

32 A

### Motor rating [P]

AC-3

220 V 230 V 240 V [P]

7.5 kW

AC-3

380 V 400 V 415 V [P]

15 kW

AC-3

440 V [P]

15 kW

AC-3

500 V [P]

18.5 kW

AC-3

660 V 690 V [P]

30 kW

Motor output/rated motor current

Motor rating	Rated motor current
--------------	---------------------

**AC-3**

220 V	380	V	660	V
230 V	400	440	500	690
240 V	415			V

P	I	I	I	I	I
---	---	---	---	---	---

kW	A	A	A	A	A
----	---	---	---	---	---

2.2	8.7 Rated	-	-	-	-
Motor rating	motor current	-	-	-	-
4	14.8	8.5	-	-	-
5.5	19.3	11.3	10.2	9	-
7.5	26.4	15.2	13.8	12.1	8.8
11	-	21.7	19.8	17.4	12.6
15	-	29.3	26.6	23.4	17
18.5	-	36.6	44.0	50.0	60.0
22	240 V	V	V	V	V23.8
30	I-	I-	I-	I-	I-32

A A A A A

## TECHNICAL DATA

### General


Standards  
IEC/EN 60947, VDE 0660, UL, CSA

Climatic proofing  
Damp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature  
Storage  
- 40 - 80 °C

Ambient temperature  
Open  
-25 - +55 °C

Ambient temperature  
Enclosed  
- 25 - 40 °C



Direction of incoming supply  
as required

Degree of protection  
Device  
IP20

Degree of protection  
Terminations  
IP00

Protection against direct contact when actuated  
from front (EN 50274)  
Finger and back-of-hand proof

Mechanical shock resistance half-sinusoidal shock  
10 ms to IEC 60068-2-27  
15 g

Altitude  
Max. 2000 m

Terminal capacity main cable  
Screw terminals  
Solid  
1 x (0.75 - 16)  
2 x (0.75 - 16) mm<sup>2</sup>

Terminal capacity main cable  
Screw terminals  
Flexible with ferrule to DIN 46228  
1 x (0.75 - 35)  
2 x (0.75 - 25) mm<sup>2</sup>

Terminal capacity main cable  
Screw terminals  
Solid or stranded  
14 - 2 AWG

Terminal capacity main cable  
Screw terminals  
Stripping length  
14 mm

Specified tightening torque for terminal screws  
Main cable  
3.3 Nm

Specified tightening torque for terminal screws  
Control circuit cables  
1 Nm

## Main conducting paths

Rated impulse withstand voltage [ $U_{imp}$ ]  
6000 V AC

Overvoltage category/pollution degree  
III/3

Rated operational voltage [ $U_e$ ]  
690 V AC

Rated uninterrupted current = rated operational  
current [ $I_u = I_e$ ]  
32 A

Rated frequency [f]  
40 - 60 Hz

Current heat loss (3 pole at operating temperature)  
5.2 W

Lifespan, mechanical [Operations]  
 $0.05 \times 10^6$

Lifespan, electrical (AC-3 at 400 V)  
Lifespan, electrical [Operations]  
 $0.05 \times 10^6$

Max. operating frequency  
60 Ops/h

Motor switching capacity  
AC-3 (up to 690V)  
32 A

AC-4 cycle operation  
Minimum current flow times  
500 (Class 5)  
700 (Class 10)  
900 (Class 15)  
1000 (Class 20) ms

AC-4 cycle operation  
Minimum cut-out periods  
500 ms

AC-4 cycle operation

Note

In AC-4 cycle operation, going below the minimum current flow time can cause overheating of the load (motor).

For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods. ms

## Trip blocks

Temperature compensation  
to IEC/EN 60947, VDE 0660

- 5...40 °C

Temperature compensation

Operating range

- 25...55 °C

Setting range of overload releases

0.25 - 1 x  $I_u$

short-circuit release

Basic device, fixed: 15.5 x  $I_u$

Trip block, fixed: 15.5 x  $I_u$

delayed approx. 60 ms

Short-circuit release tolerance

± 20%

Phase-failure sensitivity

IEC/EN 60947-4-1, VDE 0660 Part 102

## Rating data for approved types

Switching capacity

Maximum motor rating

Three-phase

200 V

208 V

7.5 HP

Switching capacity

Maximum motor rating

Three-phase

230 V

240 V

7.5 HP

Switching capacity  
Maximum motor rating  
Three-phase  
460 V  
480 V  
20 HP

Switching capacity  
Maximum motor rating  
Three-phase  
575 V  
600 V  
25 HP

Switching capacity  
Maximum motor rating  
Single-phase  
115 V  
120 V  
2 HP

Switching capacity  
Maximum motor rating  
Single-phase  
230 V  
240 V  
3 HP

Switching capacity  
General use  
32 A

Short Circuit Current Rating, group protection  
600 V High Fault  
SCCR (fuse)  
100 kA

Short Circuit Current Rating, group protection  
600 V High Fault  
max. Fuse  
200 Class JA

## DESIGN VERIFICATION AS PER IEC/EN 61439

### Technical data for design verification

Rated operational current for specified heat dissipation [ $I_h$ ]

32 A

Heat dissipation per pole, current-dependent [ $P_{vid}$ ]  
1.7 W

Equipment heat dissipation, current-dependent  
[ $P_{vid}$ ]  
5.2 W

Static heat dissipation, non-current-dependent [ $P_{vs}$ ]  
0 W

Heat dissipation capacity [ $P_{diss}$ ]  
0 W

Operating ambient temperature min.  
-25 °C

Operating ambient temperature max.  
+55 °C

### IEC/EN 61439 design verification

10.2 Strength of materials and parts  
10.2.2 Corrosion resistance  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.1 Verification of thermal stability of  
enclosures  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.2 Verification of resistance of insulating  
materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.3 Verification of resistance of insulating  
materials to abnormal heat and fire due to internal  
electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.4 Resistance to ultra-violet (UV) radiation  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.5 Lifting  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.6 Mechanical impact  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.7 Inscriptions  
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES  
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances  
Meets the product standard's requirements.

10.5 Protection against electric shock  
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components  
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections  
Is the panel builder's responsibility.

10.8 Connections for external conductors  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.2 Power-frequency electric strength  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.3 Impulse withstand voltage  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

#### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Motor protection circuit-breaker (EO000074)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Motor protection circuit-breaker (ec1@ss10.0.1-27-37-04-01 [AGZ529016])

Overload release current setting  
8 - 32 A

Adjustment range undelayed short-circuit release  
496 - 496 A

With thermal protection  
Yes

Phase failure sensitive  
Yes

Switch off technique  
Electronic

Rated operating voltage  
690 - 690 V

Rated permanent current  $I_{\text{p}}$   
32 A

Rated operation power at AC-3, 230 V  
7.5 kW

Rated operation power at AC-3, 400 V  
15 kW

Type of electrical connection of main circuit  
Screw connection

Type of control element  
Turn button

Device construction  
Built-in device fixed built-in technique

With integrated auxiliary switch  
No

With integrated under voltage release  
No

Number of poles  
3

Rated short-circuit breaking capacity  $I_{\text{cu}}$  at 400 V,  
AC  
0 kA

Degree of protection (IP)  
IP20

Height  
162 mm

Width  
55 mm

Depth  
187 mm

## APPROVALS

Product Standards  
IEC/EN 60947-4-1; UL 60947-4-1; CSA - C22.2 No.  
60947-4-1-14; CE marking

UL File No.  
E36332

UL Category Control No.  
NLRV

CSA File No.  
165628


CSA Class No.  
3211-05

North America Certification  
UL listed, CSA certified

Specially designed for North America  
No

## CHARACTERISTICS

Characteristic curve



Tripping characteristics

Characteristic curve



Let-through current

Characteristic curve



1 half-cycle

Let-through energy

## DIMENSIONS



