

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



Powering Business Worldwide

NZMH2-A25-SVE - Circuit-breaker, 3p, 25A, plug-in module



113352 NZMH2-A25-SVE

[Overview](#) [Specifications](#) [Resources](#)



# 113352 NZMH2-A25-SVE

Circuit-breaker, 3p, 25A, plug-in module

EL-Nummer (Norway)

4357040

Circuit-breaker NZM2, 3 pole, Switching capacity 400/415 V 50 Hz( I<sub>cu</sub> ): 150 kA, Rated current = rated uninterrupted current Rated current = rated uninterrupted current( I<sub>n</sub> = I<sub>n</sub> ): 25 A, Installation type: Plug-in units, Screw connection, Standard/Approval: IEC, Protective function: System and cable protection

• [Delivery program](#)

• [Technical data](#)

• [Design verification as per IEC/EN 61439](#)

• [Technical data ETIM 7.0](#)

• [Characteristics](#)

• [Dimensions](#)

## Delivery program

Product range

Circuit-breaker

Protective function

System and cable protection

Standard/Approval

IEC

Installation type

Plug-in units

Release system

Thermomagnetic release

Construction size

NZM2

Number of poles

3 pole

Standard equipment

Screw connection

Switching capacity

400/415 V 50 Hz [I<sub>cu</sub>]


150 kA

Rated current = rated uninterrupted current [I<sub>n</sub> = I<sub>n</sub>]

Rated current = rated uninterrupted current [I<sub>n</sub> = I<sub>n</sub>]

25 A

**Setting range**

Overload trip  [ $I_t$ ]

20 - 25 A

Short-circuit releases  [ $I_{cm}$ ] Non-delayed  [ $I_t = I_n \times \dots$ ]

350 A fixed

## Technical data

General

Standards

IEC/EN 60947

Protection against direct contact

Finger and back of hand proof to VDE 0106 Part 100

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature Ambient temperature, storage

- 40 - + 70 °C

Ambient temperature Operation

-25 - +70 °C

Mechanical shock resistance (10 ms half-sinusoidal shock) according to IEC 60068-2-27

20 (half-sinusoidal shock 20 ms) g


Safe isolation to EN 61140 Between auxiliary contacts and main contacts

500 V AC

Safe isolation to EN 61140 between the auxiliary contacts

300 V AC

Mounting position

|  |   |
|--|---|
| Vertical and 90° in all directions   |   |
|  | With XF earth-fault release:  |
|  | - NZM1, N1, NZM2, N2: vertical and 90° in all directions                    |
|  | with plug-in unit   |
|  | - NZM1, N1, NZM2, N2: vertical, 90° right/left                              |
|  | with withdrawable unit:   |
|  | - NZM3, N3: vertical, 90° right/left  |
|  | - NZM4, N4: vertical  |
|  | with remote operator:   |
|  | - NZM2, N(S)2, NZM3, N(S)3, NZM4, N(S)4: vertical and 90° in all directions |

Direction of incoming supply

as required

Degree of protection Device

In the operating controls area: IP20 (basic degree of protection)

Degree of protection Enclosures

With insulating surround: IP40

With door coupling rotary handle: IP66

Degree of protection Terminations

Tunnel terminal: IP10

Phase isolator and strip terminal: IP00

Other technical data (sheet catalogue)

[Temperature dependency, Derating](#)

Circuit-breakers

Rated current = rated uninterrupted current [ $I_n = I_u$ ]

25 A

Rated surge voltage invariability [ $U_{imp}$ ] Main contacts

8000 V

Rated surge voltage invariability [ $U_{imp}$ ] Auxiliary contacts

6000 V

Rated operational voltage [ $U_b$ ]

690 V AC

Overvoltage category/pollution degree

III/3

Rated insulation voltage [ $U_i$ ]

1000 V

Use in unearthed supply systems

☐ 690 V

Switching capacity

Rated short-circuit making capacity [ $I_{cm}$ ] 240 V [ $I_{cm}$ ]

330 kA

Rated short-circuit making capacity [ $I_{cm}$ ] 400/415 V [ $I_{cm}$ ]

330 kA  
 Rated short-circuit making capacity [ $I_{cm}$ ] 440 V 50/60 Hz [ $I_{cm}$ ]  
 286 kA  
 Rated short-circuit making capacity [ $I_{cm}$ ] 525 V 50/60 Hz [ $I_{cm}$ ]  
 105 kA  
 Rated short-circuit making capacity [ $I_{cm}$ ] 690 V 50/60 Hz [ $I_{cm}$ ]  
 40 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  $I_{cu}$  to IEC/EN 60947 test cycle O-t-OO [ $I_{cu}$ ] 240 V 50/60 Hz [ $I_{cu}$ ]  
 150 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  $I_{cu}$  to IEC/EN 60947 test cycle O-t-OO [ $I_{cu}$ ] 400/415 V 50/60 Hz [ $I_{cu}$ ]  
 150 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  $I_{cu}$  to IEC/EN 60947 test cycle O-t-OO [ $I_{cu}$ ] 440 V 50/60 Hz [ $I_{cu}$ ]  
 130 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  $I_{cu}$  to IEC/EN 60947 test cycle O-t-OO [ $I_{cu}$ ] 525 V 50/60 Hz [ $I_{cu}$ ]  
 50 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  $I_{cu}$  to IEC/EN 60947 test cycle O-t-OO [ $I_{cu}$ ] 690 V 50/60 Hz [ $I_{cu}$ ]  
 20 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  $I_{cs}$  to IEC/EN 60947 test cycle O-t-OO-t-OO [ $I_{cs}$ ] 240 V 50/60 Hz [ $I_{cs}$ ]  
 150 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  $I_{cs}$  to IEC/EN 60947 test cycle O-t-OO-t-OO [ $I_{cs}$ ] 400/415 V 50/60 Hz [ $I_{cs}$ ]  
 150 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  $I_{cs}$  to IEC/EN 60947 test cycle O-t-OO-t-OO [ $I_{cs}$ ] 440 V 50/60 Hz [ $I_{cs}$ ]  
 130 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  $I_{cs}$  to IEC/EN 60947 test cycle O-t-OO-t-OO [ $I_{cs}$ ] 525 V 50/60 Hz [ $I_{cs}$ ]  
 37.5 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  $I_{cs}$  to IEC/EN 60947 test cycle O-t-OO-t-OO [ $I_{cs}$ ] 690 V 50/60 Hz [ $I_{cs}$ ]  
 5 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
 Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit-breaker.  
 Rated short-time withstand current  $I_{cw}$  = 0.3 s [ $I_{cw}$ ]  
 1.9 kA  
 Rated short-time withstand current  $I_{cw}$  = 1 s [ $I_{cw}$ ]  
 1.9 kA  
 Utilization category to IEC/EN 60947-2  
 A  
 Lifespan, mechanical (of which max. 50 % trip by shunt/undervoltage release) [Operations]  
 20000  
 Lifespan, electrical AC-1400 V 50/60 Hz [Operations]  
 10000  
 Lifespan, electrical AC-1415 V 50/60 Hz [Operations]  
 10000  
 Lifespan, electrical AC-1690 V 50/60 Hz [Operations]  
 7500  
 Lifespan, electrical AC-3400 V 50/60 Hz [Operations]  
 6500  
 Lifespan, electrical AC-3415 V 50/60 Hz [Operations]  
 6500  
 Lifespan, electrical AC-3690 V 50/60 Hz [Operations]  
 5000  
 Lifespan, electrical Max. operating frequency  
 120 Ops/h  
 Total break time at short-circuit  
 < 10 ms  
**Terminal capacity**  
 Standard equipment  
 Screw connection  
 Accessories required  
 NZM2-XSVS  
 Optional accessories  
 Box terminal  
 Tunnel terminal  
 connection on rear  
 Round copper conductor Box terminal Solid  
 1 x (10 - 16)  
 2 x (6 - 16) mm<sup>2</sup>  
 Round copper conductor Box terminal Stranded  
 1 x (25 - 185)  
 2 x (25 - 70) mm<sup>2</sup>

Round copper conductor Tunnel terminal Solid  
 1 x 16 mm<sup>2</sup>  
 Round copper conductor Tunnel terminal Stranded 1-hole  
 1 x (25 - 185) mm<sup>2</sup>  
 Round copper conductor Bolt terminal and rear-side connection Direct on the switch Solid  
 1 x (10 - 16)  
 2 x (6 - 16) mm<sup>2</sup>  
 Round copper conductor Bolt terminal and rear-side connection Direct on the switch Stranded  
 1 x (25 - 185)  
 2 x (25 - 70) mm<sup>2</sup>  
 Al circular conductor Tunnel terminal Solid  
 1 x 16 mm<sup>2</sup>  
 Al circular conductor Tunnel terminal Stranded Stranded  
 1 x (25 - 185) mm<sup>2</sup>  
 Cu strip (number of segments x width x segment thickness) Box terminal [min.]  
 2 x 9 x 0.8 mm  
 Cu strip (number of segments x width x segment thickness) Box terminal [max.]  
 10 x 16 x 0.8  
 (2x) 8 x 15.5 x 0.8 mm  
 Cu strip (number of segments x width x segment thickness) Bolt terminal and rear-side connection Flat copper strip,  
 with holes [min.]  
 2 x 16 x 0.8 mm  
 Cu strip (number of segments x width x segment thickness) Bolt terminal and rear-side connection Flat copper strip,  
 with holes [max.]  
 10 x 24 x 0.8 mm  
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Screw connection  
 MB  
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Direct on the switch [min.]  
 16 x 5 mm  
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Direct on the switch [max.]  
 24 x 8 mm  
 Control cables  
 1 x (0.75 - 2.5)  
 2 x (0.75 - 1.5) mm<sup>2</sup>

## Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [ $I_n$ ]

25 A

Equipment heat dissipation, current-dependent [ $P_{ed}$ ]

7.97 W

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss10.0.1-27-37-04-09 [AJZ716013])

Rated permanent current I<sub>n</sub>

25 A

Rated voltage

690 - 690 V

Rated short-circuit breaking capacity I<sub>cu</sub> at 400 V, 50 Hz

150 kA

Overload release current setting

20 - 25 A

Adjustment range short-term delayed short-circuit release

0 - 0 A

Adjustment range undelayed short-circuit release

350 - 350 A

Integrated earth fault protection

No

Type of electrical connection of main circuit

Screw connection

Device construction

Built-in device plug-in technique

Suitable for DIN rail (top hat rail) mounting

No

DIN rail (top hat rail) mounting optional

Yes

Number of auxiliary contacts as normally closed contact

0

Number of auxiliary contacts as normally open contact

0

Number of auxiliary contacts as change-over contact

0

With switched-off indicator

No

With under voltage release

No

Number of poles

3

Position of connection for main current circuit

Front side

Type of control element

Rocker lever

Complete device with protection unit

Yes  
Motor drive integrated  
No  
Motor drive optional  
Yes  
Degree of protection (IP)  
IP20

## Characteristics

Characteristic curve

Characteristic curve

Let-through current

Characteristic curve

Let-through energy

## Dimensions

☐ Blow out area, minimum clearance to adjacent parts

☐ Minimum clearance to adjacent parts

## CAD data

- [Product-specific CAD data](#)  
(Web)
- [3D Preview](#)  
(Web)

## DWG files

- [DA-CD-nzm2\\_xsve](#)  
File  
(Web)

## Step files

- [DA-CS-nzm2\\_xsve](#)  
File  
(Web)

## Additional product information

- [Temperature dependency, Derating](#)  
(Web)
- [CurveSelect characteristics program](#)  
(Web)
- [additional technical information for NZM power switch](#)  
(PDF)

## Dimensions single product

- ☐  
[123X029](#)  
Line drawing  
Plug-in adapter elements
- ☐  
[123X312](#)  
Line drawing  
Circuit-breaker, switch-disconnector, 3-pole  
☐ Blow out area, minimum clearance to adjacent parts  
☐ Minimum clearance to adjacent parts
- ☐  
[123X341](#)

Line drawing  
Circuit-breakers, switch-disconnectors

## 3D drawing

- ☐ [1231247](#)  
Line drawing  
Circuit-breakers, switch-disconnectors

## Product photo

-   
[1230PIC-875](#)  
Photo

## Characteristic curve

- ☐ [1230DIA-57](#)  
Coordinate visualization  
Let-through characteristics
- ☐ [1230DIA-8](#)  
Coordinate visualization  
Let-through current
- ☐ [123U176](#)  
Coordinate visualization  
NZM2-A40...250 tripping characteristic

## Symbol

- ☐ [0000SPC-173](#)  
Graphic  
Logo new yellow small

## Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center



Generate data sheet in PDF format



Generate data sheet in Excel format



Write a comment

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

