

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NZMH2-4-A40-SVE - Circuit-breaker, 4p, 40A, plug-in module



113367 NZMH2-4-A40-SVE

[Overview](#) [Specifications](#) [Resources](#)



113367 NZMH2-4-A40-SVE

Circuit-breaker, 4p, 40A, plug-in module

EL-Nummer (Norway)

4357053

Circuit-breaker NZM2, 4 pole, Switching capacity 400/415 V 50 Hz(I_{cu}): 150 kA, Rated current = rated uninterrupted current Rated current = rated uninterrupted current(I_n = I_u): 40 A, Installation type: Plug-in units, Screw connection, Standard/Approval: IEC, Protective function: System and cable protection

- Delivery program
- Technical data
- Design verification as per IEC/EN 61439
- Technical data ETIM 7.0
- Characteristics
- Dimensions

Delivery program

Product range
Circuit-breaker
Protective function
System and cable protection
Standard/Approval
IEC
Installation type
Plug-in units
Release system
Thermomagnetic release
Construction size
NZM2
Description
Set value in neutral conductor is synchronous with set value I_r of main pole.
Number of poles
4 pole
Standard equipment
Screw connection
Switching capacity
400/415 V 50 Hz [I_{cu}]
150 kA
Rated current = rated uninterrupted current [I_n = I_u]
Rated current = rated uninterrupted current [I_n = I_u]
40 A
Neutral conductor [% of phase conductor]

100 %

Setting range

Overload trip I_{tr} [A]

32 - 40 A

Overload trip Main pole I_{tr} [A]

32 - 40 A

Short-circuit releases I_{sc} [kA] Non-delayed I_{sc} [$I_n \times \dots$]

8 - 10

Technical data

General

Standards

IEC/EN 60947

Protection against direct contact

Finger and back of hand proof to VDE 0106 Part 100

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature Ambient temperature, storage

- 40 - + 70 °C

Ambient temperature Operation

-25 - +70 °C

Mechanical shock resistance (10 ms half-sinusoidal shock) according to IEC 60068-2-27

20 (half-sinusoidal shock 20 ms) g

Safe isolation to EN 61140 Between auxiliary contacts and main contacts


500 V AC

Safe isolation to EN 61140 between the auxiliary contacts

300 V AC

Mounting position

Vertical and 90° in all directions

	With XFI earth-fault release:
	- NZM1, N1, NZM2, N2: vertical and 90° in all directions
	with plug-in unit
	- NZM1, N1, NZM2, N2: vertical, 90° right/left
	with withdrawable unit:
	- NZM3, N3: vertical, 90° right/left
	- NZM4, N4: vertical
with remote operator:	
- NZM2, N(S)2, NZM3, N(S)3, NZM4, N(S)4: vertical and 90° in all directions	

Direction of incoming supply

as required

Degree of protection Device

In the operating controls area: IP20 (basic degree of protection)

Degree of protection Enclosures

With insulating surround: IP40

With door coupling rotary handle: IP66

Degree of protection Terminations

Tunnel terminal: IP10

Phase isolator and strip terminal: IP00

Other technical data (sheet catalogue)

[Temperature dependency, Derating](#)

Circuit-breakers

Rated current = rated uninterrupted current [$I_n = I_u$]

40 A

Rated surge voltage invariability [U_{imp}] Main contacts

8000 V

Rated surge voltage invariability [U_{imp}] Auxiliary contacts

6000 V

Rated operational voltage [U_e]

690 V AC

Overvoltage category/pollution degree

III/3

Rated insulation voltage [U_i]

1000 V

Use in unearthed supply systems

690 V

Switching capacity

Rated short-circuit making capacity [I_{cm}]240 V [I_{cm}]

330 kA

Rated short-circuit making capacity [I_{cm}]400/415 V [I_{cm}]

330 kA

Rated short-circuit making capacity [I_{cm}]440 V 50/60 Hz [I_{cm}]

286 kA

Rated short-circuit making capacity [I_{cm}]525 V 50/60 Hz [I_{cm}]

105 kA

Rated short-circuit making capacity [I_{cm}]690 V 50/60 Hz [I_{cm}]

40 kA

Rated short-circuit breaking capacity [I_{cn}] [I_{cu}] to IEC/EN 60947 test cycle O-t-CO [I_{cu}]240 V 50/60 Hz [I_{cu}]

150 kA

Rated short-circuit breaking capacity [I_{cn}] [I_{cu}] to IEC/EN 60947 test cycle O-t-CO [I_{cu}]400/415 V 50/60 Hz [I_{cu}]

150 kA

Rated short-circuit breaking capacity [I_{cn}] [I_{cu}] to IEC/EN 60947 test cycle O-t-CO [I_{cu}]440 V 50/60 Hz [I_{cu}]

130 kA

Rated short-circuit breaking capacity [I_{cn}] [I_{cu}] to IEC/EN 60947 test cycle O-t-CO [I_{cu}]525 V 50/60 Hz [I_{cu}]

50 kA

Rated short-circuit breaking capacity [I_{cn}] [I_{cu}] to IEC/EN 60947 test cycle O-t-CO [I_{cu}]690 V 50/60 Hz [I_{cu}]

20 kA

Rated short-circuit breaking capacity [I_{cn}] [I_{cs}] to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]240 V 50/60 Hz [I_{cs}]

150 kA

Rated short-circuit breaking capacity [I_{cn}] [I_{cs}] to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]400/415 V 50/60 Hz [I_{cs}]

150 kA

Rated short-circuit breaking capacity [I_{cn}] [I_{cs}] to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]440 V 50/60 Hz [I_{cs}]

130 kA

Rated short-circuit breaking capacity [I_{cn}] [I_{cs}] to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]525 V 50/60 Hz [I_{cs}]

37.5 kA

Rated short-circuit breaking capacity [I_{cn}] [I_{cs}] to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]690 V 50/60 Hz [I_{cs}]

5 kA

Rated short-circuit breaking capacity [I_{cn}] [I_{cs}]

Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit-breaker.

Rated short-time withstand current $t = 0.3$ s [I_{cw}]

1.9 kA

Rated short-time withstand current $t = 1$ s [I_{cw}]

1.9 kA

Utilization category to IEC/EN 60947-2

A

Lifespan, mechanical (of which max. 50 % trip by shunt/undervoltage release) [Operations]

20000

Lifespan, electrical AC-1400 V 50/60 Hz [Operations]

10000

Lifespan, electrical AC-1415 V 50/60 Hz [Operations]

10000

Lifespan, electrical AC-1690 V 50/60 Hz [Operations]

7500

Lifespan, electrical AC-3400 V 50/60 Hz [Operations]

6500

Lifespan, electrical AC-3415 V 50/60 Hz [Operations]

6500

Lifespan, electrical AC-3690 V 50/60 Hz [Operations]

5000

Lifespan, electrical Max. operating frequency

120 Ops/h

Total break time at short-circuit

< 10 ms

Terminal capacity

Standard equipment

Screw connection

Accessories required

NZM2-4-XSVS

Optional accessories

Box terminal

Tunnel terminal

connection on rear

Round copper conductor Box terminal Solid

1 x (10 - 16)

2 x (6 - 16) mm²
 Round copper conductor Box terminal Stranded
 1 x (25 - 185)
 2 x (25 - 70) mm²
 Round copper conductor Tunnel terminal Solid
 1 x 16 mm²
 Round copper conductor Tunnel terminal Stranded 1-hole
 1 x (25 - 185) mm²
 Round copper conductor Bolt terminal and rear-side connection Direct on the switch Solid
 1 x (10 - 16)
 2 x (6 - 16) mm²
 Round copper conductor Bolt terminal and rear-side connection Direct on the switch Stranded
 1 x (25 - 185)
 2 x (25 - 70) mm²
 Al circular conductor Tunnel terminal Solid
 1 x 16 mm²
 Al circular conductor Tunnel terminal Stranded Stranded
 1 x (25 - 185) mm²
 Cu strip (number of segments x width x segment thickness) Box terminal [min.]
 2 x 9 x 0.8 mm
 Cu strip (number of segments x width x segment thickness) Box terminal [max.]
 10 x 16 x 0.8
 (2x) 8 x 15.5 x 0.8 mm
 Cu strip (number of segments x width x segment thickness) Bolt terminal and rear-side connection Flat copper strip,
 with holes [min.]
 2 x 16 x 0.8 mm
 Cu strip (number of segments x width x segment thickness) Bolt terminal and rear-side connection Flat copper strip,
 with holes [max.]
 10 x 24 x 0.8 mm
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Screw connection
 M8
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Direct on the switch [min.]
 16 x 5 mm
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Direct on the switch [max.]
 24 x 8 mm
 Control cables
 1 x (0.75 - 2.5)
 2 x (0.75 - 1.5) mm²

Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_r]

40 A

Equipment heat dissipation, current-dependent [P_{vid}]

13.44 W

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss10.0.1-27-37-04-09 [A.JZ716013])

Rated permanent current I_n

40 A

Rated voltage

690 - 690 V

Rated short-circuit breaking capacity I_{cu} at 400 V, 50 Hz

150 kA

Overload release current setting

32 - 40 A

Adjustment range short-term delayed short-circuit release

0 - 0 A

Adjustment range undelayed short-circuit release

8 - 10 A

Integrated earth fault protection

No

Type of electrical connection of main circuit

Screw connection

Device construction

Built-in device plug-in technique

Suitable for DIN rail (top hat rail) mounting

No

DIN rail (top hat rail) mounting optional

Yes

Number of auxiliary contacts as normally closed contact

0

Number of auxiliary contacts as normally open contact

0

Number of auxiliary contacts as change-over contact

0

With switched-off indicator

No

With under voltage release

No

Number of poles

4

Position of connection for main current circuit

Front side
Type of control element
Rocker lever
Complete device with protection unit
Yes
Motor drive integrated
No
Motor drive optional
Yes
Degree of protection (IP)
IP20

Characteristics

Characteristic curve

Characteristic curve

Let-through current

Characteristic curve

Let-through energy

Dimensions

- Blow out area, minimum clearance to adjacent parts
- Minimum clearance to adjacent parts

CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)

DWG files

- [DA-CD-nzm2_xsve](#)
File
(Web)

Step files

- [DA-CS-nzm2_xsve](#)
File
(Web)

Additional product information

- [Temperature dependency, Derating](#)
(Web)
- [CurveSelect characteristics program](#)
(Web)
- [additional technical information for NZM power switch](#)
(PDF)

Dimensions single product

- [123X341](#)
Line drawing
Circuit-breakers, switch-disconnectors

- [123X508](#)
Line drawing
Circuit-breaker, switch-disconnector, 4-pole

- Blow out area, minimum clearance to adjacent parts
- Minimum clearance to adjacent parts
- Does not apply to DC applications

3D drawing

- [123I611](#)
Line drawing
Protection of systems and cables

Product photo



[1230PIC-873](#)
Photo

Characteristic curve

- [1230DIA-57](#)
Coordinate visualization
Let-through characteristics
- [1230DIA-8](#)
Coordinate visualization
Let-through current
- [123U176](#)
Coordinate visualization
NVM2-A40...250 tripping characteristic

Symbol


- [0000SPC-173](#)
Graphic
Logo new yellow small

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH