



121464
M22-PVT60P

Overview

Specifications

Resources



DELIVERY PROGRAM

Delivery program

Product range

RMQ-Titan

Technical data

Basic function

Controlled stop pushbuttons/emergency-stop buttons

Design verification as

per IEC/EN 61439

Mounting hole diameter [□]

22.5 mm

Approvals

Single unit/Complete unit

Single unit

Dimensions

Design

Palm-tree shape

Diameter [□]

60 mm

Illumination

Non-illuminated

Turn-to-release function

Description

Tamper-proof according to ISO 13850/EN 418

Colour

Mushroomhead

Red



Base

yellow

RAL 3000

Degree of Protection

IP66, IP67, IP69

Connection to SmartWire-DT

no

Instructions

Max. number of contacts: four M22-(C)K01, ...10
or two M22-(C)K02, ...20, ...11

TECHNICAL DATA

General

Standards

IEC/EN 60947

VDE 0660

Lifespan, mechanical [Operations]

> 0.1 x 10⁶

Operating frequency [Operations/h]

600

Actuating force

50 N

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Degree of Protection

IP66, IP67, IP69

Ambient temperature

Open

-25 - +70 °C

Mounting position

As required

Mechanical shock resistance

50

Shock duration 11 ms

Sinusoidal

according to IEC 60068-2-27 g

Shipping classification

DNV

GL

LR



DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_h]

0 A

Heat dissipation per pole, current-dependent [P_{vid}]
0 W

Equipment heat dissipation, current-dependent
[P_{vid}]
0 W

Static heat dissipation, non-current-dependent [P_{vs}]
0 W

Heat dissipation capacity [P_{diss}]
0 W

Operating ambient temperature min.
-25 °C

Operating ambient temperature max.
+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of
enclosures
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.2 Verification of resistance of insulating
materials to normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.3 Verification of resistance of insulating
materials to abnormal heat and fire due to internal
electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.4 Resistance to ultra-violet (UV) radiation
Please enquire

10.2 Strength of materials and parts
10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.

10.8 Connections for external conductors
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Front element for mushroompush-button (EC001038)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for mushroompush-button actuators (ecl@ss 10.0.1-27-37-12-12 [AKF030014])

Colour button

Red

Construction type lens

Round

Diameter cap

60 mm

Hole diameter

22.5 mm

Width opening

0 mm

Height opening
0 mm

Degree of protection (IP)
IP67/IP69K

Degree of protection (NEMA)
4X

Type of button
High

Suitable for illumination
No

Switching function latching
Yes

Spring-return
No

With front ring
No

Material front ring
Other

Colour front ring
Other

Suitable for emergency stop
Yes

Unlocking method
Turn-release

APPROVALS

North America Certification
Request filed for UL and CSA

DIMENSIONS

