

Auxiliary switch changeover contact and Fault signal contact
changeover contact 0.5 MW 230/400 V AC 24-220 V DC for 5SY,
5SL for 5SP, 5SV, 5SU1, 5ST3



Model	
Product brand name	SENTRON
Design of the product	Mountable
Electrical endurance (switching cycles) / typical	10 000
Supply voltage	
Operating voltage	
• rated value	230 V
• at AC / rated value / minimum	24 V
• at AC / rated value / maximum	440 V
• at DC / rated value / minimum	24 V
• at DC / rated value / maximum	110 V
Protection class IP	IP20
Product details	
Product feature / interlock	No
Product component	
• fault signal contact	Yes
• Auxiliary switch	Yes

Number	
Number of fault signal contacts	1
Number of NC contacts	0
Number of NO contacts	0
Number of CO contacts	2

Connections	
Connectable conductor cross-section	0.5 ... 2.5 mm ²
Tightening torque / with screw-type terminals	0.5 N·m
Type of connectable conductor cross-sections / at AWG conductors	24 ... 12

Mechanical Design	
Height	90 mm
Width	9 mm
Depth	74 mm
Net weight	57 g
• during operation	-25 ... +55 °C
• during storage	-40 ... +75 °C

Certificates	
General Product Approval	Declaration of Conformity



CCC



UR



VDE



EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3062>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3062>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3062

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



