

Auxiliary current switch 1 CO For MCB 5SL, 5SY, 5SP Incorporated switch 5TL1 RCBO 5SU1, RC 5SV



Model	
Product brand name	SETRON
Product designation	Auxiliary current switch
Design of the product	Mountable
Electrical endurance (switching cycles) / typical	20 000
Protection class IP	IP20
Product details	
Product component	Yes
• Auxiliary switch	
Product extension	auxiliary switch
Number	
Number of fault signal contacts	0
Number of NC contacts	0
Number of NO contacts	0
Number of CO contacts	1
Connections	
Connectable conductor cross-section	0.5 ... 2.5 mm²
Tightening torque / with screw-type terminals	0.5 N·m

Type of connectable conductor cross-sections / at AWG conductors	24 ... 12
--	-----------

Mechanical Design

Height	90 mm
Width	9 mm
Depth	70 mm
Net weight	51 g
• during operation	-25 ... +55 °C
• during storage	-40 ... +75 °C

Certificates

General Product Approval	Declaration of Conformity	other	Railway
 CCC	 UR	 VDE	 EG-Konf.
		Miscellaneous	Vibration and Shock

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3016>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3016>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3016

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



