

Infeed terminal, 25 mm<sup>2</sup> IP20 Cable entry on the left with touch protection



| Model                                   |                |
|-----------------------------------------|----------------|
| Product brand name                      | SETRON         |
| Product designation                     | Busbar systems |
| Design of the product                   | Accessories    |
| Current / at AC / rated value           | 80 A           |
| Operating voltage / at AC / rated value | 690 V          |

| Mechanical Design |         |
|-------------------|---------|
| Height            | 17.7 mm |
| Width             | 17.5 mm |
| Depth             | 14 mm   |
| Net weight        | 10 g    |

| Certificates              |  |
|---------------------------|--|
| Declaration of Conformity |  |



## Further information

### **Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

### **Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3771-2>

### **Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3771-2>

### **Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5ST3771-2](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3771-2)

### **CAX-Online-Generator**

<http://www.siemens.com/cax>

### **Tender specifications**

<http://www.siemens.com/specifications>