

## Product data sheet

Item No. 91.922.3353.0

### Male connector with strain relief GST15I2S S1 ZR1WW BL02

Connector GST15i2, 2 pole, male, screw connection, 250V/16A,  
color of coding: light blue, color of housing: black



Item No.	91.922.3353.0
EAN	4015573916128
Order Unit	100 Piece(s)

## Certificates / Approvals



## Technical data

### General

Rated current	16 A
Rated voltage	50 V
Rated impulse voltage	4 kV
Strain relief	Yes
Pollution degree	2
Mechanical coding	Code 3
Lockable	Yes
Color of coding/ contact carrier	Light blue
Marking of poles	1, 2
Color of housing inclusive strain relief	White

### Connection Data

Cable diameter	7.7 mm
Cable diameter 2	6 mm
Cross section solid	2.5 mm <sup>2</sup>
Cross section solid 2	0.5 mm <sup>2</sup>
Connection cross section stranded max.	2.5 mm <sup>2</sup>
Cross section stranded 2	0.5 mm <sup>2</sup>

Terminations per pole	1
-----------------------	---

**Model**

Model	male
Connection type	Screw connection
Degree of protection (IP)	IP20

**Material**

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

**Dimensions**

Length	53.2 mm
Width	17.7 mm
Height	13.8 mm