

Product data sheet

Item No. G0.000.0087.5

Cable assembly GST18i3S -S 10 5kVRT03

Connection cable, male - free end, length 1,5m, GST18i3, 3 pole, 250V/10A, cable type N2GMH, with silicon, 180°C, cross section 1,0 mm², color of coding: salomon red 5kV, color of cable: black

Item No.	G0.000.0087.5
EAN	4015573721746
Order Unit	50 Piece(s)

Certificates / Approvals

Technical data

General

Rated current	10 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 3
Lockable	Yes
Color of coding/ contact carrier	Salmon pink
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

Model

Nominal cross section conductor	1 mm ²
Degree of protection (IP)	IP20
Wire strip length	7 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05SS-F
Cable colour	Black
Cable diameter	8.2 mm
Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 1	GST18i3 plug
Version cable end 2	Free end

Material

Surface finish	Tin-plated
Halogen free	Yes
Continuous temperature of cable	180 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	1 m
--------------	-----