



Product data sheet

Item No. 96.151.0053.1

Connector RST20I5C B1 ZR1 SW

RST 20i5/4 connector, 5 pole, for crimpcontact, application 250V/400V, 20A, for cable diameters 6-10mm, coding-color black, color of housing black



Item No.	96.151.0053.1
EAN	4015573932180
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

Genera

Gellefal	
Rated current	20 A
Rated voltage	250 V
Rated voltage 2	400 V
Rated impulse voltage	4 kV
Strain relief	Yes
Pollution degree	3
Mechanical coding	Code 0
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	1, 2, 3, N, PE
Color of housing inclusive strain relief	Black

Connection Data

Cable diameter	10 mm
Cable diameter 2	6 mm
Cable diameter 3	10 mm
Connection cross section stranded max.	4 mm²
Cross section stranded 2	0.75 mm²





1		
Model		
female		
Crimp		
IP66/68 (3m;2h) /IP69		
Material		
Polyamide		
Yes		
CuZn		
100 °C		
Silver-plated		
Dimensions		
80.4 mm		

34.6 mm

34.6 mm

Technical drawing

Width

Height

