

Datasheet

Art.No. 75.450.0114.3

Connecting module FCS 16 5 SA SAM63G

Feed-in module for tray cable PODIS CON 5G16 connection by roundcable; M50 cable gland; 5-pole; nominal ratings acc. VDE 63A; 690 V; 6kV/3; nominal ratings acc. UL 61 A; 600 V; degree of protection IP65; screw clamps max. 35 mm² (AWG 2) single/fine-stranded; max. cable diameter 38 mm (1 ½"); housing grey; mounting position any; Outline dimensions L x W x H 300 x 145 x 100 mm



Art.No.	75.450.0114.3
EAN	4049088483929
Order unit	1 pieces

Approvals

Technical data

General

Colour	Light grey
Degree of protection (IP)	IP65
Rated cross section power bus	16 mm ²
Operating temperature min.	-25 °C
Operating temperature max.	55 °C
Storage temperature / transport min.	-40 °C
Storage temperature / transport max.	70 °C

Technical data

Rated voltage	690 V
Rated current	63 A
Number of poles	5
Number of clamp positions per pole	1
Connection type 1	Insulation piercing connection
Connection type 2	Screw connection
Mounting method	Surface mounting
Type of supply voltage	AC/DC

Dimensions

Length	300 mm
Assembly width	145 mm
Assembly height	100 mm