









eNet wireless operating top unit Memory



Specification	Order No.	Packing unit	PS	EAN
 cream white glossy	5493 01	1	42	4010337091578
 pure white glossy	5493 03	1/5	42	4010337091585
 pure white matt	5493 27	1/5	42	4010337091592
 anthracite	5493 28	1/5	42	4010337091608
 colour aluminium	5493 26	1/5	42	4010337091615
 black matt	5493 005	1/5	42	4010337091639
 stainless steel	5493 600	1	42	4010337091622

Features

- Operation on switching, dimming or blind insert or auxiliary insert, 3-wire from the System 3000 design line.
- Manual, wireless and time-controlled operation of e.g. blinds, shutters, awnings, lighting or fans.
- Transmitter for wireless transmission of switching, dimming and blind commands.

- Save a time for raising and lowering blinds or a switch-on and switch-off time. In memory mode, these switching times are repeated every 24 hours.
- Accuracy: +/- 15 sec. / month
- Blocking function blocks auxiliary unit operation, wireless operation and deactivates memory mode.
- Adjustable night mode. Status LED and function LED are not lit up continuously.
- Status feedback to wireless transmitter.
- Status display with LED.
- Evaluation of auxiliary inputs.

Functions in combination with blind insert:

- Positioning of hangings via scene call-up.
- Position for sun protection and twilight.
- Runtime and ventilation position of the hanging can be saved.

Functions in combination with light insert:

- Scene operation possible.
- Switch-on brightness can be permanently stored when combined with dimming insert.

Adjustable with eNet server version 2.2 and higher (depending on the insert):

- Fully encrypted wireless transmission (AES-CCM).
- Deactivate auxiliary unit evaluation.
- Operation locks.
- Reversal time adjustable for blinds, shutters and awnings.
- Direction of travel can be inverted.
- Position for sun protection, twilight, lock-out protection and wind alarm.
- Maximum brightness, minimum brightness and dimming speed adjustable.
- Delay time.
- Switch-on/off delay.
- Dimming ramp up/down.
- Switch-off pre-warning.
- Permanent-on, permanent-off.
- Hotel function.
- Light control.
- Repeater function.
- Device software update.

Technical data

Ambient temperature:	-5 °C to +45 °C
Wireless frequency:	868.0 to 868.6 MHz
Range (free field):	approx. 100 m

Notes

- The range can be reduced when using a metal top unit and/or metal cover frames.
 - Wireless approval is valid for EU and EFTA countries.
-