

# PRODUCT DATASHEET

## P CLAS P 40 5 W/2700K E27

PARATHOM Retrofit CLASSIC P DIM | Dimmable LED lamps, classic bulb shape



---

### AREAS OF APPLICATION

- Domestic applications
- General illumination
- Outdoor use in outdoor luminaires only (minimum IP65)
- Perfect for decorative installations

---

### PRODUCT BENEFITS

- Design, dimensions, luminous flux comparable to an incandescent lamp
- Very low energy consumption
- Robust against vibrations
- Lamps with innovative LED "filament" technology
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs

---

### PRODUCT FEATURES

- Professional LED lamps for line voltage
- Dimmable (with many common dimmers, see also [www.ledvance.com/dim](http://www.ledvance.com/dim))
- Mercury-free lamps
- Lifetime: up to 15,000 h
- Beam angle: up to 300°



## TECHNICAL DATA

### Electrical data

|  |             |
|--|-------------|
| Rated wattage                            | 5.00 W      |
| Nominal wattage                          | 5.00 W      |
| Nominal voltage                          | 220...240 V |
| Max. lamp no. on circuit break. 10 A (B) | 90          |
| Max. lamp no. on circuit break. 16 A (B) | 145         |
| Operating frequency                      | 50...60 Hz  |
| Power factor $\lambda$                   | > 0.70      |
| Claimed equiv. conventional lamp power   | 40 W        |


### Photometrical data

|   |               |
|---|---------------|
| Nominal luminous flux                   | 470 lm        |
| Rated luminous flux                     | 470 lm        |
| Lumen main.fact.at end of nom.life time | 0.70          |
| Light color (designation)               | Warm White    |
| Color temperature                       | 2700 K        |
| Luminous flux                           | 470 lm        |
| Color rendering index Ra                | 95            |
| Standard deviation of color matching    | $\leq 6$ sdcn |
| Rated color temperature                 | 2700 K        |

### Light technical data

|                     |          |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |
| Starting time       | < 0.5 s  |

### Dimensions & weight



|                |         |
|----------------|---------|
| Overall length | 78.0 mm |
| Diameter       | 45.0 mm |

|                   |         |
|-------------------|---------|
| <b>Outer bulb</b> | P45     |
| <b>Length</b>     | 78.0 mm |

## Temperatures &amp; operating conditions

|   |              |
|---|--------------|
| <b>Ambient temperature range</b>            | -20...+40 °C |
| <b>Maximum temperature at tc test point</b> | 70 °C        |

## Lifespan

|                                   |         |
|-----------------------------------|---------|
| <b>Nominal lamp life time</b>     | 15000 h |
| <b>Rated lamp life time</b>       | 15000 h |
| <b>Number of switching cycles</b> | 100000  |

## Additional product data

|                                    |   |
|------------------------------------|---|
| <b>Base (standard designation)</b> | E27   |
| <b>Mercury content</b>             | 0.0 mg  |
| <b>Mercury-free</b>                | Yes   |
| <b>Show WEEE picto</b>             | Yes   |
| <b>Product remark</b>              | All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/In preparation |

## Capabilities

|                 |     |
|-----------------|-----|
| <b>Dimmable</b> | Yes |
|-----------------|-----|

## Certificates &amp; standards

|                                |             |
|--------------------------------|-------------|
| <b>Energy efficiency class</b> | A+          |
| <b>Energy consumption</b>      | 5 kWh/1000h |

## Country-specific categorizations

|                        |                 |
|------------------------|-----------------|
| <b>Order reference</b> | LEDPCLP40D 5W/9 |
|------------------------|-----------------|

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075439634 | Folding carton box<br>1      | 46 mm x 46 mm x 93 mm                | 42.00 g      | 0.20 dm <sup>3</sup> |
| 4058075439641 | Shipping carton box<br>10    | 240 mm x 101 mm x 108 mm             | 338.00 g     | 2.62 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.