

# PRODUCT DATASHEET

## P CLAS A 60 7.5 W/2700K E27

PARATHOM Retrofit CLASSIC A DIM | Dimmable LED lamps, classic bulb shape



---

### AREAS OF APPLICATION

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in outdoor luminaires only (minimum IP65)

---

### PRODUCT BENEFITS

- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Very low energy consumption
- Robust against vibrations
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)

---

### PRODUCT FEATURES

- Professional LED lamps for line voltage
- Dimmable
- Base: E27, B22d
- Mercury-free lamps
- Lifetime: up to 15,000 h



## TECHNICAL DATA

### Electrical data

|                                          |             |
|------------------------------------------|-------------|
| Rated wattage                            | 7.50 W      |
| Nominal wattage                          | 7.50 W      |
| Nominal voltage                          | 220...240 V |
| Max. lamp no. on circuit break. 10 A (B) | 65          |
| Max. lamp no. on circuit break. 16 A (B) | 106         |
| Operating frequency                      | 50...60 Hz  |
| Power factor $\lambda$                   | > 0.70      |
| Claimed equiv. conventional lamp power   | 60 W        |


### Photometrical data

|                                         |               |
|-----------------------------------------|---------------|
| Nominal luminous flux                   | 806 lm        |
| Rated luminous flux                     | 806 lm        |
| Lumen main.fact.at end of nom.life time | 0.70          |
| Light color (designation)               | Warm White    |
| Color temperature                       | 2700 K        |
| Luminous flux                           | 806 lm        |
| Color rendering index Ra                | 95            |
| Standard deviation of color matching    | $\leq 6$ sdcn |
| Rated color temperature                 | 2700 K        |

### Light technical data

|                     |          |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |
| Starting time       | < 0.5 s  |

### Dimensions & weight



|                |          |
|----------------|----------|
| Overall length | 104.0 mm |
| Diameter       | 60.0 mm  |

|                   |          |
|-------------------|----------|
| <b>Outer bulb</b> | A60      |
| <b>Length</b>     | 104.0 mm |

## Temperatures &amp; operating conditions

|                                             |              |
|---------------------------------------------|--------------|
| <b>Ambient temperature range</b>            | -20...+40 °C |
| <b>Maximum temperature at tc test point</b> | 70 °C        |

## Lifespan

|                                                 |         |
|-------------------------------------------------|---------|
| <b>Nominal lamp life time</b>                   | 15000 h |
| <b>Rated lamp life time</b>                     | 15000 h |
| <b>Number of switching cycles</b>               | 100000  |
| <b>Lumen maintenance at end of service life</b> | 0.70    |

## Additional product data

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Base (standard designation)</b> | E27                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Mercury content</b>             | 0.0 mg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Mercury-free</b>                | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Show WEEE picto</b>             | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Product remark</b>              | All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance) |

## Capabilities

|                 |     |
|-----------------|-----|
| <b>Dimmable</b> | Yes |
|-----------------|-----|

## Certificates &amp; standards

|                                |             |
|--------------------------------|-------------|
| <b>Energy efficiency class</b> | A+          |
| <b>Energy consumption</b>      | 8 kWh/1000h |

## Country-specific categorizations

|                        |                |
|------------------------|----------------|
| <b>Order reference</b> | LEDPCA60D 7,5W |
|------------------------|----------------|

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075439696 | Folding carton box<br>1      | 67 mm x 67 mm x 162 mm               | 56.00 g      | 0.73 dm <sup>3</sup> |

|               |                           |                          |          |                      |
|---------------|---------------------------|--------------------------|----------|----------------------|
| 4058075439702 | Shipping carton box<br>10 | 349 mm x 146 mm x 175 mm | 672.00 g | 8.92 dm <sup>3</sup> |
|---------------|---------------------------|--------------------------|----------|----------------------|

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.