

# DATASHEET - DILMC50(230V50HZ,240V60HZ)



**Contactor, 3 pole, 380 V 400 V 22 kW, 230 V 50 Hz, 240 V 60 Hz, AC operation, Spring-loaded terminals**




**Part no.** DILMC50(230V50HZ,240V60HZ)  
**Catalog No.** 277995  
**Alternate Catalog No.** XTCEC050D00F  
**EL-Nummer (Norway)** 4110345

## Delivery program

|                                                           |                |    |                                                                                                                                                                                                                            |
|-----------------------------------------------------------|----------------|----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product range                                             |                |    | Contactors                                                                                                                                                                                                                 |
| Application                                               |                |    | Contactors for Motors                                                                                                                                                                                                      |
| Subrange                                                  |                |    | Contactors up to 170 A, 3 pole                                                                                                                                                                                             |
| Utilization category                                      |                |    | AC-1: Non-inductive or slightly inductive loads, resistance furnaces<br>NAC-3: Normal AC induction motors: starting, switch off during running<br>AC-4: Normal AC induction motors: starting, plugging, reversing, inching |
|                                                           |                |    |                                                                                                                                                                                                                            |
| Notes                                                     |                |    | Also suitable for motors with efficiency class IE3.<br>IE3-ready devices are identified by the logo on their packaging.                                                                                                    |
| Connection technique                                      |                |    | Spring-loaded terminals                                                                                                                                                                                                    |
| Description                                               |                |    | Spring-cage terminals on auxiliary and control circuit terminals                                                                                                                                                           |
| Number of poles                                           |                |    | 3 pole                                                                                                                                                                                                                     |
| <b>Rated operational current</b>                          |                |    |                                                                                                                                                                                                                            |
| AC-3                                                      |                |    |                                                                                                                                                                                                                            |
| Notes                                                     |                |    | At maximum permissible ambient temperature (open.)                                                                                                                                                                         |
| 380 V 400 V                                               | $I_e$          | A  | 50                                                                                                                                                                                                                         |
| AC-1                                                      |                |    |                                                                                                                                                                                                                            |
| Conventional free air thermal current, 3 pole, 50 - 60 Hz |                |    |                                                                                                                                                                                                                            |
| Open                                                      |                |    |                                                                                                                                                                                                                            |
| at 40 °C                                                  | $I_{th} = I_e$ | A  | 80                                                                                                                                                                                                                         |
| enclosed                                                  | $I_{th}$       | A  | 58                                                                                                                                                                                                                         |
| Conventional free air thermal current, 1 pole             |                |    |                                                                                                                                                                                                                            |
| open                                                      | $I_{th}$       | A  | 162                                                                                                                                                                                                                        |
| enclosed                                                  | $I_{th}$       | A  | 145                                                                                                                                                                                                                        |
| <b>Max. rating for three-phase motors, 50 - 60 Hz</b>     |                |    |                                                                                                                                                                                                                            |
| AC-3                                                      |                |    |                                                                                                                                                                                                                            |
| 220 V 230 V                                               | P              | kW | 15.5                                                                                                                                                                                                                       |
| 380 V 400 V                                               | P              | kW | 22                                                                                                                                                                                                                         |
| 660 V 690 V                                               | P              | kW | 30                                                                                                                                                                                                                         |
| AC-4                                                      |                |    |                                                                                                                                                                                                                            |
| 220 V 230 V                                               | P              | kW | 6                                                                                                                                                                                                                          |
| 380 V 400 V                                               | P              | kW | 10                                                                                                                                                                                                                         |
| 660 V 690 V                                               | P              | kW | 14                                                                                                                                                                                                                         |
| Contact sequence                                          |                |    |                                                                                                                                                                                                                            |
| <b>Instructions</b>                                       |                |    | Contacts to EN 50 012.<br>Auxiliary current, coil connections with spring-cage connection technology.<br>Main current connections with screw terminals.                                                                    |
| Can be combined with auxiliary contact                    |                |    | DILM150-XHIC(V)..<br>DILM1000-XHIC..                                                                                                                                                                                       |
| Actuating voltage                                         |                |    | 230 V 50 Hz, 240 V 60 Hz                                                                                                                                                                                                   |
| Voltage AC/DC                                             |                |    | AC operation                                                                                                                                                                                                               |
| Connection to SmartWire-DT                                |                |    | no                                                                                                                                                                                                                         |

## Technical data

### General

|                                                                       |                                     |                 |                                                                                    |
|-----------------------------------------------------------------------|-------------------------------------|-----------------|------------------------------------------------------------------------------------|
| Standards                                                             |                                     |                 | IEC/EN 60947, VDE 0660, UL, CSA                                                    |
| Lifespan, mechanical                                                  |                                     |                 |                                                                                    |
| AC operated                                                           | Operations                          | $\times 10^6$   | 10                                                                                 |
| Operating frequency, mechanical                                       |                                     |                 |                                                                                    |
| AC operated                                                           | Operations/h                        |                 | 5000                                                                               |
| Climatic proofing                                                     |                                     |                 | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30     |
| Ambient temperature                                                   |                                     |                 |                                                                                    |
| Open                                                                  |                                     | °C              | -25 - +60                                                                          |
| Enclosed                                                              |                                     | °C              | - 25 - 40                                                                          |
| Storage                                                               |                                     | °C              | - 40 - 80                                                                          |
| Mounting position                                                     |                                     |                 |  |
| Mechanical shock resistance (IEC/EN 60068-2-27)                       |                                     |                 |                                                                                    |
| Half-sinusoidal shock, 10 ms                                          |                                     |                 |                                                                                    |
| Main contacts                                                         |                                     |                 |                                                                                    |
| N/O contact                                                           |                                     | g               | 10                                                                                 |
| Auxiliary contacts                                                    |                                     |                 |                                                                                    |
| N/O contact                                                           |                                     | g               | 7                                                                                  |
| N/C contact                                                           |                                     | g               | 5                                                                                  |
| Mechanical shock resistance (IEC/EN 60068-2-27) when tabletop-mounted |                                     |                 |                                                                                    |
| Half-sinusoidal shock, 10 ms                                          |                                     |                 |                                                                                    |
| Main contacts                                                         |                                     |                 |                                                                                    |
| N/O contact                                                           |                                     | g               | 10                                                                                 |
| Auxiliary contacts                                                    |                                     |                 |                                                                                    |
| N/O contact                                                           |                                     | g               | 7                                                                                  |
| N/C contact                                                           |                                     | g               | 5                                                                                  |
| Degree of Protection                                                  |                                     |                 | IP00                                                                               |
| Protection against direct contact when actuated from front (EN 50274) |                                     |                 | Finger and back-of-hand proof                                                      |
| Altitude                                                              |                                     | m               | Max. 2000                                                                          |
| Weight                                                                |                                     |                 |                                                                                    |
| AC operated                                                           |                                     | kg              | 0.872                                                                              |
| Screw connector terminals                                             |                                     |                 |                                                                                    |
| Terminal capacity main cable                                          |                                     |                 |                                                                                    |
| Solid                                                                 |                                     | mm <sup>2</sup> | 1 x (0.75 - 16)<br>2 x (0.75 - 16)                                                 |
| Flexible with ferrule                                                 |                                     | mm <sup>2</sup> | 1 x (0.75 - 35)<br>2 x (0.75 - 25)                                                 |
| Stranded                                                              |                                     | mm <sup>2</sup> | 1 x (16 - 50)<br>2 x (16 - 35)                                                     |
| Solid or stranded                                                     |                                     | AWG             | single 14 - 1, double 14 - 2                                                       |
| Flat conductor                                                        | Lamellenzahl<br>x Breite x<br>Dicke | mm              | 2 x (6 x 9 x 0.8)                                                                  |
| Stripping length                                                      |                                     | mm              | 14                                                                                 |
| Terminal screw                                                        |                                     |                 | M6                                                                                 |
| Tightening torque                                                     |                                     | Nm              | 3.3                                                                                |
| Tool                                                                  |                                     |                 |                                                                                    |
| Pozidriv screwdriver                                                  |                                     | Size            | 2                                                                                  |
| Standard screwdriver                                                  |                                     | mm              | 0.8 x 5.5<br>1 x 6                                                                 |
| Spring-loaded terminal connection                                     |                                     |                 |                                                                                    |

|                                          |  |                 |                                      |
|------------------------------------------|--|-----------------|--------------------------------------|
| Terminal capacity control circuit cables |  |                 |                                      |
| Solid                                    |  | mm <sup>2</sup> | 1 x (0.75 - 2.5)<br>2 x (0.75 - 2.5) |
| Flexible                                 |  | mm <sup>2</sup> | 1 x (0.75 - 2.5)<br>2 x (0.75 - 2.5) |
| Flexible with ferrule                    |  | mm <sup>2</sup> | 1 x (0.75 - 1.5)<br>2 x (0.75 - 1.5) |
| Solid or stranded                        |  | AWG             | 18 - 14                              |
| Stripping length                         |  | mm              | 10                                   |
| Tool                                     |  |                 |                                      |
| Screwdriver blade width                  |  | mm              | 3.5                                  |

### Main conducting paths

|                                        |                  |      |       |
|----------------------------------------|------------------|------|-------|
| Rated impulse withstand voltage        | U <sub>imp</sub> | V AC | 8000  |
| Overvoltage category/pollution degree  |                  |      | III/3 |
| Rated insulation voltage               | U <sub>i</sub>   | V AC | 690   |
| Rated operational voltage              | U <sub>e</sub>   | V AC | 690   |
| Safe isolation to EN 61140             |                  |      |       |
| between coil and contacts              |                  | V AC | 440   |
| between the contacts                   |                  | V AC | 440   |
| Making capacity (p.f. to IEC/EN 60947) |                  |      |       |
|                                        | Up to 690 V      | A    | 700   |
| Breaking capacity                      |                  |      |       |
| 220 V 230 V                            |                  | A    | 500   |
| 380 V 400 V                            |                  | A    | 500   |
| 500 V                                  |                  | A    | 500   |
| 660 V 690 V                            |                  | A    | 320   |
| Short-circuit rating                   |                  |      |       |
| Short-circuit protection maximum fuse  |                  |      |       |
| Type "2" coordination                  |                  |      |       |
| 400 V                                  | gG/gL 500 V      | A    | 80    |
| 690 V                                  | gG/gL 690 V      | A    | 63    |
| Type "1" coordination                  |                  |      |       |
| 400 V                                  | gG/gL 500 V      | A    | 160   |
| 690 V                                  | gG/gL 690 V      | A    | 80    |

### AC

|                                                           |                                  |   |                                                    |
|-----------------------------------------------------------|----------------------------------|---|----------------------------------------------------|
| AC-1                                                      |                                  |   |                                                    |
| Rated operational current                                 |                                  |   |                                                    |
| Conventional free air thermal current, 3 pole, 50 - 60 Hz |                                  |   |                                                    |
| Open                                                      |                                  |   |                                                    |
| at 40 °C                                                  | I <sub>th</sub> = I <sub>e</sub> | A | 80                                                 |
| at 50 °C                                                  | I <sub>th</sub> = I <sub>e</sub> | A | 71                                                 |
| at 55 °C                                                  | I <sub>th</sub> = I <sub>e</sub> | A | 68                                                 |
| at 60 °C                                                  | I <sub>th</sub> = I <sub>e</sub> | A | 65                                                 |
| enclosed                                                  | I <sub>th</sub>                  | A | 58                                                 |
| Conventional free air thermal current, 1 pole             |                                  |   |                                                    |
| open                                                      | I <sub>th</sub>                  | A | 162                                                |
| enclosed                                                  | I <sub>th</sub>                  | A | 145                                                |
| AC-3                                                      |                                  |   |                                                    |
| Rated operational current                                 |                                  |   |                                                    |
| Open, 3-pole: 50 – 60 Hz                                  |                                  |   |                                                    |
| Notes                                                     |                                  |   | At maximum permissible ambient temperature (open.) |
| 220 V 230 V                                               | I <sub>e</sub>                   | A | 50                                                 |
| 240 V                                                     | I <sub>e</sub>                   | A | 50                                                 |
| 380 V 400 V                                               | I <sub>e</sub>                   | A | 50                                                 |
| 415 V                                                     | I <sub>e</sub>                   | A | 50                                                 |
| 440V                                                      | I <sub>e</sub>                   | A | 50                                                 |

|                          |                |     |      |
|--------------------------|----------------|-----|------|
| 500 V                    | I <sub>e</sub> | A   | 50   |
| 660 V 690 V              | I <sub>e</sub> | A   | 32   |
| 380 V 400 V              | I <sub>e</sub> | A   | 50   |
| Motor rating             | P              | kWh |      |
| 220 V 230 V              | P              | kW  | 15.5 |
| 240V                     | P              | kW  | 17   |
| 380 V 400 V              | P              | kW  | 22   |
| 415 V                    | P              | kW  | 30   |
| 440 V                    | P              | kW  | 32   |
| 500 V                    | P              | kW  | 36   |
| 660 V 690 V              | P              | kW  | 30   |
| AC-4                     |                |     |      |
| Open, 3-pole: 50 – 60 Hz |                |     |      |
| 220 V 230 V              | I <sub>e</sub> | A   | 21   |
| 240 V                    | I <sub>e</sub> | A   | 21   |
| 380 V 400 V              | I <sub>e</sub> | A   | 21   |
| 415 V                    | I <sub>e</sub> | A   | 21   |
| 440 V                    | I <sub>e</sub> | A   | 21   |
| 500 V                    | I <sub>e</sub> | A   | 21   |
| 660 V 690 V              | I <sub>e</sub> | A   | 17   |
| Motor rating             | P              | kWh |      |
| 220 V 230 V              | P              | kW  | 6    |
| 240 V                    | P              | kW  | 6.5  |
| 380 V 400 V              | P              | kW  | 10   |
| 415 V                    | P              | kW  | 11   |
| 440 V                    | P              | kW  | 12   |
| 500 V                    | P              | kW  | 13   |
| 660 V 690 V              | P              | kW  | 14   |

## DC

|                                 |                |   |    |
|---------------------------------|----------------|---|----|
| Rated operational current, open |                |   |    |
| DC-1                            |                |   |    |
| 60 V                            | I <sub>e</sub> | A | 60 |
| 110 V                           | I <sub>e</sub> | A | 50 |
| 220 V                           | I <sub>e</sub> | A | 45 |

## Current heat loss

|                                                   |  |    |      |
|---------------------------------------------------|--|----|------|
| 3 pole, at I <sub>th</sub> (60°)                  |  | W  | 16.7 |
| Current heat loss at I <sub>e</sub> to AC-3/400 V |  | W  | 9.9  |
| Impedance per pole                                |  | mΩ | 1.9  |

## Magnet systems

|                                                                        |          |                  |           |
|------------------------------------------------------------------------|----------|------------------|-----------|
| Voltage tolerance                                                      |          |                  |           |
| AC operated                                                            | Pick-up  | x U <sub>c</sub> | 0.8 - 1.1 |
| Drop-out voltage AC operated                                           | Drop-out | x U <sub>c</sub> | 0.3 - 0.6 |
| Power consumption of the coil in a cold state and 1.0 x U <sub>S</sub> |          |                  |           |
| 50 Hz                                                                  | Pick-up  | VA               | 149       |
| 50 Hz                                                                  | Sealing  | VA               | 16        |
| 50 Hz                                                                  | Sealing  | W                | 4.1       |
| 60 Hz                                                                  | Pick-up  | VA               | 178       |
| 60 Hz                                                                  | Sealing  | VA               | 19        |
| 60 Hz                                                                  | Sealing  | W                | 4.1       |
| Duty factor                                                            |          | % DF             | 100       |
| Changeover time at 100 % U <sub>S</sub> (recommended value)            |          |                  |           |
| Main contacts                                                          |          |                  |           |
| AC operated                                                            |          |                  |           |
| Closing delay                                                          |          | ms               | 12 - 18   |

|                                            |      |                 |
|--------------------------------------------|------|-----------------|
| Opening delay                              | ms   | 8 - 13          |
| Arcing time                                | ms   | 10              |
| <b>Electromagnetic compatibility (EMC)</b> |      |                 |
| Emitted interference                       |      | to EN 60947-1   |
| Interference immunity                      |      | to EN 60947-1   |
| <b>Rating data for approved types</b>      |      |                 |
| Switching capacity                         |      |                 |
| Maximum motor rating                       |      |                 |
| Three-phase                                |      |                 |
| 200 V<br>208 V                             | HP   | 15              |
| 230 V<br>240 V                             | HP   | 20              |
| 460 V<br>480 V                             | HP   | 40              |
| 575 V<br>600 V                             | HP   | 50              |
| Single-phase                               |      |                 |
| 115 V<br>120 V                             | HP   | 3               |
| 230 V<br>240 V                             | HP   | 10              |
| General use                                | A    | 80              |
| Short Circuit Current Rating               | SCCR |                 |
| Basic Rating                               |      |                 |
| SCCR                                       | kA   | 10              |
| max. Fuse                                  | A    | 250             |
| max. CB                                    | A    | 250             |
| 480 V High Fault                           |      |                 |
| SCCR (fuse)                                | kA   | 30/100          |
| max. Fuse                                  | A    | 250/150 Class J |
| SCCR (CB)                                  | kA   | 65              |
| max. CB                                    | A    | 100             |
| 600 V High Fault                           |      |                 |
| SCCR (fuse)                                | kA   | 30/100          |
| max. Fuse                                  | A    | 250/150 Class J |
| SCCR (CB)                                  | kA   | 30              |
| max. CB                                    | A    | 250             |
| Special Purpose Ratings                    |      |                 |
| Electrical Discharge Lamps (Ballast)       |      |                 |
| 480V 60Hz 3phase, 277V 60Hz 1phase         | A    | 79              |
| 600V 60Hz 3phase, 347V 60Hz 1phase         | A    | 79              |
| Incandescent Lamps (Tungsten)              |      |                 |
| 480V 60Hz 3phase, 277V 60Hz 1phase         | A    | 74              |
| 600V 60Hz 3phase, 347V 60Hz 1phase         | A    | 74              |
| Resistance Air Heating                     |      |                 |
| 480V 60Hz 3phase, 277V 60Hz 1phase         | A    | 79              |
| 600V 60Hz 3phase, 347V 60Hz 1phase         | A    | 79              |
| Elevator Control                           |      |                 |
| 200V 60Hz 3phase                           | HP   | 10              |
| 200V 60Hz 3phase                           | A    | 32.2            |
| 240V 60Hz 3phase                           | HP   | 15              |
| 240V 60Hz 3phase                           | A    | 42              |
| 480V 60Hz 3phase                           | HP   | 30              |
| 480V 60Hz 3phase                           | A    | 40              |
| 600V 60Hz 3phase                           | HP   | 40              |
| 600V 60Hz 3phase                           | A    | 41              |

## Design verification as per IEC/EN 61439

|                                                                                                                        |                   |    |                                                                                                                                  |
|------------------------------------------------------------------------------------------------------------------------|-------------------|----|----------------------------------------------------------------------------------------------------------------------------------|
| Technical data for design verification                                                                                 |                   |    |                                                                                                                                  |
| Rated operational current for specified heat dissipation                                                               | I <sub>n</sub>    | A  | 50                                                                                                                               |
| Heat dissipation per pole, current-dependent                                                                           | P <sub>vid</sub>  | W  | 3.3                                                                                                                              |
| Equipment heat dissipation, current-dependent                                                                          | P <sub>vid</sub>  | W  | 9.9                                                                                                                              |
| Static heat dissipation, non-current-dependent                                                                         | P <sub>vs</sub>   | W  | 4.1                                                                                                                              |
| Heat dissipation capacity                                                                                              | P <sub>diss</sub> | W  | 0                                                                                                                                |
| Operating ambient temperature min.                                                                                     |                   | °C | -25                                                                                                                              |
| Operating ambient temperature max.                                                                                     |                   | °C | 60                                                                                                                               |
| IEC/EN 61439 design verification                                                                                       |                   |    |                                                                                                                                  |
| 10.2 Strength of materials and parts                                                                                   |                   |    |                                                                                                                                  |
| 10.2.2 Corrosion resistance                                                                                            |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.1 Verification of thermal stability of enclosures                                                               |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat                                             |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                                                       |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.5 Lifting                                                                                                         |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.2.6 Mechanical impact                                                                                               |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.2.7 Inscriptions                                                                                                    |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.3 Degree of protection of ASSEMBLIES                                                                                |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.4 Clearances and creepage distances                                                                                 |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.5 Protection against electric shock                                                                                 |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.6 Incorporation of switching devices and components                                                                 |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.7 Internal electrical circuits and connections                                                                      |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.8 Connections for external conductors                                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9 Insulation properties                                                                                             |                   |    |                                                                                                                                  |
| 10.9.2 Power-frequency electric strength                                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9.3 Impulse withstand voltage                                                                                       |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9.4 Testing of enclosures made of insulating material                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.10 Temperature rise                                                                                                 |                   |    | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating                                                                                             |                   |    | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility                                                                                    |                   |    | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function                                                                                              |                   |    | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

## Technical data ETIM 7.0

|                                                                                                                                                                                       |  |    |                  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|------------------|
| Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)                                                                                               |  |    |                  |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015]) |  |    |                  |
| Rated control supply voltage U <sub>s</sub> at AC 50HZ                                                                                                                                |  | V  | 230 - 230        |
| Rated control supply voltage U <sub>s</sub> at AC 60HZ                                                                                                                                |  | V  | 240 - 240        |
| Rated control supply voltage U <sub>s</sub> at DC                                                                                                                                     |  | V  | 0 - 0            |
| Voltage type for actuating                                                                                                                                                            |  |    | AC               |
| Rated operation current I <sub>e</sub> at AC-1, 400 V                                                                                                                                 |  | A  | 80               |
| Rated operation current I <sub>e</sub> at AC-3, 400 V                                                                                                                                 |  | A  | 50               |
| Rated operation power at AC-3, 400 V                                                                                                                                                  |  | kW | 22               |
| Rated operation current I <sub>e</sub> at AC-4, 400 V                                                                                                                                 |  | A  | 21               |
| Rated operation power at AC-4, 400 V                                                                                                                                                  |  | kW | 10               |
| Rated operation power NEMA                                                                                                                                                            |  | kW | 29.8             |
| Modular version                                                                                                                                                                       |  |    | No               |
| Number of auxiliary contacts as normally open contact                                                                                                                                 |  |    | 0                |
| Number of auxiliary contacts as normally closed contact                                                                                                                               |  |    | 0                |
| Type of electrical connection of main circuit                                                                                                                                         |  |    | Screw connection |
| Number of normally closed contacts as main contact                                                                                                                                    |  |    | 0                |

|                                                  |   |
|--------------------------------------------------|---|
| Number of main contacts as normally open contact | 3 |
|--------------------------------------------------|---|


Approvals

|                                      |                                                                          |
|--------------------------------------|--------------------------------------------------------------------------|
| Product Standards                    | IEC/EN 60947-4-1; UL 60947-4-1; CSA - C22.2 No. 60947-4-1-14; CE marking |
| UL File No.                          | E29096                                                                   |
| UL Category Control No.              | NLDX                                                                     |
| CSA File No.                         | 012528                                                                   |
| CSA Class No.                        | 2411-03, 3211-04                                                         |
| North America Certification          | UL listed, CSA certified                                                 |
| Specially designed for North America | No                                                                       |


Characteristics

1: Overload relay  
2: Suppressor  
3: Auxiliary contact modules

# DILM1000-XHI(V)11-...




on the side: 2 x DILM1000-XHI(V)11-SI; surface mounting: 1 x DILM150-XHIA11  
 on the side: 2 x DILM1000-XHI(V)11-SA; surface mounting: 1 x DILM150-XHI (2 pole)  
 on the side: 1 x DILM1000-XHI(V)11-SI; surface mounting: 1 x DILM150-XHIA22  
 on the side: 1 x DILM1000-XHI(V)11-SA; surface mounting: 1 x DILM150-XHI (4 pole)






Squirrel-cage motor  
 Operating characteristics  
 Starting: from rest  
 Stopping: after attaining full running speed  
 Electrical characteristics  
 Make: up to 6 x rated motor current  
 Break: up to 1 x rated motor current  
 Utilization category  
 100 % AC-3  
 Typical applications  
 Compressors  
 Lifts  
 Mixers  
 Pumps  
 Escalators  
 Agitators  
 Fans  
 Conveyor belts  
 Centrifuges  
 Hinged flaps  
 Bucket-elevators  
 Air conditioning system  
 General drives in manufacturing and processing machines




Extreme switching duty  
 Squirrel-cage motor  
 Operating characteristics  
 Inching, plugging, reversing  
 Electrical characteristics  
 Make: up to 6 x rated motor current  
 Break: up to 6 x rated motor current  
 Utilization category  
 100 % AC-4  
 Typical applications  
 Printing presses  
 Wire-drawing machines  
 Centrifuges  
 Special drives for manufacturing and processing machines




Switching conditions for non-motor consumers, 3 pole, 4 pole  
 Operating characteristics  
 Non inductive and slightly inductive loads  
 Electrical characteristics  
 Switch on: 1 x rated operational current  
 Switch off: 1 x rated operational current  
 Utilization category  
 100 % AC-1  
 Typical examples of application  
 Electric heat

Dimensions



Contactor with auxiliary contact module



Lateral clearance to earthed parts: 6 mm

DILM40...DILM72  
DILMC40...DILMC65  
DILMF40...DILMF65

## Assets (links)

### Declaration of CE Conformity

00003252

### Instruction Leaflets

IL03407033Z2018\_03