



277701
DILM C32-10(230V50HZ,240V60HZ)

[Overview](#)
[Specifications](#)
[Resources](#)



DELIVERY PROGRAM

[Delivery program](#)

[Technical data](#)

[Design verification as
per IEC/EN 61439](#)

[Technical data ETIM 7.0](#)

[Approvals](#)

[Characteristics](#)

[Dimensions](#)

Product range
 Contactors

Application
 Contactors for Motors

Subrange
 Contactors up to 170 A, 3 pole

Utilization category
 AC-1: Non-inductive or slightly inductive loads,
 resistance furnaces
 AC-3/AC-3e: Normal AC induction motors: Starting,
 switching off while running
 AC-4: Normal AC induction motors: starting,
 plugging, reversing, inching



Notes
 Also suitable for motors with efficiency class IE3.

Connection technique
Spring-loaded terminals

Description
Spring-cage terminals on auxiliary and control
circuit terminals

Number of poles
3 pole

Rated operational current

AC-3
Notes
At maximum permissible ambient temperature
(open.)
Also tested according to AC-3e.

AC-3
380 V 400 V [I_e]
32 A

AC-1
Conventional free air thermal current, 3 pole, 50 -
60 Hz
Open
at 40 °C [$I_{th} = I_e$]
45 A

AC-1
Conventional free air thermal current, 3 pole, 50 -
60 Hz
enclosed [I_{th}]
36 A

AC-1
Conventional free air thermal current, 1 pole
open [I_{th}]
100 A

AC-1
Conventional free air thermal current, 1 pole
enclosed [I_{th}]
90 A

Max. rating for three-phase motors, 50 - 60 Hz

AC-3
220 V 230 V [P]
10 kW

AC-3
380 V 400 V [P]
15 kW

AC-3
660 V 690 V [P]
17 kW

AC-4
220 V 230 V [P]
4 kW

AC-4
380 V 400 V [P]
7 kW

AC-4
660 V 690 V [P]
10 kW

Contacts

NO = Normally open
1 NO

Contact sequence



Instructions

Contacts to EN 50 012.

Auxiliary current, coil connections with spring-cage connection technology.

Main current connections with screw terminals.

Can be combined with auxiliary contact

DILM32-XHC...

DILA-XHC(V)...

Actuating voltage
230 V 50 Hz, 240 V 60 Hz

Voltage AC/DC
AC operation

Connection to SmartWire-DT
no

Frame size
2

TECHNICAL DATA

General

Standards
IEC/EN 60947, VDE 0660, UL, CSA

Lifespan, mechanical
AC operated [Operations]
 10×10^6

Operating frequency, mechanical
AC operated [Operations/h]
5000


Climatic proofing
Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature
Open
-25 - +60 °C

Ambient temperature
Enclosed
- 25 - 40 °C

Ambient temperature
Storage
- 40 - 80 °C

Mounting position



Mechanical shock resistance (IEC/EN 60068-2-27)

Half-sinusoidal shock, 10 ms

Main contacts

N/O contact

10 g

Mechanical shock resistance (IEC/EN 60068-2-27)

Half-sinusoidal shock, 10 ms

Auxiliary contacts

N/O contact

7 g

Mechanical shock resistance (IEC/EN 60068-2-27)

Half-sinusoidal shock, 10 ms

Auxiliary contacts

N/C contact

5 g

Mechanical shock resistance (IEC/EN 60068-2-27)

when tabletop-mounted

Half-sinusoidal shock, 10 ms

Main contacts

N/O contact

6.9 g

Mechanical shock resistance (IEC/EN 60068-2-27)

when tabletop-mounted

Half-sinusoidal shock, 10 ms

Auxiliary contacts

N/O contact

5.3 g

Mechanical shock resistance (IEC/EN 60068-2-27)

when tabletop-mounted

Half-sinusoidal shock, 10 ms

Auxiliary contacts

N/C contact

3.5 g

Degree of Protection

IP00

Protection against direct contact when actuated
from front (EN 50274)

Finger and back-of-hand proof

Altitude
Max. 2000 m

Weight
AC operated
0.433 kg

Screw connector terminals
Terminal capacity main cable
Solid
1 x (0.75 - 16)
2 x (0.75 - 10) mm²

Screw connector terminals
Terminal capacity main cable
Flexible with ferrule
1 x (0.75 - 16)
2 x (0.75 - 10) mm²

Screw connector terminals
Terminal capacity main cable
Stranded
1 x 16 mm²

Screw connector terminals
Terminal capacity main cable
Solid or stranded
single 18 - 6, double 18 - 8 AWG

Screw connector terminals
Terminal capacity main cable
Stripping length
10 mm

Screw connector terminals
Terminal capacity main cable
Terminal screw
M5

Screw connector terminals
Terminal capacity main cable
Tightening torque
3.2 Nm

Screw connector terminals
Terminal capacity main cable
Tool
Pozidriv screwdriver
2 Size

Screw connector terminals
Terminal capacity main cable
Tool
Standard screw driver
0.8 x 5.5
1 x 6 mm

Spring-loaded terminal connection
Terminal capacity control circuit cables
Flexible
1 x (0.75 - 2.5)
2 x (0.75 - 2.5) mm²

Spring-loaded terminal connection
Terminal capacity control circuit cables
Flexible with ferrule
1 x (0.75 - 1.5)
2 x (0.75 - 1.5) mm²

Spring-loaded terminal connection
Terminal capacity control circuit cables
Solid or stranded
18 - 14 AWG

Spring-loaded terminal connection
Terminal capacity control circuit cables
Stripping length
10 mm

Spring-loaded terminal connection
Tool
Screw driver blade width
3.5 mm

Main conducting paths

Rated impulse withstand voltage [U_{imp}]
8000 V AC

Overvoltage category/pollution degree
III/3

Rated insulation voltage [U_i]
690 V AC

Rated operational voltage [U_e]
690 V AC

Safe isolation to EN 61140
between coil and contacts
440 V AC

Safe isolation to EN 61140
between the contacts
440 V AC

Making capacity (p.f. to IEC/EN 60947) [Up to 690
V]
384 A

Breaking capacity
220 V 230 V
320 A

Breaking capacity
380 V 400 V
320 A

Breaking capacity
500 V
320 A

Breaking capacity
660 V 690 V
180 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "2" coordination
400 V [gG/gL 500 V]
63 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "2" coordination
690 V [gG/gL 690 V]
35 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "1" coordination
400 V [gG/gL 500 V]
125 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "1" coordination

690 V [gG/gL 690 V]
63 A

AC

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 -
60 Hz
Open
at 40 °C [$I_{th} = I_e$]
45 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 -
60 Hz
Open
at 50 °C [$I_{th} = I_e$]
43 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 -
60 Hz
Open
at 55 °C [$I_{th} = I_e$]
42 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 -
60 Hz
Open
at 60 °C [$I_{th} = I_e$]
40 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 -
60 Hz
enclosed [I_{th}]
36 A

AC-1
Rated operational current
Conventional free air thermal current, 1 pole
open [I_{th}]
100 A

AC-1
Rated operational current
Conventional free air thermal current, 1 pole

enclosed [I_{th}]
90 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
Notes
At maximum permissible ambient temperature
(open.)
Also tested according to AC-3e.

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
220 V 230 V [I_e]
32 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
240 V [I_e]
32 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
380 V 400 V [I_e]
32 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
415 V [I_e]
32 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
440V [I_e]
32 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
500 V [I_e]
32 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
660 V 690 V [I_e]
18 A

AC-3
Motor rating [P]
220 V 230 V [P]
10 kW

AC-3
Motor rating [P]
240V [P]
11 kW

AC-3
Motor rating [P]
380 V 400 V [P]
15 kW

AC-3
Motor rating [P]
415 V [P]
19 kW

AC-3
Motor rating [P]
440 V [P]
20 kW

AC-3
Motor rating [P]
500 V [P]
23 kW

AC-3
Motor rating [P]
660 V 690 V [P]
17 kW

AC-4
Open, 3-pole: 50 – 60 Hz
220 V 230 V [I_e]
15 A

AC-4
Open, 3-pole: 50 – 60 Hz
240 V [I_e]
15 A

AC-4
Open, 3-pole: 50 – 60 Hz
380 V 400 V [I_e]
15 A

AC-4
Open, 3-pole: 50 – 60 Hz
415 V [I_e]
15 A

AC-4
Open, 3-pole: 50 – 60 Hz
440 V [I_e]
15 A

AC-4
Open, 3-pole: 50 – 60 Hz
500 V [I_e]
15 A

AC-4
Open, 3-pole: 50 – 60 Hz
660 V 690 V [I_e]
12 A

AC-4
Mtor rating [P]
220 V 230 V [P]
4 kW

AC-4
Mtor rating [P]
240 V [P]
4.5 kW

AC-4
Mtor rating [P]
380 V 400 V [P]
7 kW

AC-4
Mtor rating [P]
415 V [P]
7.5 kW

AC-4
Mtor rating [P]
440 V [P]
8 kW

AC-4
Mtor rating [P]
500 V [P]
9 kW

AC-4
Motor rating [P]
660 V 690 V [P]
10 kW

DC

Rated operational current, open
DC-1
60 V [I_e]
40 A

Rated operational current, open
DC-1
110 V [I_e]
40 A

Rated operational current, open
DC-1
220 V [I_e]
40 A

Current heat loss

3 pole, at I_{th} (60°)
10.3 W

Current heat loss at I_e to AC-3/400 V
6.6 W

Impedance per pole
2.7 mΩ

Magnet systems

Voltage tolerance
AC operated [Pick-up]
 $0.8 - 1.1 \times U_e$

Voltage tolerance
Drop-out voltage AC operated [Drop-out]
 $0.3 - 0.6 \times U_e$

Power consumption of the coil in a cold state and
 $1.0 \times U_b$
50 Hz [Pick-up]
52 VA

Power consumption of the coil in a cold state and
1.0 x U_N
50 Hz [Sealing]
7.1 VA

Power consumption of the coil in a cold state and
1.0 x U_N
50 Hz [Sealing]
2.1 W

Power consumption of the coil in a cold state and
1.0 x U_N
60 Hz [Pick-up]
67 VA

Power consumption of the coil in a cold state and
1.0 x U_N
60 Hz [Sealing]
8.7 VA

Power consumption of the coil in a cold state and
1.0 x U_N
60 Hz [Sealing]
2.1 W

Duty factor
100 % DF

Changeover time at 100 % U_N (recommended
value)
Main contacts
AC operated
Closing delay
16 - 22 ms

Changeover time at 100 % U_N (recommended
value)
Main contacts
AC operated
Opening delay
8 - 14 ms

Changeover time at 100 % U_N (recommended
value)
Arcing time
10 ms

Electromagnetic compatibility (EMC)

Emitted interference
to EN 60947-1

Interference immunity
to EN 60947-1

Rating data for approved types

Switching capacity
Maximum motor rating
Three-phase
200 V
208 V
10 HP

Switching capacity
Maximum motor rating
Three-phase
230 V
240 V
10 HP

Switching capacity
Maximum motor rating
Three-phase
460 V
480 V
20 HP

Switching capacity
Maximum motor rating
Three-phase
575 V
600 V
25 HP

Switching capacity
Maximum motor rating
Single-phase
115 V
120 V
2 HP

Switching capacity
Maximum motor rating
Single-phase
230 V
240 V
5 HP

Switching capacity

General use
40 A

Auxiliary contacts
Pilot Duty
AC operated
A600

Auxiliary contacts
Pilot Duty
DC operated
P300

Auxiliary contacts
General Use
AC
600 V

Auxiliary contacts
General Use
AC
10 A

Auxiliary contacts
General Use
DC
250 V

Auxiliary contacts
General Use
DC
1 A

Short Circuit Current Rating
Basic Rating
SCCR
5 kA

Short Circuit Current Rating
Basic Rating
max. Fuse
125 A

Short Circuit Current Rating
Basic Rating
max. CB
125 A

Short Circuit Current Rating
480 V High Fault

SCCR (fuse)
10/100 kA

Short Circuit Current Rating
480 V High Fault
max. Fuse
125/70 Class J A

Short Circuit Current Rating
480 V High Fault
SCCR (CB)
10/65 kA

Short Circuit Current Rating
480 V High Fault
max. CB
50/32 A

Short Circuit Current Rating
600 V High Fault
SCCR (fuse)
10/100 kA

Short Circuit Current Rating
600 V High Fault
max. Fuse
125/125 Class J A

Short Circuit Current Rating
600 V High Fault
SCCR (CB)
10/22 kA

Short Circuit Current Rating
600 V High Fault
max. CB
50/32 A

Special Purpose Ratings
Electrical Discharge Lamps (Ballast)
480V 60Hz 3phase, 277V 60Hz 1phase
40 A

Special Purpose Ratings
Electrical Discharge Lamps (Ballast)
600V 60Hz 3phase, 347V 60Hz 1phase
40 A

Special Purpose Ratings
Incandescent Lamps (Tungsten)

480V 60Hz 3phase, 277V 60Hz 1phase
40 A

Special Purpose Ratings
Incandescent Lamps (Tungsten)
600V 60Hz 3phase, 347V 60Hz 1phase
40 A

Special Purpose Ratings
Resistance Air Heating
480V 60Hz 3phase, 277V 60Hz 1phase
40 A

Special Purpose Ratings
Resistance Air Heating
600V 60Hz 3phase, 347V 60Hz 1phase
40 A

Special Purpose Ratings
Refrigeration Control (CSA only)
LRA 480V 60Hz 3phase
240 A

Special Purpose Ratings
Refrigeration Control (CSA only)
FLA 480V 60Hz 3phase
40 A

Special Purpose Ratings
Refrigeration Control (CSA only)
LRA 600V 60Hz 3phase
180 A

Special Purpose Ratings
Refrigeration Control (CSA only)
FLA 600V 60Hz 3phase
30 A

Special Purpose Ratings
Definite Purpose Ratings (100,000 cycles acc. to
UL 1995)
LRA 480V 60Hz 3phase
192 A

Special Purpose Ratings
Definite Purpose Ratings (100,000 cycles acc. to
UL 1995)
FLA 480V 60Hz 3phase
32 A

Special Purpose Ratings
Elevator Control
200V 60Hz 3phase
7.5 HP

Special Purpose Ratings
Elevator Control
200V 60Hz 3phase
25.3 A

Special Purpose Ratings
Elevator Control
240V 60Hz 3phase
7.5 HP

Special Purpose Ratings
Elevator Control
240V 60Hz 3phase
22 A

Special Purpose Ratings
Elevator Control
480V 60Hz 3phase
20 HP

Special Purpose Ratings
Elevator Control
480V 60Hz 3phase
27 A

Special Purpose Ratings
Elevator Control
600V 60Hz 3phase
20 HP

Special Purpose Ratings
Elevator Control
600V 60Hz 3phase
22 A

DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat
dissipation [I_n]

Heat dissipation per pole, current-dependent [P_{vd}]
2.2 W

Equipment heat dissipation, current-dependent
[P_{vd}]
6.6 W

Static heat dissipation, non-current-dependent [P_{vs}]
2.1 W

Heat dissipation capacity [P_{diss}]
0 W

Operating ambient temperature min.
-25 °C

Operating ambient temperature max.
+60 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of
enclosures
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.2 Verification of resistance of insulating
materials to normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.3 Verification of resistance of insulating
materials to abnormal heat and fire due to internal
electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015])

Rated control supply voltage U_s at AC 50-HZ
230 - 230 V

Rated control supply voltage U_s at AC 60-HZ
240 - 240 V

Rated control supply voltage U_s at DC
0 - 0 V

Voltage type for actuating
AC

Rated operation current I_e at AC-1, 400 V
45 A

Rated operation current I_e at AC-3, 400 V
32 A

Rated operation power at AC-3, 400 V
15 kW

Rated operation current I_e at AC-4, 400 V
15 A

Rated operation power at AC-4, 400 V
7 kW

Rated operation power NEMA
14.9 kW

Modular version
No

Number of auxiliary contacts as normally open
contact
1

Number of auxiliary contacts as normally closed
contact
0

Type of electrical connection of main circuit
Screw connection

Number of normally closed contacts as main
contact
0

Number of main contacts as normally open contact
3

APPROVALS

Product Standards
IEC/EN 60947-4-1; UL 60947-4-1; CSA - C22.2 No.
60947-4-1-14; CE marking

UL File No.
E29096

UL Category Control No.
NLDX

CSA File No.
012528

CSA Class No.
2411-03, 3211-04

North America Certification
UL listed, CSA certified

Specially designed for North America
No

CHARACTERISTICS



Accessories
1: Overload relay
2: Suppressor
3: Auxiliary contact modules


Characteristic curve



Squirrel-cage motor
Operating characteristics
Starting:from rest
Stopping:after attaining full running speed
Electrical characteristics
Make: up to 6 x rated motor current
Break: up to 1 x rated motor current
Utilization category
100 % AC-3
Typical applications
Compressors
Lifts
Mixers
Pumps
Escalators
Agitators
Fans

Conveyor belts
Centrifuges
Hinged flaps
Bucket-elevators
Air conditioning system
General drives in manufacturing and processing machines

Characteristic curve



Extreme switching duty
Squirrel-cage motor
Operating characteristics
Inching, plugging, reversing
Electrical characteristics
Make: up to 6 x rated motor current
Break: up to 6 x rated motor current
Utilization category
100 % AC-4
Typical applications
Printing presses
Wire-drawing machines
Centrifuges
Special drives for manufacturing and processing machines

Characteristic curve



Switching conditions for non-motor consumers, 3 pole, 4 pole
Operating characteristics
Non inductive and slightly inductive loads
Electrical characteristics
Switch on: 1 x rated operational current
Switch off: 1 x rated operational current
Utilization category
100 % AC-1
Typical examples of application
Electric heat

DIMENSIONS



Contactor with auxiliary contact module



distance at side to earthed parts: 6 mm

