



Powering Business Worldwide



101672

DILM12-XSPD



Overview



Specifications



Resources



[Delivery program >](#)

[Design verification as
per IEC/EN 61439 >](#)

[Technical data ETIM7.0
>](#)

[Approvals >](#)

[Dimensions >](#)

DELIVERY PROGRAM


Product range
Accessories

Accessories
Suppressor circuit

Voltage [U_b]
12 - 250 DC V

For use with
DILM7 - DILM15
DILMP20
DILA

Contact sequence



Instructions

Additional for integrated suppressor with DC

operated contactors.
Prevention of negative switch-off voltage when
the contactor is used together with a safety PLC.

DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat
dissipation [I_n]
0 A

Heat dissipation per pole, current-dependent [P_{id}]
0 W

Equipment heat dissipation, current-dependent
[P_{id}]
0 W

Static heat dissipation, non-current-dependent [P_{is}]
0 W

Heat dissipation capacity [P_{diss}]
0 W

Operating ambient temperature min.
-25 °C

Operating ambient temperature max.
+60 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of
enclosures
Meets the product standard's requirements.

10.2 Strength of materials and parts
2/6

10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.

10.8 Connections for external conductors
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.

10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Surge protection module (EC000683)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Component for protective circuit (ecl@ss10.0.1-27-37-10-10 [AKF019013])

Function
Diode

Rated control supply voltage U_s at AC 50-Hz
0 - 0 V

Rated control supply voltage U_s at AC 60-Hz
0 - 0 V

Rated control supply voltage U_s at DC
12 - 250 V

Voltage type for actuating
DC

With LED indication
No

APPROVALS

Product Standards
IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05;
CE marking

UL File No.
E29184

UL Category Control No.
NKC2, NKC8

CSA File No.
256465

CSA Class No.
3211-07

North America Certification
UL recognized, CSA certified

Specially designed for North America
No

DIMENSIONS

