Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norw egian Bokmål

Worldwide English



DILM95-XSL - Secondary terminal wire kit, star-delta, DILM80-95



101486 DILM95-XSL

Overview Specifications Resources



101486 DILM95-XSL

Secondary terminal wire kit, star-delta, DILM80-95 Alternate Catalog No. EL-Nummer (Norway) Quick, reliable wiring using wire jumpers.

XTOEXSDLF 4137732

Delivery program

Design verification as per IEC/EN 61439

- Technical data ETIM 7.0
- Approvals

Delivery program

Product range

Accessories

Accessories

Wiring accessories

Description

Main current wiring for star-delta combination

Including star-point bridge

For use with

DILM50

DILM65

DILM80

DILM95

For use with

DILM 80/95 mains contactor

DILM80/95 delta contactor

DILM50/65 star contactor

Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [In]

130 A

Heat dissipation per pole, current-dependent [P_{vid}]

3.2 W

Equipment heat dissipation, current-dependent [Pid]

9.6 W

Static heat dissipation, non-current-dependent [P_s]

0 W

Heat dissipation capacity [Pdiss]

0 W

Operating ambient temperature min.

-25°C

Operating ambient temperature max.

+60 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEVBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switch technology (accessories) (ecl@ss10.0.1-27-37-13-92 [AKN570013])

Type of accessory

Connecting bridge

Approvals

Product Standards

IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05; CE marking

UL File No.

E36332

UL Category Control No.
NLRV
CSA File No.
012528
CSA Class No.
2411-03, 3211-04
North America Certification
UL listed, CSA certified
Specially designed for North America

CAD data

- Product-specific CAD data (Web)
- 3D Preview (Web)

DWG files

DA-CD-dilm95_xsl File (Web)

edz files

 DA-CE-ETN.DILM95-XSL File (Web)


Step files

DA-CS-dilm95_xsl File (Web)

Additional product information

- Motor starters and "Special Purpose Ratings" for the North American market (PDF)
- Switchgear of Power Factor Correction Systems (PDF)
- X-Start Modern Switching Installations Efficiently Fitted and Wired Securely (PDF)
- Mrror Contacts for Highly-Reliable Information Relating to Safety-Related Control Functions (PDF)
- Effect of the Cabel Capacitance of Long Control Cables on the Actuation of Contactors (PDF)
- Switchgear for Luminaires (PDF)
- Standard Compliant and Functionally Safe Engineering Design with Mechanical Auxiliary Contacts (PDF)
- The Interaction of Contactors with PLCs (PDF)
- Busbar Component Adapters for modern Industrial control panels (PDF)

3D drawing



Product photo





Standards

• **XStart** 000Z153 Logo xStart logo

Instruction Leaflet

• Wiring kits (IL03407045Z) (PDF, multilingual)

Download-Center

- Download-Center (this item) Eaton EVEA Download-Center - download data for this item
- Download-Center Eaton EVEA Download-Center

Generate data sheet in PDF format

B

X

Generate data sheet in Excel format

 \Box

Write a comment Imprint Privacy Policy Legal Disclaimer Terms and Conditions © 2021 by Eaton Industries GmbH