



239765  
DILMC150(RDC24)

Overview

Specifications

Resources



Delivery program

Technical data

Design verification as  
per IEC/EN 61439

Technical data ETIM 7.0

Approvals

Characteristics

Dimensions

## DELIVERY PROGRAM

Product range  
Contactors

Application  
Contactors for Motors

Subrange  
Contactors up to 170 A, 3 pole

Utilization category  
AC-1: Non-inductive or slightly inductive loads,  
resistance furnaces  
AC-3/AC-3e: Normal AC induction motors: Starting,  
switching off while running  
AC-4: Normal AC induction motors: starting,  
plugging, reversing, inching



Notes  
Also suitable for motors with efficiency class IE3.

Connection technique  
Spring-loaded terminals

Description  
Spring-cage terminals on auxiliary and control  
circuit terminals

Number of poles  
3 pole

### Rated operational current

AC-3  
Notes  
At maximum permissible ambient temperature  
(open.)  
Also tested according to AC-3e.

AC-3  
380 V 400 V [ $I_e$ ]  
150 A

AC-1  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 40 °C [ $I_{th} = I_e$ ]  
190 A

AC-1  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
enclosed [ $I_{th}$ ]  
144 A

AC-1  
Conventional free air thermal current, 1 pole  
open [ $I_{th}$ ]  
400 A

AC-1  
Conventional free air thermal current, 1 pole  
enclosed [ $I_{th}$ ]  
360 A

### Max. rating for three-phase motors, 50 - 60 Hz

AC-3  
220 V 230 V [P]  
48 kW

AC-3  
380 V 400 V [P]  
75 kW

AC-3  
660 V 690 V [P]  
96 kW

AC-4  
220 V 230 V [P]  
20 kW

AC-4  
380 V 400 V [P]  
33 kW

AC-4  
660 V 690 V [P]  
48 kW

Contact sequence



### Instructions

Contacts to EN 50 012.

Auxiliary current, coil connections with spring-cage connection technology.

Main current connections with screw terminals.

integrated suppressor circuit in actuating electronics

Can be combined with auxiliary contact  
DILM150-XHIC(V)...  
DILM1000-XHIC...

Actuating voltage  
RDC 24: 24 - 27 V DC

Voltage AC/DC  
DC operation

Connection to SmartWire-DT

no

Frame size  
4

## TECHNICAL DATA

### General

Standards  
IEC/EN 60947, VDE 0660, UL, CSA

Lifespan, mechanical  
DC operated [Operations]  
 $6.4 \times 10^6$

Operating frequency, mechanical  
DC operated [Operations/h]  
3600


Climatic proofing  
Damp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature  
Open  
-25 - +60 °C

Ambient temperature  
Enclosed  
- 25 - 40 °C

Ambient temperature  
Storage  
- 40 - 80 °C

Mounting position



Mechanical shock resistance (IEC/EN 60068-2-27)

Half-sinusoidal shock, 10 ms  
Main contacts  
N/O contact  
10 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms  
Auxiliary contacts  
N/O contact  
7 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms  
Auxiliary contacts  
N/C contact  
5 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
when tabletop-mounted  
Half-sinusoidal shock, 10 ms  
Main contacts  
N/O contact  
10 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
when tabletop-mounted  
Half-sinusoidal shock, 10 ms  
Auxiliary contacts  
N/O contact  
7 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
when tabletop-mounted  
Half-sinusoidal shock, 10 ms  
Auxiliary contacts  
N/C contact  
5 g

Degree of Protection  
IP00

Protection against direct contact when actuated  
from front (EN 50274)  
Finger and back-of-hand proof

Altitude  
Max. 2000 m

Weight  
DC operated  
2.27 kg

Screw connector terminals  
Terminal capacity main cable  
Flexible with ferrule  
1 x (10 - 95)  
2 x (10 - 70) mm<sup>2</sup>

Screw connector terminals  
Terminal capacity main cable  
Stranded  
1 x (16 - 95)  
2 x (16 - 70) mm<sup>2</sup>

Screw connector terminals  
Terminal capacity main cable  
Solid or stranded  
single 8...3/0, double 8...2/0 AWG

Screw connector terminals  
Terminal capacity main cable  
Flat conductor [Lamellenzahl x Breite x Dicke ]  
2 x (6 x 16 x 0.8) mm

Screw connector terminals  
Terminal capacity main cable  
Stripping length  
24 mm

Screw connector terminals  
Terminal capacity main cable  
Terminal screw  
M10

Screw connector terminals  
Terminal capacity main cable  
Tightening torque  
14 Nm

Screw connector terminals  
Terminal capacity main cable  
Tool  
Hexagon socket-head spanner [SW]  
5 mm

Spring-loaded terminal connection  
Terminal capacity main cable  
Solid  
1 x (0.75 - 2.5) mm<sup>2</sup>

Spring-loaded terminal connection  
Terminal capacity main cable

flexible  
1 x (0.75 - 2.5) mm<sup>2</sup>

Spring-loaded terminal connection  
Terminal capacity main cable  
flexible with ferrules  
1 x (0.75 - 1.5) mm<sup>2</sup>

Spring-loaded terminal connection  
Terminal capacity control circuit cables  
Flexible  
1 x (0.75 - 2.5)  
2 x (0.75 - 2.5) mm<sup>2</sup>

Spring-loaded terminal connection  
Terminal capacity control circuit cables  
Flexible with ferrule  
1 x (0.75 - 1.5)  
2 x (0.75 - 1.5) mm<sup>2</sup>

Spring-loaded terminal connection  
Terminal capacity control circuit cables  
Solid or stranded  
18 - 14 AWG

Spring-loaded terminal connection  
Terminal capacity control circuit cables  
Stripping length  
10 mm

Spring-loaded terminal connection  
Tool  
Screwdriver blade width  
3.5 mm

## Main conducting paths

Rated impulse withstand voltage [U<sub>imp</sub>]  
8000 V AC

Overvoltage category/pollution degree  
III/3

Rated insulation voltage [U<sub>i</sub>]  
690 V AC

Rated operational voltage [U<sub>e</sub>]  
690 V AC

Safe isolation to EN61140  
between coil and contacts  
690 V AC

Safe isolation to EN61140  
between the contacts  
690 V AC

Making capacity (p.f. to IEC/EN 60947) [Up to 690 V]  
2100 A

Breaking capacity  
220 V 230 V  
1500 A

Breaking capacity  
380 V 400 V  
1500 A

Breaking capacity  
500 V  
1500 A

Breaking capacity  
660 V 690 V  
1200 A

Short-circuit rating  
Short-circuit protection maximum fuse  
Type "2" coordination  
400 V [gG/gL 500 V]  
250 A

Short-circuit rating  
Short-circuit protection maximum fuse  
Type "2" coordination  
690 V [gG/gL 690 V]  
250 A

Short-circuit rating  
Short-circuit protection maximum fuse  
Type "1" coordination  
400 V [gG/gL 500 V]  
250 A

Short-circuit rating  
Short-circuit protection maximum fuse



Type "1" coordination  
690 V [gG/gL 690 V]  
250 A

## AC

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 40 °C [ $I_{th} = I_e$ ]  
190 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 50 °C [ $I_{th} = I_e$ ]  
180 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 55 °C [ $I_{th} = I_e$ ]  
170 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 60 °C [ $I_{th} = I_e$ ]  
160 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
enclosed [ $I_{th}$ ]  
144 A

AC-1  
Rated operational current  
Conventional free air thermal current, 1 pole  
open [ $I_{th}$ ]  
400 A

AC-1  
Rated operational current

Conventional free air thermal current, 1 pole  
enclosed [ $I_{th}$ ]  
360 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
Notes  
At maximum permissible ambient temperature  
(open.)  
Also tested according to AC-3e.

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
220 V 230 V [ $I_e$ ]  
150 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
240 V [ $I_e$ ]  
150 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
380 V 400 V [ $I_e$ ]  
150 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
415 V [ $I_e$ ]  
150 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
440V [ $I_e$ ]  
150 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
500 V [ $I_e$ ]  
150 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
660 V 690 V [ $I_e$ ]  
100 A

AC-3  
Motor rating [P]  
220 V 230 V [P]  
48 kW

AC-3  
Motor rating [P]  
240V [P]  
52 kW

AC-3  
Motor rating [P]  
380 V 400 V [P]  
75 kW

AC-3  
Motor rating [P]  
415 V [P]  
91 kW

AC-3  
Motor rating [P]  
440 V [P]  
95 kW

AC-3  
Motor rating [P]  
500 V [P]  
110 kW

AC-3  
Motor rating [P]  
660 V 690 V [P]  
96 kW

AC-4  
Open, 3-pole: 50 – 60 Hz  
220 V 230 V [I<sub>e</sub>]  
65 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
240 V [I<sub>e</sub>]  
65 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
380 V 400 V [I<sub>e</sub>]  
65 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
415 V [ $I_e$ ]  
65 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
440 V [ $I_e$ ]  
65 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
500 V [ $I_e$ ]  
65 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
660 V 690 V [ $I_e$ ]  
50 A

AC-4  
Mtor rating [ $P$ ]  
220 V 230 V [ $P$ ]  
20 kW

AC-4  
Mtor rating [ $P$ ]  
240 V [ $P$ ]  
22 kW

AC-4  
Mtor rating [ $P$ ]  
380 V 400 V [ $P$ ]  
33 kW

AC-4  
Mtor rating [ $P$ ]  
415 V [ $P$ ]  
39 kW

AC-4  
Mtor rating [ $P$ ]  
440 V [ $P$ ]  
41 kW

AC-4  
Mtor rating [ $P$ ]  
500 V [ $P$ ]  
47 kW

AC-4  
Motor rating [P]  
660 V 690 V [P]  
48 kW

## DC

Rated operational current, open  
DC-1  
60 V [ $I_e$ ]  
160 A

Rated operational current, open  
DC-1  
110 V [ $I_e$ ]  
160 A

Rated operational current, open  
DC-1  
220 V [ $I_e$ ]  
90 A

## Current heat loss

3 pole, at  $I_{th}$  (60°)  
36.5 W

Current heat loss at  $I_e$  to AC-3/400 V  
32.1 W

Impedance per pole  
0.6 mΩ

## Magnet systems

Voltage tolerance  
DC operated [Pick-up]  
 $0.7 - 1.2 \times U_e$

Voltage tolerance  
Notes  
RDC 24 ( $U_{min}$  24 V DC/ $U_{max}$  27 V DC)  
Example:  $U_S = 0.7 \times U_{min} - 1.2 \times U_{max}$  /  $U_S = 0.7 \times$   
24V - 1.2 x 27V DC

Voltage tolerance

DC operated [Drop-out]  
0.15 - 0.6 x  $U_c$

Voltage tolerance

Notes

at least smoothed two-phase bridge rectifier or  
three-phase rectifier

Power consumption of the coil in a cold state and  
1.0 x  $U_S$   
DC operated [Pick-up]  
149 W

Power consumption of the coil in a cold state and  
1.0 x  $U_S$   
DC operated [Sealing]  
1.9 W

Duty factor  
100 % DF

Changeover time at 100 %  $U_S$  (recommended  
value)  
Main contacts  
DC operated  
Closing delay  
Closing delay  
35 ms

Changeover time at 100 %  $U_S$  (recommended  
value)  
Main contacts  
DC operated  
Opening delay  
Opening delay  
30 ms

Changeover time at 100 %  $U_S$  (recommended  
value)  
Arcing time  
15 ms

Changeover time at 100 %  $U_S$  (recommended  
value)  
Permissible residual current with actuation of A1 -  
A2 by the electronics (with 0 signal).  
□ 1 mA

## Electromagnetic compatibility (EMC)

Emitted interference  
to EN 60947-1

Interference immunity  
to EN 60947-1

### Rating data for approved types

Switching capacity  
Maximum motor rating  
Three-phase  
200 V  
208 V  
50 HP

Switching capacity  
Maximum motor rating  
Three-phase  
230 V  
240 V  
60 HP

Switching capacity  
Maximum motor rating  
Three-phase  
460 V  
480 V  
125 HP

Switching capacity  
Maximum motor rating  
Three-phase  
575 V  
600 V  
125 HP

Switching capacity  
Maximum motor rating  
Single-phase  
115 V  
120 V  
10 HP

Switching capacity  
Maximum motor rating  
Single-phase  
230 V  
240 V  
30 HP

Switching capacity  
General use  
225 A

Short Circuit Current Rating  
Basic Rating  
SCCR  
10 kA

Short Circuit Current Rating  
Basic Rating  
max. Fuse  
600 A

Short Circuit Current Rating  
Basic Rating  
max. CB  
600 A

Short Circuit Current Rating  
480 V High Fault  
SCCR (fuse)  
30/100 kA

Short Circuit Current Rating  
480 V High Fault  
max. Fuse  
300/300 Class J A

Short Circuit Current Rating  
480 V High Fault  
SCCR (CB)  
65 kA

Short Circuit Current Rating  
480 V High Fault  
max. CB  
250 A

Short Circuit Current Rating  
600 V High Fault  
SCCR (fuse)  
30/100 kA

Short Circuit Current Rating  
600 V High Fault  
max. Fuse  
300/600 Class J A



Short Circuit Current Rating  
600 V High Fault  
SCCR (CB)  
30 kA

Short Circuit Current Rating  
600 V High Fault  
max. CB  
350 A

Special Purpose Ratings  
Electrical Discharge Lamps (Ballast)  
480V 60Hz 3phase, 277V 60Hz 1phase  
160 A

Special Purpose Ratings  
Electrical Discharge Lamps (Ballast)  
600V 60Hz 3phase, 347V 60Hz 1phase  
160 A

Special Purpose Ratings  
Incandescent Lamps (Tungsten)  
480V 60Hz 3phase, 277V 60Hz 1phase  
160 A

Special Purpose Ratings  
Incandescent Lamps (Tungsten)  
600V 60Hz 3phase, 347V 60Hz 1phase  
160 A

Special Purpose Ratings  
Resistance Air Heating  
480V 60Hz 3phase, 277V 60Hz 1phase  
160 A

Special Purpose Ratings  
Resistance Air Heating  
600V 60Hz 3phase, 347V 60Hz 1phase  
160 A

Special Purpose Ratings  
Refrigeration Control (CSA only)  
LRA 480V 60Hz 3phase  
540 A

Special Purpose Ratings  
Refrigeration Control (CSA only)  
FLA 480V 60Hz 3phase  
90 A

Special Purpose Ratings  
Refrigeration Control (CSA only)  
LRA 600V 60Hz 3phase  
540 A

Special Purpose Ratings  
Refrigeration Control (CSA only)  
FLA 600V 60Hz 3phase  
90 A

Special Purpose Ratings  
Definite Purpose Ratings (100,000 cycles acc. to  
UL 1995)  
LRA 480V 60Hz 3phase  
900 A

Special Purpose Ratings  
Definite Purpose Ratings (100,000 cycles acc. to  
UL 1995)  
FLA 480V 60Hz 3phase  
150 A

Special Purpose Ratings  
Elevator Control  
200V 60Hz 3phase  
30 HP

Special Purpose Ratings  
Elevator Control  
200V 60Hz 3phase  
92 A

Special Purpose Ratings  
Elevator Control  
240V 60Hz 3phase  
40 HP

Special Purpose Ratings  
Elevator Control  
240V 60Hz 3phase  
104 A

Special Purpose Ratings  
Elevator Control  
480V 60Hz 3phase  
75 HP

Special Purpose Ratings  
Elevator Control  
480V 60Hz 3phase  
96 A

Special Purpose Ratings  
Elevator Control  
600V 60Hz 3phase  
100 HP

Special Purpose Ratings  
Elevator Control  
600V 60Hz 3phase  
99 A

## DESIGN VERIFICATION AS PER IEC/EN 61439

### Technical data for design verification

Rated operational current for specified heat  
dissipation [ $I_n$ ]  
150 A

Heat dissipation per pole, current-dependent [ $P_{vid}$ ]  
10.7 W

Equipment heat dissipation, current-dependent  
[ $P_{vid}$ ]  
32.1 W

Static heat dissipation, non-current-dependent [ $P_{vs}$ ]  
1.9 W

Heat dissipation capacity [ $P_{diss}$ ]  
0 W

Operating ambient temperature min.  
-25 °C

Operating ambient temperature max.  
+60 °C

### IEC/EN 61439 design verification

10.2 Strength of materials and parts  
10.2.2 Corrosion resistance  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.1 Verification of thermal stability of enclosures  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.2 Verification of resistance of insulating materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.4 Resistance to ultra-violet (UV) radiation  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.5 Lifting  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.6 Mechanical impact  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.7 Inscriptions  
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES  
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances  
Meets the product standard's requirements.

10.5 Protection against electric shock  
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components  
Does not apply, since the entire switchgear needs

to be evaluated.

10.7 Internal electrical circuits and connections  
Is the panel builder's responsibility.

10.8 Connections for external conductors  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.2 Power-frequency electric strength  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.3 Impulse withstand voltage  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.4 Testing of enclosures made of insulating material  
Is the panel builder's responsibility.

10.10 Temperature rise  
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function  
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)

Rated control supply voltage  $U_s$  at AC 50HZ  
0 - 0 V

Rated control supply voltage  $U_s$  at AC 60HZ  
0 - 0 V

Rated control supply voltage  $U_s$  at DC  
24 - 27 V

Voltage type for actuating  
DC

Rated operation current  $I_e$  at AC-1, 400 V  
190 A

Rated operation current  $I_e$  at AC-3, 400 V  
150 A

Rated operation power at AC-3, 400 V  
75 kW

Rated operation current  $I_e$  at AC-4, 400 V  
65 A

Rated operation power at AC-4, 400 V  
33 kW

Rated operation power NEMA  
93 kW

Modular version  
No

Number of auxiliary contacts as normally open  
contact  
0

Number of auxiliary contacts as normally closed  
contact  
0

Type of electrical connection of main circuit  
Screw connection

Number of normally closed contacts as main  
contact  
0

Number of main contacts as normally open contact  
3

## APPROVALS

Product Standards  
IEC/EN 60947-4-1; UL 60947-4-1; CSA - C22.2 No.  
60947-4-1-14; CE marking

UL File No.  
E29096

UL Category Control No.  
NLDX


CSA File No.  
012528

CSA Class No.  
2411-03, 3211-04

North America Certification  
UL listed, CSA certified

Specially designed for North America  
No

## CHARACTERISTICS




## Accessories

1: Overload relay

2: Suppressor

3: Auxiliary contact modules

### Side mounting auxiliary contacts




possible variants at auxiliary contact module fitting  
options

on the side: 2 x DILMB20-XH11(V)-SI; 2 x

DILMB20-XH11-SA

### Characteristic curve



## Squirrel-cage motor

Operating characteristics

Starting: from rest

Stopping: after attaining full running speed

Electrical characteristics

Make: up to 6 x rated motor current

Break: up to 1 x rated motor current

Utilization category

100 % AC-3

Typical applications

Compressors

Lifts

Mixers

Pumps

Escalators

Agitators

Fans

Conveyor belts

Centrifuges


Hinged flaps

Bucket-elevators

Air conditioning system

General drives in manufacturing and processing  
machines

### Characteristic curve



Extreme switching duty

Squirrel-cage motor



Operating characteristics  
 Inching, plugging, reversing  
 Electrical characteristics  
 Make: up to 6 x rated motor current  
 Break: up to 6 x rated motor current  
 Utilization category  
 100 % AC-4  
 Typical applications  
 Printing presses  
 Wire-drawing machines  
 Centrifuges  
 Special drives for manufacturing and processing machines

Characteristic curve



Switching conditions for non-motor consumers, 3 pole, 4 pole  
 Operating characteristics  
 Non inductive and slightly inductive loads  
 Electrical characteristics  
 Switch on: 1 x rated operational current  
 Switch off: 1 x rated operational current  
 Utilization category  
 100 % AC-1  
 Typical examples of application  
 Electric heat

Characteristic curve



## DIMENSIONS



Contactor with auxiliary contact module



distance at side to earthed parts: 10 mm

DILM80...DILM170

