

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English




DILM32-XSP(RDC24) - Replacement coil, Tool-less plug connection, RDC 24: 24 - 27 V DC, DC, For use with: DILM17, DILM25, DILM32, DILM38, DILMP32 - DILMP45



281155 DILM32-XSP(RDC24)

[Overview](#) [Specifications](#) [Resources](#)



- [Delivery program](#)
- [Design verification as per IEC/EN 61439](#)
- [Technical data ETIM 7.0](#)
- [Approvals](#)

281155 DILM32-XSP(RDC24)

Replacement coil, Tool-less plug connection, RDC 24: 24 - 27 V DC, DC, For use with: DILM17, DILM25, DILM32, DILM38, DILMP32 - DILMP45

Alternate Catalog No.

XTCERENCOILCTD

EL-Nummer (Norway)

4130506

Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: RDC 24: 24 - 27 V DC, Voltage AC/DC: DC, For use with: DILM17, DILM25, DILM32, DILM38, DILMP32 - DILMP45, DILM17 - DILM38

Delivery program

Actuating voltage

RDC 24: 24 - 27 V DC

Voltage AC/DC

DC

For use with

DILM17

DILM25

DILM32

DILM38

DILMP32 - DILMP45

For use with

DILM17 - DILM38

Design verification as per IEC/EN 61439

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+60 °C

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Coil for relay (EC001043)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (ecl@ss10.0.1-27-37-10-12 [AKF021013])

Rated control supply voltage U_s at AC 50Hz
0 - 0 V
Rated control supply voltage U_s at AC 60Hz
0 - 0 V
Rated control supply voltage U_s at DC
24 - 27 V
Voltage type for actuating
DC

Approvals

Product Standards
IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05; CE marking
UL File No.
E29096
UL Category Control No.
NLDX
CSA File No.
012528
CSA Class No.
2411-03, 3211-04
North America Certification
UL listed, CSA certified
Specially designed for North America
No

Additional product information

- [Motor starters and "Special Purpose Ratings" for the North American market](#)
(PDF)
- [Switchgear of Power Factor Correction Systems](#)
(PDF)
- [X-Start - Modern Switching Installations Efficiently Fitted and Wired Securely](#)
(PDF)
- [Mirror Contacts for Highly-Reliable Information Relating to Safety-Related Control Functions](#)
(PDF)
- [Effect of the Cable Capacitance of Long Control Cables on the Actuation of Contactors](#)
(PDF)
- [Switchgear for Luminaires](#)
(PDF)
- [Standard Compliant and Functionally Safe Engineering Design with Mechanical Auxiliary Contacts](#)
(PDF)
- [The Interaction of Contactors with PLCs](#)
(PDF)
- [Busbar Component Adapters for modern Industrial control panels](#)
(PDF)


Product photo



2100PIC-47

Photo
Individual coil

3D drawing



2100DRV-102

Line drawing
Individual coil

Standards

-  **xStart**
000Z153
Logo
xStart logo

Instruction Leaflet

- Coil exchange: DILM17 to DILM38, DILMP32 to DILMP45 (IL03407036Z)
Asset
(PDF, multilingual)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

